



Productivity Inc[®]

Haas CNC Lathe: ST-30SSY



Machine shown with optional equipment

For reference only. Please request an official quotation.

STANDARD MACHINE FEATURES, ST-30SSY:

- Cutting Capacity 16" x 23" (406 mm x 584 mm)
- 31.75" (806 mm) Swing
- Heavy-Duty Sheet metal Enclosure
- 24-Position Hybrid Turret
- Spindle Speed 4500 rpm
- Chuck Size 10" (254 mm)
- 55-Gallon Coolant Tank
- Rigid Tapping
- Flood Coolant System
- 30 hp (22 kW) Spindle
- Automatic Lubrication System
- Tool Load Monitoring
- USB port
- Brushless Motors
- High-Torque Live Tooling with C Axis
- Spindle Orientation
- 1-Year Parts and Labor Warranty

Other Features Include:

- Embedded coolant collection tray
- High-precision spindle
- Rigid tapping
- Direct-coupled servo motors
- Massive ribbed castings
- Double wall safety door

HAAS ST-30SSY CNC LATHE

16" x 23" (406 x 584 mm) max capacity, 31.75" (806 mm) swing, $\pm 2.00"$ (± 50.8 mm) Y axis travel, 30 hp (22.4 kW) vector drive, 4500 rpm, A2-6 spindle, 10" (254 mm) chuck, 24-station hybrid turret (12 VDI / 12 BOT), high-torque live tooling w/C-axis, 15" color LCD monitor, memory lock keyswitch, spindle orientation, USB port and rigid tapping. Includes standard toolholder kit

(05/13)

Options Included:

300 PSI High Pressure Coolant, Auxillary Coolant Filter, Auto Door, Programmable Tailstock, 8 spare M functions