

NORTON

SAINT-GOBAIN

clipper[®]

DIAMOND, ABRASIVES, AND EQUIPMENT PRODUCTS FOR THE
**CONSTRUCTION
DISTRIBUTION MARKET**



REDEFINING
JOBSITE MUSCLE[™]


SAINT-GOBAIN



Transforming
surfaces
...and beyond

Our Expertise

Norton Clipper is your one reliable source for all of your cutting, grinding, and drilling jobsite solutions for the construction market.

For over 135 years, the Norton brand has been a leader in product innovation in cutting and grinding applications. The Clipper brand has been a trusted equipment source on the jobsite since the first masonry saw was invented in 1937. We have taken the core strengths of both brands and merged them into an even stronger entity so that we deliver a unified product offering with the name that can be trusted for quality, durability, speed, life and value.

Norton Clipper boasts the widest range of diamond tools for cutting the most common surfaces: reinforced concrete, asphalt, granite, tile, stone, and steel. Norton Clipper is also well known for supplying high performance machines including: high-speed, walk-behind, masonry, tile and core drilling equipment. Whatever your job requires, we can offer you a leading product line of diamond, abrasives and light equipment for the concrete, construction and rental market with the relentless performance you've come to expect.

Our Mission

We offer powerful, precise, user-friendly solutions, which enable our customers to cut, grind, drill and finish all materials even in the most complex and challenging applications. By working closely with end-users and our construction expert partners, we design and provide customized solutions to secure the best option for performance, cost and safety.

Why Tiers Matter

At Norton Clipper we believe in delivering right choices that matter. Our diamond blades and abrasives are classified in GOOD, BETTER, and BEST performance/price tiers to help you choose the right product for your specific application every time.

If you need help determining the right tier for your specific needs, don't hesitate to contact us directly or reach out to your Norton Clipper sales representative.

Go Further

Visit our website at www.nortonabrasives.com for a more comprehensive outline of products, safety and application information. We continually update it with our most current information.

Connect with us:



GENERAL INFORMATION

About Norton Clipper	2
Quick-Reference	4
What's New	6
Product Selection Guide	8
Leadership	127
Website	128
Trademarks	128

ABRASIVES

Cut-off Wheels	11
High-Speed Cut-off Wheels	14
Universal Arbor	15
Grinding Wheels	16
Fiber and Flap Discs	17
Non-Woven	18
Wheels and Wire Brushes	19

HIGH-SPEED SAWS AND BLADES

Range Overview	21
CP500 Series Cut-off Saws	22
CE414 Cut-off Saw	24
Speedy Cart	26
High-Speed iHD Diamond Blades	27
High-Speed Diamond Blades	28

WALK-BEHIND SAWS AND BLADES

Range Overview	33
20HP Gas Mid-Range Self-Propelled	34
13/14HP Gas Mid-Range Self-Propelled Saws	36
C1320P/C1420P Gas Mid-Range Push Saw	38
C1318P/C1418P Gas Small Push Saw	40
C13PE/C14PEK Gas Small Push Saw	42
C914P Compact Push Saw	44
GC55 Early-Entry/Green Small Push Saws	46
GC55VAC Early-Entry/Green Small Push Saws	48
Walk-Behind Diamond Blades	50

MASONRY SAWS AND BLADES

Range Overview	55
BBL Blockbuster Large - Electric	56
BBL Blockbuster Large - Gas	58
BBC Blockbuster Compact - Electric	60
BBC Blockbuster Compact - Gas	62
BBM307 Blockbuster Mini	64
BBM158 Blockbuster Mini	66
CST Series Masonry/Stone/Tile Saws	68
Masonry Diamond Blades	70

TILE SAWS AND BLADES

Range Overview	77
CTC1020XL Tile Saw	78
CTC705 Tile Saw	80
Tile Diamond Blades	82

PORTABLE HAND-HELD BLADES

Diamond and Abrasive Blades For Cordless Tools	88
Diamond Blades	89
Diamond Cup Grinders	93
Vacuum Shroud Kit	95

CORE DRILLS, CORE BITS, AND ACCESSORIES

Range Overview	97
DR520 and DR620 Core Drill Rigs	98
HDR600C Hand-Held	100
HHD3TOL Hand-Held	101
HHDETOL Hand-Held	102
HHDET1800 Hand-Held	103
Accessories and Extensions	104
Core Bits	106

MERCHANDISING

Point-of-Purchase Displays	111
Point-of-Purchase Signage	116
Point-of-Purchase Packaging	127

SAFETY

Guidelines for Safety Use	118
Breakages/Personal Injury	119
Safe Operating Practices	119
Safety Icons	120
Silica Dust	121
Technical Information	122
Cutting Depths / Operating Speeds	125
Extension Cord Recommendations	126



Abrasive Products



Cut-Off Wheels

Page 11



Flap Discs

Page 17



Grinding Wheels

Page 16



High-Speed
Cut-Off Wheels

Page 14



Non-Woven Discs

Page 18



Wire Brushes

Page 19

Premium Diamond Products



4X4 MaxCut

Page 28



DUO Asphalt

Page 30



DUO EVO

Page 29



GMAX

Page 51



Silencio

Page 71



4X4

Page 28



Aero-Jet

Page 30



DUO

Page 29



DUO Abrasive

Page 30



DUO Small
Diameter

Page 89



Paradigm

Page 53




Rescue Runner

Page 32



Paradigm

Page 107



iHD Cup Grinders

Page 93

High-Speed Saws



CP500 Gas
Cut-Off Saws

Page 22



CE414-350SS Electric
Cut-Off Saws

Page 24



Speedy Cart
High-Speed Saw Cart

Page 26

Walk-Behind Saws



20HP Gasoline
Mid-Range
Self-Propelled Saws
Page 34



13/14HP Gas Mid-
Range Self-Propelled
Saws
Page 36



C1320P/C1420P
Gasoline
Small Push Saws
Page 38



C1318P/C1418P Gas
Small Push Saw
Page 40



C13PE/C14PEK Gas
Small Push Saw
Page 42



C914P Compact
Push Saw
Page 44



GC55 Early-Entry/Green
Small Push Saws
Page 46



GC55VAC Early-Entry/
Green Small Push Saws
Page 48

Masonry Saws



BBL Blockbuster Large
Masonry Saws
Page 56



BBC Blockbuster
Compact Masonry Saws
Page 60



BBM Blockbuster Mini
Masonry Saws
Page 64



CST Series Masonry,
Stone, Tile Saws
Page 68

Tile Saws



CTC1020XL
Tile Saw
Page 78



CTC705
Tile Saw
Page 80

Core Drills



DR520/620
Core Drill Rigs
Page 98



HDR600C
Hand-Held Core Drill
Page 100



HHD3TOL
Hand-Held Core Drill
Page 101



HHDETOL
Hand-Held Core Drill
Page 102



HHDET1800
Hand-Held Core Drill
Page 103

Whether you are looking to expand your rental fleet with rugged, reliable equipment, or grow your walk-in consumable sales, Norton Clipper can help. We have expanded our portfolio with new high-quality products to complement our existing offering you've come to know and trust. We will continue to deliver product innovation that makes Norton Clipper the single source supplier for all of your rental and construction needs.

We look forward to showing you how Norton Clipper is REDEFINING JOBSITE MUSCLE.

Equipment

C914P

Bridging the gap between the GC55 and reliable 13HP walk-behind saw range.



KOHLER ENGINES

We are excited to expand our partnership with KOHLER on our gas walk-behind saw line. KOHLER is an industry leader and trusted engine supplier for almost 100 years.



SPEEDY CART

Convert your hand-held high-speed saw to a walk-behind saw. The last cart needed to get the job done.



CE414-350SS

The electric high-speed cut-off saw that redefines jobsite muscle with power, performance, durability and innovation.



GC55VAC

The best early entry saw just got better with a vacuum attachment option.



CST SERIES

The missing link between long tiles saws and powerful masonry saws.



Diamond Blades

High-Speed - Multi-Cut for Multiple Materials

Premium features combined with low pricing make for a reliable, fast cutting, long life blade for a variety of common construction materials.

High-Speed - ValuPlus for Abrasive Materials

Ideal for residential contractors, priced competitively and designed to perform in abrasive materials either wet or dry.

Walk-Behind - Classic 18" & 20"

Designed to handle all of the material applications of the small walk-behind saw without breaking the bank.

Masonry - Silencio Charger

Easy on the ears and the wallet. A more economical quiet sandwich core is the perfect solution when cutting in sound sensitive work areas.

Tile - Slicer Turbo Mesh

The unique mesh segment is designed for fast cutting and minimal chipping on extra hard ceramics, porcelain and other hard/dense materials. Available in 14" down to 4 1/2".

Portable – 9" blades for cordless power tools

Make your battery tool more versatile. This new product offering is designed to enhance the productivity of the 9" cordless portable saw.



Abrasives















Charger Chop Saw Wheel

New and improved with increased performance and STUD cutting option. Your better choice when performance counts.



Performance Quality Tiers

Within the Norton Clipper diamond and abrasive range, we offer a choice of performance levels, adapted to the requirements of our customers. For blades, a higher number of diamonds represent higher diamond concentration and longer product life. Each blade is clearly marked with these diamonds located underneath the product name. The color of the right half of the label also indicates the performance level as indicated below. Our abrasive products display a + symbol that represents the same tiering structure.

SUB BRAND	TIER	DIAMOND BLADES	ABRASIVE WHEELS	PERFORMANCE	LABEL COLOR
PREMIUM BLADES	Best	5     		Best Performance	Blue
CHARGER	Better	4    	4 + + + +	High Performance	Gray
CLASSIC	Good	3   	3 + + +	Good Performance	Black
VALUPLUS	Value	2  		Consistent Performance	White

Blotter Examples:
Abrasive Wheels

Blotter Examples:
Diamond Blades



Types of Diamond Blades



Segmented Rim

- Most aggressive cutting action for use on the widest variety of materials.
- Typically used on high-speed, walk-behind and masonry saw blades.
- Gullets (space between segments) are designed for specific applications.



Turbo Rim

- Aggressive cutting action with a smoother quality of cut.
- For use on harder materials such as granite, marble, and stone, to reduce chipping.



Continuous Rim

- Provides the smoothest of cuts.
- For use on porcelain, ceramic tile, marble, and other hard materials requiring a high quality cut.

In addition to the easily identifiable performance quality tiers, Norton Clipper packaging helps you select the correct product for your application by simply answering these 5 questions.

How to Choose the Right Diamond Blade

- 1** How deep is the cut? **BLADE DIAMETER**
(Refer to cutting depth charts beginning on page 127)
- 2** What are you cutting? **APPLICATION**
(Refer to application chart on catalog back cover)
- 3** Is the cutting application wet or dry? **WATER SYMBOL**
- 4** What type of saw (horsepower)? **MACHINE PICTURE**
- 5** How big is the job? **PERFORMANCE QUALITY TIER**
(Refer to chart on page 8)



**HOW DEEP
IS THE CUT?**
BLADE DIAMETER



**WHAT ARE
YOU CUTTING?**
APPLICATION / COLOR CODE



**IS APPLICATION
WET OR DRY?**
WET OR DRY SYMBOLS



**HOW MUCH
HORSEPOWER?**
TYPE OF MACHINE



**HOW BIG
IS THE JOB?**
PERFORMANCE QUALITY

How to Choose the Right Abrasive Product

- 1** What tool are you using? **ABRASIVE SIZE**
(Refer to icon on label to match with your tool size and tool speed)
- 2** What are you cutting or grinding? **MATERIAL TYPE**
(Color-coded by material to be cut or ground)
- 3** What abrasive product do you need? **APPLICATION**
- 4** How big is the job? **PERFORMANCE QUALITY TIER**
- 5** How to keep safe? **IDENTIFY WARNING SYMBOLS**



NORTON

SAINT-GOBAIN

clipper®

ABRASIVES LINE

Wheels, Discs, Non-Woven, Wire Brushes



CUTTING & GRINDING JOBSITE SOLUTIONS

RUGGED – Continually attuned to the market needs since our invention of the first masonry saw to today's leadership in noise-dampening steel cores, universal arbors, and grain technologies delivers innovation to help you succeed.

RELIABLE – Combining the rich history of Clipper into the Norton family brings a single source supplier to the construction market with the high-quality and product performance you can trust to get you on and off the job quickly. Better tier = Charger. Good tier = Classic.

AFFORDABLE – Leveraging the deep knowledge base of our product and technical teams to offer right product solutions for price competitiveness that make a difference to your bottom line.

REDEFINING
JOBSITE MUSCLE™
Rugged. Reliable. Affordable.

Steel & Stainless

General purpose ferrous metals (steel, iron, welds), stainless steel and other high-strength alloys.



CIRCULAR SAW WHEELS – TYPE 01/41

CLASSIC

+++

Standard grade with good performance and life when cutting metal. Standard silicon carbide with good performance when cutting brick, block, concrete and other masonry materials.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184601484	7 x 3/32 x 5/8 Diamond	Metal / Stainless	8,730	25



Multi-Material/Multi-Purpose

Concrete, reinforced concrete, granite, building materials, thin steel sections, angle iron up to 1/2" material thickness, rebar up to no. 5.



CIRCULAR SAW WHEELS – TYPE 01/41

CLASSIC

+++

Standard grade with good performance and life when cutting metal. Standard silicon carbide with good performance when cutting brick, block, concrete and other masonry materials.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184609146	6.5 x 3/32 x 5/8 Diamond	Multi-Material	9,405	25
70184609147	7 x 3/32 x 5/8 Diamond	Multi-Material	9,405	25



Steel & Stainless

General purpose ferrous metals (steel, iron, welds), stainless steel and other high-strength alloys.



CHOP SAW WHEELS – TYPE 01/41

CHARGER

++++

Industrial performance to be used in cutting pipe, angle iron, rebar and steel studs.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184601624	14 x 3/32 x 1 Side Reinforced	STUD	4,365	10



CLASSIC

+++

Industrial performance to be used in cutting conduit, tail pipes, structural and other solid shapes.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184601477	14 x 3/32 x 1 Center Reinforced	Metal / Stainless	4,365	10
70184601478	14 x 3/32 x 1 Side Reinforced	Metal / Stainless	4,365	10



Steel & Stainless

General purpose ferrous metals (steel, iron, welds), stainless steel and other high-strength alloys.




RIGHT ANGLE CUT-OFF WHEELS – TYPE 01/41

CHARGER

++++

Durable grain for maximum productivity of 3X the life and 2X the cut rate over conventional cut-off blades. High performance.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184601460	4-1/2 x .045 x 7/8	Metal / Stainless	13,580	25
70184601462	6 x .045 x 7/8	Metal / Stainless	10,185	25



CLASSIC

+++

Industrial grade performance when cutting an array of steels and metal. Good Performance.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184601481	3 x 1/16 x 3/8	Metal / Stainless	25,465	25
70184609133	4 x .045 x 5/8	Metal / Stainless	15,280	15
70184601455	4-1/2 x .045 x 7/8	Metal / Stainless	13,580	25
70184601456	5 x .045 x 7/8	Metal / Stainless	12,225	25
70184601457	6 x .045 x 7/8	Metal / Stainless	10,185	25
70184601458	7 x 1/16 x 7/8	Metal / Stainless	8,600	25



Multi-Material/Multi-Purpose

Concrete, reinforced concrete, granite, building materials, thin steel sections, angle iron up to 1/2" material thickness, rebar up to no. 5.




RIGHT ANGLE CUT-OFF WHEELS - TYPE 01/41

CLASSIC

+++

Industrial grade performance when cutting an array of steels and metal. Good Performance.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184609135	4-1/2 x .045 x 7/8	Multi-Material	13,580	25



Steel & Stainless

General-purpose ferrous metals (steel, iron, welds), stainless steel and other high strength alloys.



ABRASIVE CUT-OFF WHEEL FOR USE ON CORDLESS POWER TOOLS ONLY



CHARGER

++++

This Norton Clipper abrasive cut-off wheel completes the 9" offering for use on cordless tools in metal applications. Thinner abrasive wheel for less drag and power draw on cordless tools. Reinforced metal arbor to enhance push and cutting speed. Cordless abrasive blend to maximize cutting speed and tool battery life.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184609080	9 x .078 x 7/8	Metal / Stainless	6,600	25



Steel & Stainless

General purpose ferrous metals (steel, iron, welds), stainless steel and other high-strength alloys.



RIGHT ANGLE CUT-OFF WHEELS – TYPE 27/42

CHARGER

++++

Durable grain for maximum productivity of 3X the life and 2X the cut rate over conventional cut-off blades. High performance.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184601470	4-1/2 x .045 x 7/8	Metal / Stainless	13,580	25
70184601474	6 x .045 x 7/8	Metal / Stainless	10,185	25



CLASSIC

+++

Industrial grade performance when cutting an array of steels and metal. Good Performance.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184601464	4 x .045 x 5/8	Metal / Stainless	15,280	25
70184601465	4-1/2 x .045 x 7/8	Metal / Stainless	13,580	25
70184601466	5 x .045 x 7/8	Metal / Stainless	12,225	25
70184601467	6 x .045 x 7/8	Metal / Stainless	10,185	25
70184601468	7 x .045 x 7/8	Metal / Stainless	8,600	25



Multi-Purpose

Concrete, reinforced concrete, granite, building materials, thin steel sections, angle iron up to 1/2" material thickness, rebar up to no. 5.



REINFORCED CUT-OFF WHEELS

CHARGER

++++

High-performance aluminum oxide grain wheels designed for general purpose cutting of all steel and stainless applications. Triple reinforcement ensures longer life and smoother cutting.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184601618	12 x 1/8 x 20mm	Concrete	6,300	10
70184601620	12 x 1/8 x 20mm	Asphalt	6,300	10
70184601496	12 x 1/8 x 1"/20mm	Concrete	6,300	10
70184601619	12 x 1/8 x 20mm	Metal / Stainless	6,300	10
70184601623	14 x 1/8 x 20mm	Asphalt	5,400	10
70184601621	14 x 1/8 x 20mm	Concrete	5,400	10
70184601500	14 x 1/8 x 1"/20mm	Metal / Stainless	5,400	10
70184601622	14 x 1/8 x 20mm	Metal / Stainless	5,400	10



CLASSIC

+++

For metal and steel cutting application, including rebar, steel pipe, structural steel, sheet metal, cable and small to medium diameter solid pieces.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184601489	12 x 1/8 x 1"/20mm	Metal / Stainless	6,300	10
70184601491	14 x 1/8 x 1"/20mm	Concrete	5,400	10
70184601492	14 x 1/8 x 1"/20mm	Ductile	5,400	10
70184601493	14 x 1/8 x 1"/20mm	Metal / Stainless	5,400	10




NEW & IMPROVED CLASSIC METAL!

Achieve market-leading cutting speeds with the new and improved design of the Norton Classic Metal abrasive wheel. The new advanced alumina grain blend has more cutting points per area, offering 50% faster cut rate and a new proprietary tough bond technology offers twice the life and aggressive cutting action.



you talked WE LISTENED

In an effort to help you and your customers more easily identify the right high-speed abrasive wheel for the specific application, we have improved our packaging labels for enhanced application visibility. A color-coded pictogram is prominently displayed on the packaging to ensure the right product is selected every time!





knock out **THE COMPETITION**

Our first to market 1"/20mm knock-out arbor fits all gas and electric high speed saws. A 20mm bushing is pre-mounted into the 1" molded arbor hole. The wheel, with the 20mm bushing, can be mounted directly on any 20mm arbor high speed saw. With the bushing removed, exposing the 1" arbor hole, the wheel can be mounted on any 1" arbor high speed saw. Combining this arbor, with heavy-duty triple reinforcing results in a higher performing, extra strong, longer lasting cutting wheel.

* Once the 20mm bushing is removed, it cannot be replaced.



Universal Arbor

The Norton universal arbor allows the abrasive blade to be used on either a 1" or 20mm high-speed gas or electric cut-off saw. Also reduces inventory.



Reinforcement Options

Metal, ductile, and concrete blades all have options with triple reinforcement adding to life and a smoother cut.



High-Performance Grain

Infused with grain technology, where necessary, to offer performance advantages where it counts.

Steel & Stainless

General purpose ferrous metals (steel, iron, welds), stainless steel and other high-strength alloys.



GRINDING WHEELS – TYPE 27

CLASSIC

+++

Industrial grade performance when grinding an array of metals and steels. Exceptional life and cut rate on carbon and stainless steel. Good performance.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184601502	4-1/2 x 1/4 x 5/8-11	Concrete	13,580	10
70184601503	4-1/2 x 1/4 x 5/8-11	Metal / Stainless	13,580	10
70184601505	4-1/2 x 1/4 x 7/8	Metal / Stainless	13,580	25
70184601507	5 x 1/4 x 7/8	Metal / Stainless	12,225	25
70184601528	5 x 1/8 x 7/8	Metal / Stainless	12,225	25
70184601509	6 x 1/4 x 7/8	Metal / Stainless	10,185	25
70184601510	7 x 1/4 x 5/8-11	Metal / Stainless	8,600	25



Multi-Material/Multi-Purpose

Concrete, reinforced concrete, granite, building materials, thin steel sections, angle iron up to 1/2" material thickness, rebar up to no. 5.



CLASSIC DEPRESSED CENTER GRINDING WHEELS - TYPE 27

CLASSIC

+++

Industrial grade performance when cutting an array of steels and metal. Good Performance.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184609140	4 x 1/8 x 5/8	Multi-Material	15,280	25
70184609141	4 x 1/4 x 5/8	Multi-Material	15,280	25
70184609142	4 1/2 x 1/8 x 5/8-11	Multi-Material	13,580	10
70184609143	4 1/2 x 1/4 x 5/8-11	Multi-Material	13,580	10
70184609144	5 x 1/4 x 5/8-11	Multi-Material	12,225	10
70184609145	7 x 1/4 x 5/8-11	Multi-Material	8,600	10



Steel & Stainless

General purpose ferrous metals (steel, iron, welds), stainless steel and other high-strength alloys.



CLASSIC FIBER DISCS – UPC BARCODED

CLASSIC

+++

Good choice for steel/ferrous metal and masonry applications with low initial price.

UPC	SIZE	GRIT / GRADE	STD PKG
076607 68187	4 1/2 x 7/8	16	25
076607 02048	4 1/2 x 7/8	24	25
076607 02047	4 1/2 x 7/8	36	25
076607 02046	4 1/2 x 7/8	50	25
076607 68186	4 1/2 x 7/8	60	25
076607 02045	4 1/2 x 7/8	80	25
076607 01915	5 x 7/8	16	25
076607 01911	5 x 7/8	24	25
076607 01910	5 x 7/8	36	25
076607 01909	5 x 7/8	50	25
076607 68189	5 x 7/8	60	25
076607 68188	5 x 7/8	80	25
076607 01916	7 x 7/8	16	25
076607 01914	7 x 7/8	24	25
076607 01913	7 x 7/8	36	25
076607 01912	7 x 7/8	50	25
076607 68190	7 x 7/8	60	25



CLASSIC FLAP DISCS – UPC BARCODED

CLASSIC - RETAIL PACK

+++

Good choice for steel/ferrous metal and masonry applications with low initial price.

UPC	SIZE	GRIT / GRADE	STD PKG
701846 09163	4 1/2 x 5/8-11	40	5
701846 09164	4 1/2 x 5/8-11	60	5
701846 09165	4 1/2 x 5/8-11	80	5
701846 09166	7 x 5/8-11	40	5
701846 09167	7 x 5/8-11	60	5
701846 09168	7 x 5/8-11	80	5



Multi-Purpose, All Materials

Concrete, reinforced concrete, granite, building materials, thin steel sections, angle iron up to 1/2" material thickness, rebar up to no. 5.



RAPID STRIP DISCS - TYPE 27

CLASSIC

An open web of thick, strong, synthetic fibers and extra coarse, smear free abrasive. For cleaning and conditioning of multitude of materials, quickly and easily with very little loading. Perfect for removal of rust, residue and paint.

UPC	SIZE	GRIT / GRADE	STD PKG
70184601594	4-1/2 x 5/8-11	Ex. Coarse	10
70184601595	4-1/2 x 7/8	Ex. Coarse	10



Multi-Purpose, All Materials

Concrete, reinforced concrete, granite, building materials, thin steel sections, angle iron up to 1/2" material thickness, rebar up to no. 5.



CUP WHEELS - TYPE 11

CLASSIC

+++

Type 11 shape for maximum surface grinding coverage. For heavy stock removal and beveling applications on all types of metal materials.

UPC	SIZE	GRIT	GRAIN	STD PKG
70184601607	4 / 3 x 2 x 5/8-11	16	AO	10
70184601608	5 / 3-3/4 x 2 x 5/8-11	16	AO	5
70184601609	6 / 4-3/4 x 2 x 5/8-11	16	AO	5



WIRE CUP BRUSHES

CLASSIC - RETAIL PACK

+++

High performance cable crimped cups provide up to 50% longer life and better flexibility on irregular surfaces.

UPC	DESCRIPTION	SIZE	APPLICATION	MAX RPM	STD PKG
70184609149	Knotted Cup	3 x .020 x 5/8-11	Carbon	14,000	1/4
70184609150	Knotted Cup	4 x .020 x 5/8-11	Stainless	14,000	1/4
70184609151	Crimped Cup	3 x .014 x 5/8-11	Carbon	14,000	1/4
70184609152	Crimped Cup	3 x .014 x Drill 1/4	Brass	4,500	1/6



WIRE WHEELS & BRUSHES

CLASSIC - BULK PACK

+++

Narrow face stringer bead wire deliver high impact cutting and cleaning for the toughest applications. Specially suited for groove and weld bead, corners and t-connections. Large wire wheels clean concrete and asphalt joints and cracks quickly and efficiently before filling or scaling.

UPC	DESCRIPTION	SIZE	APPLICATION	MAX RPM	STD PKG
70184601615	Standard Twist Knot	4 x .020 x 5/8-11	Carbon	20,000	6
70184601616	Stringer Bead Knot	4 x .020 x 5/8-11	Carbon	20,000	6
70184601617	Joint/Crack Cleaning	12 x .035 x 1 - DP	Carbon	4,500	2



UPC	DESCRIPTION	SIZE	APPLICATION	MAX RPM	STD PKG
70184609153	Knotted Wire Wheel Brush	4 x .020 x 5/8-11	Stainless	20,000	1/5
70184609154	Knotted Wire Wheel Brush	4 x .020 x 5/8-11	Carbon	20,000	1/5
70184609155	Coarse Wire Wheel	4 x .012 x Drill 1/4	Carbon	4,500	1/6
70184609156	Coarse Wire Wheel	3 x .012 x Drill 1/4	Brass	4,500	1/6
70184609159	Wire Crimped Brush	2 x .012 x Drill 1/4	Brass	4,500	1/6
70184609160	Coarse Wire Wheel Brush	2 x .012 x Drill 1/4	Brass	4,500	1/6
70184609161	Coarse Wire Wheel Brush	6 x .012 x Fits 1/2 & 5/8 Arbor	Brass	4,500	1/5
70184609162	Wire Brush	8 x .012 x Fits 1/2 & 5/8 Arbor	Brass	3,750	1/5

WIRE BENCH WHEELS

CLASSIC - RETAIL PACK

+++

High performance cable crimped bench wheels provide up to 50% longer life and better flexibility on irregular surfaces.

UPC	DESCRIPTION	SIZE	APPLICATION	MAX RPM	STD PKG
70184601614	Wire Bench Wheel	6 x .014 x 1/2-2 Arbor	Carbon	6,000	1



WIRE END BRUSHES

CLASSIC - RETAIL PACK

+++

Wire shank end brushes are ideal for work on irregular surfaces, finer surface finishing, and light-to medium-duty contaminant removal applications.

UPC	DESCRIPTION	SIZE	APPLICATION	MAX RPM	STD PKG
70184609157	Coarse Wire End Brush	1 x .012 x Drill 1/4	Brass	4,500	6/1
70184609158	Wire End Brush - 6 pack	1 x .012 x Drill 1/4	Brass	4,500	6/5



[illegible]



RANGE OVERVIEW



MODEL#

CP514-350

CP514-350i

CE414-350SS

UPC#

70184647563

70184647565

70184694536

**MAXIMUM DEPTH
OF CUT**

5"
(125mm)


5"
(125mm)

**MAXIMUM
HORSEPOWER**

5.4 HP (4.0 kW)

4.2 HP (3.1 kW)

PRODUCT FEATURES




No More Pre-Mixing Oil and Fuel

The patented iLube® option automatically controls mixing of oil and fuel for maximum efficiency. An electronic sensor will indicate a low oil level and adjust the engine to idle to prevent engine damage.



Easy Start – Hot or Cold

The electronic carburetor's electromagnetic valve eliminates the standard choke and half throttle start. The 4-step easy start eliminates the hassle of a choke. Simply turn the switch on, prime the engine, and push the decompression button, then pull the cord to start.



Multi-Stage Air Filtration

Patented twin-air inlets create an air pulsation that draws fresh air in while pushing dust away from the engine and releasing it out the back to keep the saw running clean and reduce debris being trapped in the filter. The external rocker wheel vibrates the filter to further help release debris. This system extends filter life for less cleaning/replacement.



The CP500 high-speed cut-off saw is destined to be an asset on any crew. It's fully designed with the user in mind to not only cut a smooth, fast track, but it's also fully equipped to handle the everyday performance of any jobsite with unrelenting durability and reliability. Select a standard model or upgrade to the world's first patented automatic lubrication system, iLube®.

TECHNICAL SPECIFICATIONS

PRODUCT #	CP514-350	CP514-350i
UPC	701846 47563	701846 47565
Blade Guard Capacity - in (mm)	14" (356)	14" (356)
Maximum Depth of Cut - in (mm)	5" (125)	5" (125)
Arbor Size - in (mm)	.78 (20)	.78 (20)
Blade Flange Diameter - in (mm)	3.93 (100)	3.93 (100)
Blade Shaft RPM	4,500	4,500
Blade Shaft Bearings	Heavy Duty Sealed	Heavy Duty Sealed
Blade Shaft Drive	1 Belt	1 Belt
Control	Hand Held	Hand Held
Chassis	Norton Single-Cylinder Two Stroke Engine	Norton Single-Cylinder Two Stroke Engine
Power Source	Single Cylinder 2 Cycle	Single Cylinder 2 Cycle w/Lube
Motor/Engine Type	Norton Clipper	Norton Clipper
Specifications	CP514-350	CP514-350i
Maximum Horsepower ¹	5.4 hp (4.0 kW)	5.4 hp (4.0 kW)
Net Horsepower ¹	5.4 hp (4.0 kW)	5.4 hp (4.0 kW)
Max. Torque ft lbs (Nm)	3.54 (4.8)	3.54 (4.8)
Displacement - cu In (l)	4.94 (81)	4.94 (81)
Bore - in (mm)	2.04 (52)	2.04 (52)
Stroke - in (mm)	1.49 (38)	1.49 (38)
Cylinders/Cycle	Single Cylinder 2 Cycle	Single Cylinder 2 Cycle
Fuel Capacity - gal (l)	0.23 (0.9)	0.23 (0.9)
Oil Capacity - oz (l)	-NA-	10.08 (0.32)
Electronically-Controlled Oil Lubrication	-NA-	YES
Air Filter	Heavy Duty 3 Stage	Heavy Duty 3 Stage
Starter	Manual	Manual
Engine Cooling	Forced Air	Forced Air
Electronically-Controlled Carburettor With Smart Choke	YES	YES
"Sound Level ^{2,3} L _{peg} (EN ISO 19432 Annex B) dB(A)"	98	98
Sound Power Level ^{2,3} L _{weg} (EN ISO 19432 Annex B) dB(A)	108	108
"Weighted Effective Acceleration ^{2,4} a _{hveq} (EN ISO 19432 Annex C)	4.5 / 6.0	4.5 / 6.0
Rear Handle / Top Handle m/s ² "		

SAW DIMENSIONS

Height - in (mm)	16-15/16" (430)	16-15/16" (430)
Saw Width - in (mm)	10-1/2" (267)	10-1/2" (267)
Maximum Saw Length (Working) - in (mm)	30-1/2" (775)	30-1/2" (775)
Weight - Uncrated - lbs (kg)	22.49 (10.2)	23.15 (10.5)

ACCESSORIES

	UPC	SMART PART #
High-Speed Saw Wheel Kit	005101 09845	510109845
High-Speed Saw Tool Kit	005101 09846	510109846
High-Speed Saw Service Kit	701846 32294	701846 32294
Includes: one each of the following: belt, air filter, spark plug, start rope w/ grip, decompression valve, hose kit (fuel vent, primer bulb, fuel hoses), and five (5) secondary air filter screens.		
2.64 Gallon Pressure Water Tank – Metal (Manual Pump, 8ft (2.5m) with Quick Detach Fittings)	003104 64031	310464031
9.24 Gallon Pressure Water Tank – Plastic (Electric pump, automatic shut off, 34ft (10.4m) hose)	701846 02829	233936

1. DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER
2. IN DETERMINING THE ABOVE VALUES REGARDING ACCELERATION OF VIBRATIONS AND SOUND, THE DIFFERENT OPERATING CONDITIONS WERE WEIGHED IN ACCORDANCE WITH THE CURRENT STANDARDS
3. INSECURITY K PURS. TO EC DIRECTIVE 2006/42/EC: 2.5 DB(A)
4. INSECURITY K PURS. TO EC DIRECTIVE 2006/42/EC: 2 M/S²



High-Speed Saw Wheel Kit



High-Speed Saw Tool Kit



High-Speed Saw Service Kit



2.64 Gallon Pressure Water Tank



Visit our YouTube page for more product information at:
www.youtube.com/NortonAbrasives

PRODUCT FEATURES



Thermal Protection

New ultra efficient air intake system keeps the motor cool while keeping out water and dust. Light indicators show low voltage or amperage overload while electronic clutch protects motor and gear set from damage during excessive conditions. The GFCI protects operators from electric shock.



StableStart

Smoother start provides better operator control. Motor slowly builds speed during start-up preventing unintentional circuit breaker trips.



Design

Strongest motor in class with better ergonomics for easier operation in wet and dry applications, delivering versatility.



The new Norton Clipper CE414-350SS electric high-speed hand-held saw is stronger than the competition. Its powerful 4.2HP motor delivers on the jobsite with a fast cut and ease of operator use. Add on unique design features that keep your saw from motor damage or stalling out and your maintenance needs become fewer and far between. Finish with an unprecedented warranty and you'll wonder why you'd choose anything but Norton Clipper.

TECHNICAL SPECIFICATIONS

PRODUCT #		CE414-350SS
UPC		701846 94536
Blade Guard Capacity - in (mm)		14" (356)
Maximum Depth of Cut - in (mm)		5" (125)
Arbor Size - in (mm)		1" (25.4) / 0.78 (20)
Blade Flange Diameter - in (mm)		4" (100)
Blade Shaft RPM		3,800
Blade Shaft Bearings		Heavy-Duty Sealed
Blade Shaft Drive		Gear Drive
Control		Hand Held
Chassis		Electric
Power Source		115v/60/1 Electric
Motor/Engine Type		Norton Clipper
Specifications		CE414-350SS
Maximum Horsepower ¹		4.2 hp (3.1 kW)
Net Horse Power ¹		4.2 hp (3.1 kW)
Starter		Electric
Engine Cooling		Forced Air
LED Overload Indicator		Yes
IC Soft Start		Yes
Thermal Overload Protection		Yes
Cord Length - ft (m)		9.8 (3)
Clutch		Yes
SAW DIMENSIONS		
Height - in (mm)		11-1/8" (283)
Saw Width - in (mm)		11-3/8" (288)
Maximum Saw Length (Working) - in (mm)		25-1/4" (11.45)
Weight - Uncrated - lbs (kg)		25.25 (11.6)
ACCESSORIES		SMART PART #
UPC		
Vac Attachment System for CD414-350SS	701846 02863	233935

1. *1 DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER
2. 2 IN DETERMINING THE ABOVE VALUES REGARDING ACCELERATION OF VIBRATIONS AND SOUND, THE DIFFERENT OPERATING
3. CONDITIONS WERE WEIGHED IN ACCORDANCE WITH THE CURRENT STANDARDS
4. 3 INSECURITY K PURS. TO EC DIRECTIVE 2006/42/EC: 2.5 DB(A)
5. 4 INSECURITY K PURS. TO EC DIRECTIVE 2006/42/EC: 2 M/S²



Vacuum Attachment System



Vacuum Attachment System Close-up



Visit our YouTube page for more product information at:
www.youtube.com/NortonAbrasives

PRODUCT FEATURES



Advanced Design

Constructed with heavy-duty long life components and advanced design which creates a cart that allows for faster cuts, straighter cuts, less blade climb and the ultimate cutting experience.



Advanced Motor Adapter Plate

The SPEEDY CART is the world's first truly flexible high-speed saw cart with its optional advanced motor adapter plate system allowing the attachment of the Norton Clipper series and other popular high-speed saws to allow for the utmost utilization on the job site.



Steel Hub Wheels

The SPEEDY CART features steel hub wheels with real bearings for smoother rolling, straighter cuts, and easier operation than competitive models with plastic wheels and no bearings.



TECHNICAL SPECIFICATIONS

PRODUCT DESCRIPTION	UPC	SMART PART #
SPEEDY CART with Norton Clipper High-Speed Saw Adapter (Fits Norton Clipper CP500 Series Gas Saws)	701846 02411	SPEEDYCART
SPEEDY CART with Stihl High-Speed Saw Adapter (Fits Stihl TS420/TS400/TS500)	701846 07564	701846 07564
SPEEDY CART with Husqvarna High-Speed Saw Adapter (Fits Husqvarna K760/K760 Oil Guard/K770/K770 Oil Guard/K770 VAC)	701846 07565	701846 07565
SAWS (SOLD SEPARATELY)	UPC	SMART PART #
Norton Clipper 14" iLube High-Speed Cut-off Saw (SPEEDY CART not included.)	701846 47565	CP514-350i
Norton Clipper 14" Standard High-Speed Cut-off Saw (SPEEDY CART not included.)	701846 47563	CP514-350
ACCESSORIES	UPC	SMART PART #
Adapter for Norton Clipper CP500 Series Gas Saws (Cable & attachment hardware included. Saw not included.)	003105 01669	201409-138
Adapter for Stihl Series TS420 (Cable & attachment hardware included. Saw not included.)	003105 01671	310501671
Adapter for Husqvarna K760 and K770 Series Gas Saws (Cable & attachment hardware included. Saw not included.)	003105 01670	310501670
Rear mud flap kit	003105 01673	310501673
Front pointer assembly with attachment hardware	003105 01674	310501674



INFILTRATED HIGH-DENSITY DIAMOND BLADES

A new patented technology with longer blade life, faster cutting power, increased safety, and lower energy required for a high-quality result.



A STREAMLINED 2-STEP PROCESS

1

Form the segment core structure

2

Infiltrate the segment pores with exclusive bonding agent.

RESULT

A composite material with enhanced properties for limitless segment design.

UNIQUE PATENTED LASER WELDING WITH INFILTRATED SEGMENTS

Infiltration achieves high uniform density across each whole segment without applying high pressure (like the standard process). This allows Norton to manufacture very robust segments which wear evenly, remain intact and perform faster at higher cutting speeds.

The diamond grit is an integral part of the segment structure. During the patented process a special bond impregnates the core structure and binds the diamond grit into the segment. This ensures optimum use of the diamond grit, giving the diamond tools a longer life.

The simplified process also means increased segment design flexibility resulting in greater diversification of diamond blade shapes to best suit applications and materials being cut.



Multi-Purpose, All Materials

Concrete, reinforced concrete, granite, building materials, thin steel sections, angle iron up to 1/2" material thickness, rebar up to no. 5.



DRY – SEGMENTED RIM



4X4 MAX CUT

Taking high-speed cutting versatility to an all new level. The same standard features as the 4X4 with its anti-crack gullets and patented depth indicators that not only cool the blade but also allow the operator to know how deep they are cutting. An all new bond and diamond specification improves blade life in a wide range of materials while excelling in steel. New segment wear indicators give the operator an idea of remaining blade life.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 45927	4X4MC12118	12 x .118 x 1"/20mm	6,300	.472"
701846 45926	4X4MC14125	14 x .125 x 1"/20mm	5,460	.472"



4X4

Multi-purpose laser welded blade for dry cutting a range of construction materials without sacrificing performance or price. Depth of cut is easily controlled with the patented depth-of-cut indicators cut into the steel core. Anti-crack gullets for enhanced safety cutting steel and metal (up to 5mm thick).

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 84548	4X412110	12 x .110 x 1"/20mm	6,300	.393"
701846 84547	4X414118	14 x .118 x 1"/20mm	5,460	.393"
701846 45306	4X416125	16 x .125 x 1"/20mm	4,500	.393"



MULTI-CUT

NEW

The perfect combination of performance and price on high-speed, masonry, and floor saws. The laser welded segments are designed for cutting speed and long life, while a precise 1"/20mm laser cut dual arbor hole provides consistently secure mounting on the saw. Premium features combined with low pricing make for a reliable, fast cutting, long life blade for a variety of common construction materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 09680	MULTICUT14125	14 x .125 x 1"/20mm	5,460	.472"
701846 31788	MULTICUT16125	16 x .125 x 1"/20mm	4,500	.472"



MULTI-CUT

A very versatile, cut-all blade



When my first **Multi-Cut** blade order arrived, I personally called each of my biggest customers to try this blade. I have clients who cut soft and hard brick, block and other concrete. Everyone's feedback was that this blade does not degrade with use; as it cuts from day one, it cuts the same throughout the life of the blade until it finally runs out.

A really versatile blade for all types of customers that fit perfect into my business.

– Luis Galvan, MG SMALL ENGINE – Springdale, AR



We were given an opportunity in 2021 through Ferrara Equipment Co. to demo a 14" **Multi-Cut** diamond blade. We spent a short period running the blade and giving feedback to Ferrara and Saint-Gobain the day we received it. They allowed us to keep the blade and continue to run it on our job. During this period, we determined that the speed and cleanliness of this new blade was far superior to what we were currently using and what we have used in the past. Cleaner faster cuts! Although we do a wide range of cutting, our primary use of diamond blades is on concrete pavers and patio materials. Cleaner faster cuts are more efficient and eliminate the need for touch-up work on our finished product. We have been extremely satisfied with the **Multi-Cut** blade and will continue to use them going forward!

– Dean Johnson, James River Nurseries Hardscape Division - Ashland, VA



Reinforced Concrete and Harder Building Materials

Reinforced concrete, hard bricks, limestone, terrazzo, and other hard materials.



DRY – SEGMENTED RIM

DUO EVO

The unique shape of the DUO EVO segments optimizes the angle of attack while enhancing the evacuation of the debris. With a new manufacturing process, the DUO EVO segments provide an exceptional cutting speed for optimum performance and increased life up to 20% over the original DUO EVO design.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 84217	DUOEVO12110	12 x .110 x 1"/20mm	6,300	.590"
701846 84218	DUOEVO14118	14 x .118 x 1"/20mm	5,460	.590"
701846 93356	DUOEVO16130	16 x .130 x 1"/20mm	4,500	.590"



DUO

Our exclusive design, introduced in 2002, has become a dominant name in the market. The unique dual segment per land technology provides excellent cutting speed with low vibration and high comfort of cut. The exclusive arrow shape gullets not only indicate blade direction, but also assist in fast removal of cutting debris. Maximum general purpose performance when cutting medium to low reinforcement, hard materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 83611	DUO12110	12 x .110 x 1"/20mm	6,300	.393"
701846 83612	DUO14110	14 x .110 x 1"/20mm	5,460	.393"
701846 83613	DUO14125	14 x .125 x 1"/20mm	5,460	.393"
701846 83798	DUO16125	16 x .125 x 1"/20mm	4,500	.393"



proven performance DUO AND DUO EVO

“

Our firm has had terrific luck with the **DUO** family of blades. The only thing better than a DUO blade is the **DUO EVO**. The speed of cut and life of the DUO EVO blade is second to none.

– Aaron Graveen, Lincoln Contractors Supply


”

ESTIMATED NUMBER OF CUTS
HARD AGGREGATE STEEL REINFORCED



Asphalt and Abrasive Materials

Asphalt, green concrete, asphalt over concrete, abrasive blocks, mortar and other abrasive materials.



DRY – SEGMENTED RIM

DUO ASPHALT

Dry cutting laser welded blade for asphalt and green concrete. Laser welded drop segment wear-retardant extends blade life. Scoop gullets for faster swarf removal increases cut speed. Stroboscopic indicators to control cut depth and show rotation direction.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184684315	DUOASP14125	14 x .125 x 1"/20mm	5,460	.590"
70184684544	DUOASP16125	16 x .125 x 1"/20mm	4,500	.590"



DUO ABRASIVE

Utilizes the basic characteristics of original DUO blade and adds a unique segment shape that optimizes the angle of attack while enhancing the evacuation of the particles. The result is an exceptional cutting speed allied with very good performance and life in abrasive materials and concrete block. The bond specification lends additional life when high-speed cutting.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184684291	DUOAB14110	14 x .110 x 1"/20mm	5,460	.327"
70184684292	DUOAB14125	14 x .125 x 1"/20mm	5,460	.327"



CLASSIC

Ideal blade for small to medium size high-speed cutting jobs. Economically priced with good productivity in asphalt, green concrete and other abrasive materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184684429	COHSABR1420	14 x .125 x 1"/20mm	5,460	.393"
07660701230	CHDASP1620	16 x .125 x 1"/20mm	4,500	.256"



VALUPLUS


Dry cutting sintered segmented blade for abrasive materials. Drop-segment wear-retardant extends life of core. Economically priced with good performance in asphalt, green concrete and other abrasive materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184603333	VPHSABR14125	14 x .125 x 1"/20mm	5,460	.452"



Natural Stone and Tiles

Ceramic and stone tiles, granite, marble, very hard bricks and other very hard and dense materials.



DRY – TURBO RIM

AERO-JET

New innovative design allows for very fast, smooth cutting. The improved .392" high segment rim adds extremely long life whether cutting wet or dry in hard materials. Exclusive arch-shaped protection inserts allow for precision straight cuts. The ventilated waved steel core for better cooling and intensive use. Exceptional cutting on a very wide range of materials with a high quality finished cut.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
70184683785	AEROHS1420	14 x .125 x 1"/20mm	5,460	.392"





General Purpose and Masonry Building Materials

Blocks, medium-hard building bricks, paving slabs, concrete roof tiles and other medium-hard materials.

DRY – SEGMENTED RIM



CHARGER



A high performance, laser welded blade designed with quality segments for cutting concrete and medium hard materials with medium reinforcing.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
076607 56267	CGHSGP1420	14 x .125 x 1"/20mm	5,460	.472"
076607 01229	CGHSGP1620	16 x .125 x 1"/20mm	4,500	.472"



CLASSIC



The improved bond provides longer life at an economical price in medium hard materials such as concrete with light to medium reinforcement.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 81383	COHSGP1220	12 x .110 x 1"/20mm	6,300	.256"
701846 81309	COHSGP1420	14 x .110 x 1"/20mm	5,460	.256"
701846 84268	COHSGP1420P	14 x .125 x 1"/20mm	5,460	.256"
701846 40356	COHSGP1620	16 x .125 x 1"/20mm	4,500	.256"



VALUPLUS SS



For value and performance on small to medium jobs. Provides fast cutting and the .472" taller sintered super segment (SS) increase blade life. Perfect blade for jobs that require fast dry cutting of abrasive materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 84465	VPSSHSGP1420	14 x .125 x 1"/20mm	5,460	.472"



VALUPLUS



For value and performance on small to medium size jobs. The sintered blade cuts unreinforced soft to medium concrete fast on saws up to 13 HP.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 84180	VPHSGP1220	12 x .110 x 1"/20mm	6,300	.393"
701846 84181	VPHSGP1420	14 x .110 x 1"/20mm	5,460	.393"
701846 84428	VPHSGP1420 20PK	14 x .110 x 1"/20mm	5,460	.393"



DRY – TURBO RIM



CHARGER



High performance dry cutting of a variety of materials. The segment specification allows extended life and fast cut for medium to large jobs.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 84524	CGHSTS1220	12 x .125 x 1"/20mm	6,300	.472"
701846 84525	CGHSTS1420	14 x .125 x 1"/20mm	5,460	.472"



Rescue, Demolition

Ductile, steel, polyvinyl pipe, thin steel plate, acrylic sheet, fiberglass, rubber, standard glass, wood, concrete, brick, asphalt.



DRY – CONTINUOUS RIM



RESCUE RUNNER



When seconds count, reach for the Norton Rescue Runner. The specially tempered steel core provides maximum durability under the toughest conditions on many materials. A new diamond placement technology allows diamonds to cut in both directions for quick cutting.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184684426	NXHSRR1220	12 x .140 x 20mm	6,300	.275"
70184684361	NXHSRR1420	14 x .140 x 20mm	5,460	.275"



proven performance RESCUE RUNNER


“The best thing about this blade is it always works. While operating at a strip mall fire, our tower was assigned vent work. The guys that operated that night stated that it out-cut the other saws working that fire. They cut several different holes without having to change blades and were able to continue working without missing a beat. They cleaned the blade up, flipped it over and it was ready to meet its next challenge.

– FF/PM Chris Wilson, Bloomingdale Fire District



Bidirectional Blade Usage

The symmetrical diamond pattern placement allows the quick blade mounting without worry of proper direction.



Faster Cutting and Longer Life

The bonding system allows the diamond to resist premature release providing longer diamond life and speed of cut.

DIALAST



Vacuum brazed segments laser welded to steel core for maximum attachment strength for hand-held saw applications. Radially cut segments for less vibration. Advanced segment design with vent holes to provide enhanced cooling when cutting dry in hard and non-ferrous materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184602503	NDLAST14125	14 x .125 x 1"/20mm	5,400	.123"
70184602504	NDLAST16125	16 x .125 x 1"/20mm	4,725	.123"





RANGE OVERVIEW



MODEL#	C2024SS	C1320SS	C1318P	C13PE	C914P	GC55
UPC#	70184627371	70184627368	70184642453	70184647524	70184608504	70184630005
MAX. DEPTH OF CUT	9 5/8" (244mm)	7 5/8" (193mm)	6 5/8" (168mm)	6 5/8" (168mm)	4-5/8" (117mm)	3 3/4" (95mm)
MAX. HP.	20 HP (14.9 kW)	13 HP (9.5 kW)	13 HP (9.5 kW)	13 HP (9.5 kW)	9 HP (6.7 kW)	5.5 HP (4.1 kW)

PRODUCT FEATURES



Simple Maintenance Design

Easy to get to belt tensioning for quick replacements.




Spindle-Saver Blade Flanges

Allows blade to sit on inner flange instead of shaft for replacement of flange only instead of complete shaft.



Raised Axle

Heavy-duty boxed-in design resists bending and flexing during transport.



Manufactured with an uncomplicated, reinforced frame design to withstand the harshness of job cutting requirements on mid-sized jobs. Blade capabilities of 16", 20" or 24". The self-propelled hydrostatic transmission and the 4-V belt drive transfers maximum power to the blade shaft for ease of operation with dependable performance.

TECHNICAL SPECIFICATIONS

PRODUCT #	C2020SS	C2024SS
UPC	701846 27370	701846 27371
Blade Guard Capacity – in. (mm)	20" (356)	24" (406)
Maximum Depth of Cut – in. (mm)	7-5/8" (193)	9-5/8" (244)
Arbor Size – in. (mm)	1" (25)	1" (25)
Blade Flange Diameter – in. (mm)	4-1/2" (114)	4-1/2" (114)
Blade Shaft RPM	2520 RPM	2120 RPM
Blade Shaft Diameter – in. (mm)	1-1/4" (32)	
Blade Shaft Bearings	Heavy Duty Pillow Block	
Blade Shaft Drive	4 Belts	
Blade Guard Attachment	Pivoting, All Steel	
Blade Control	Hand Wheel/Screw Feed	
Axle – Front – in. (mm)	3/4" (19)	
Axle – Rear – in. (mm)	3/4" (19)	
Wheels – Front D x W x B – in. (mm)	5" x 2" x 3/4" (127 x 50 x 19)	
Wheels – Rear D x W x B – in. (mm)	6" x 2" x 3/4" (152 x 50 x 19)	
Handle Bars/Adjustment Length	20-5/8" (530)	
Transmission	Eaton Hydrostatic	
Control	Roller Gear	
Speed	0-220 FPM	
Chassis	Heavy duty jig-welded box frame	
Power Source	Gasoline, 2 Cylinders 4 Cycle	
Engine Type	Honda GX630	
Specifications	GX630RHTXF2	
Maximum Horsepower	20.8 HP (15.5 kW)	
Net Horsepower	18.1 HP (13.5 kW) – *	
Displacement – cu. In. (l)	41.9 cu in (0.688 l)	
Bore – in. (mm)	3.1" (78)	
Stroke – in. (mm)	2.8" (72)	
Cylinders/Cycle	Two Cylinder 4 Cycle	
Fuel Capacity – gal (l)	2.12 gal. (8.03 l)	
Oil Capacity – qt (l)	2.1 qt. (2.0 l)	
Air Filter	Three Stage Honda	
Starter	Electric	
Engine Cooling	Forced Air	
SAW DIMENSIONS		
Height	40" (1,016)	40" (1,016)
Minimum Saw Length (Transport) – in. (mm)	56" (1,142)	56" (1,142)
Maximum Saw Length (Working) – in. (mm)	114" (2,896)	114" (2,896)
Maximum Pointer Length – in. (mm)	40" (1,016)	40" (1,016)
Frame Width – in. (mm)	17" (432)	17" (432)
Saw Width – in. (mm)	26" (660)	26" (660)
Front (Outside to Outside Wheel Width) – in. (mm)	14-3/16" (360)	14-3/16" (360)
Rear (Outside to Outside Wheel Width) – in. (mm)	15-1/4" (388)	15-1/4" (388)
Blade to Wall – in. (mm)	2-9/16" (65)	2-9/16" (65)
Wheel Base Length – in. (mm)	16-1/6" (407)	16-1/6" (407)
Weight Crated – lbs (kg)	468 (212)	468 (212)
Weight Uncrated – lbs (kg)	428 (195)	428 (195)
ACCESSORIES	UPC	SMART PART #
Water Tank Kit for 13HP & 20HP	701846 28014	238001

*= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER



Water Tank Kit

PRODUCT FEATURES



Pivoting Blade Guard

All steel construction, with no springs or hinges, eliminates possible breakage.



Heavy-Duty Box Frame

Resists bending and flexing for a solid design.



Eaton Transmission

Hydro-static for infinitely variable forward and reverse speeds.



Combining all the features of the larger self-propelled Norton Clipper saw, this saw features a strong 13HP Honda or Kohler 14HP engine in either manual or electric start. Constructed with a well-balanced and narrow box frame with right or left cutting capability, these flat saws are very versatile on any size job site.

TECHNICAL SPECIFICATIONS

PRODUCT #	C1320SM	C1320SS	C1420SM	C1420SS
UPC	701846 27366	701846 27368	701846 02772	701846 02773
Blade Guard Capacity – in. (mm)	20" (356)	20" (356)	20" (356)	20" (356)
Maximum Depth of Cut – in. (mm)	7-5/8" (193)	7-5/8" (193)	7-5/8" (193)	7-5/8" (193)
Arbor Size – in. (mm)	1" (25)	1" (25)	1" (25)	1" (25)
Blade Flange Diameter – in. (mm)	4-1/2" (114)	4-1/2" (114)	4-1/2" (114)	4-1/2" (114)
Blade Shaft RPM	2520 RPM	2520 RPM	2520 RPM	2520 RPM
Blade Shaft Diameter – in. (mm)	1-1/4" (32)			
Blade Shaft Bearings	Heavy Duty Pillow Block			
Blade Shaft Drive	4 Belts			
Blade Guard Attachment	Pivoting, All Steel			
Blade Control	Hand Wheel/Screw Feed			
Axle – Front – in. (mm)	3/4" (19)			
Axle – Rear – in. (mm)	3/4" (19)			
Wheels – Front D x W x B – in. (mm)	5" x 2" x 3/4" (127 x 50 x 19)			
Wheels – Rear D x W x B – in. (mm)	6" x 2" x 3/4" (152 x 50 x 19)			
Handle Bars/Adjustment Length	20-5/8" (530)			
Transmission	Eaton Hydrostatic			
Control	Roller Gear			
Speed	0-220 FPM			
Chassis	Heavy duty jig-welded box frame			
Power Source	Gasoline, Single Cylinder 4 Cycle			
Engine Type	Honda GX390		Kohler CH440	Kohler CH440
Specifications	GX390K1QXC9	GX390K1QAE2	CH440-1349	CH440-3021
Maximum Horsepower	13 HP (9.5 kW) – *		14 HP (10.5kW)	14 HP (10.5kW)
Net Horsepower	11 HP (8.2 kW) – *		14 HP (10.5kW)	14 HP (10.5kW)
Displacement – cu. In. (l)	23.7 cu in (0.39)		24.7 cu in (0.429)	24.7 cu in (0.429)
Bore – in. (mm)	3.5" (88)		3.5" (88)	3.5" (88)
Stroke – in. (mm)	2.5" (64)		2.7 (69)	2.7 (69)
Cylinders/Cycle	Single Cylinder 4 Cycle		Single Cylinder 4 Cycle	Single Cylinder 4 Cycle
Fuel Capacity – gal. (l)	1.79 gal. (6.5 l)		1.9 (6.8)	1.9 (6.8)
Oil Capacity – qt. (l)	1.16 qt. (1.1 l)		1.4 (1.3)	1.4 (1.3)
Air Filter	Four Stage Honda	Two Stage Honda	Four Stage Kohler	Four Stage Kohler
Starter	Manual	Electric	Manual	Electric
Engine Cooling	Forced Air	Forced Air	Forced Air	Forced Air
SAW DIMENSIONS				
Height	40" (1,016)	40" (1,016)	40" (1,016)	40" (1,016)
Minimum Saw Length (Transport) – in. (mm)	56" (1,142)	56" (1,142)	56" (1,142)	56" (1,142)
Maximum Saw Length (Working) – in. (mm)	114" (2,896)	114" (2,896)	114" (2,896)	114" (2,896)
Maximum Pointer Length – in. (mm)	40" (1,016)	40" (1,016)	40" (1,016)	40" (1,016)
Frame Width – in. (mm)	17" (432)	17" (432)	17" (432)	17" (432)
Saw Width – in. (mm)	26" (660)	26" (660)	26" (660)	26" (660)
Front (Outside to Outside Wheel Width) – in. (mm)	14-3/16" (360)	14-3/16" (360)	14-3/16" (360)	14-3/16" (360)
Rear (Outside to Outside Wheel Width) – in. (mm)	15-1/4" (388)	15-1/4" (388)	15-1/4" (388)	15-1/4" (388)
Blade to Wall – in. (mm)	2-9/16" (65)	2-9/16" (65)	2-9/16" (65)	2-9/16" (65)
Wheel Base Length – in. (mm)	16-1/6" (407)	16-1/6" (407)	16-1/6" (407)	16-1/6" (407)
Weight Crated – lbs (kg)	445 (202)	425 (193)	445 (202)	425 (193)
Weight Uncrated – lbs (kg)	405 (175)	385 (175)	405 (175)	385 (175)
ACCESSORIES				
	UPC	SMART PART #		
Water Tank Kit for 13HP & 20HP	701846 28014	238001		

*= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER



Water Tank Kit

PRODUCT FEATURES



Spindle-Saver Blade Flanges

Allows blade to sit on inner flange instead of shaft for replacement of flange only instead of complete shaft.




Four V-Belts

Transferring maximum power to the blade shaft.



Reinforced Frame and Axle

Strongest in its class.



Small to medium contractor work demands performance with an economical solution. The C1320P and C1420P brings the contractor the ideal saw with a heavy-duty box frame that resists bending and supported with the high-performing Honda 13HP and Kohler 14HP engines. The heavy frame also provides a straighter cut. Changing or adjusting belts is simple with the single screw tensioner. The C1320P and the C1420P are in a class by themselves.

TECHNICAL SPECIFICATIONS

PRODUCT #	C1320P	C1420P
UPC	701846 42456	701846 02769
Blade Guard Capacity – in (mm)	20" (356)	20" (356)
Maximum Depth of Cut – in (mm)	7-5/8" (193)	7-5/8" (193)
Arbor Size – in (mm)	1" (25)	1" (25)
Blade Flange Diameter – in (mm)	4-1/2" (114)	4-1/2" (114)
Blade Shaft RPM	2,520 RPM	2,520 RPM
Blade Shaft Diameter – in (mm)	1-1/4" (32)	
Blade Shaft Bearings	Heavy Duty Pillow Block	
Blade Shaft Drive	4 Belts	
Blade Guard Attachment	Pivoting, All Steel	
Blade Control	Hand Wheel/Screw Feed	
Axle – Front – in (mm)	3/4" (19)	
Axle – Rear – in (mm)	3/4" (19)	
Wheels – Front D x W x B – in (mm)	5" x 2" x 3/4" (127 x 50 x 19)	
Wheels – Rear D x W x B – in (mm)	6" x 2" x 3/4" (152 x 50 x 19)	
Handle Bars/Adjustment Length	20-5/8" (530)	
Control	Roller Gear	
Speed	0-220 FPM	
Chassis	Heavy duty jig welded box frame	
Power Source	Gasoline, Single Cylinder 4 Cycle	
Engine Type	Honda GX390	Kohler CH440
Specifications	GX390K1QXC9	CH440-1349
Maximum Horsepower*	13 HP (9.5kW)	14 HP (10.5kW)
Net Horsepower*	11 HP (8.2 kW)	14 HP (10.5kW)
Displacement – cu in (l)	23.7 cu in (0.39)	24.7 cu in (0.429)
Bore – in (mm)	3.5" (88)	3.5" (88)
Stroke – in (mm)	2.5" (64)	2.7" (69)
Cylinders/Cycle	Single Cylinder 4 Cycle	Single Cylinder 4 Cycle
Fuel Capacity – gal (l)	1.79 gal. (6.5 l)	1.9 (6.8)
Oil Capacity – qt (l)	1.16 qt. (1.1 l)	1.4 (1.3)
Air Filter	Four Stage Honda	Four Stage Kohler
Starter	Manual	Manual
Engine Cooling	Air	Forced Air
SAW DIMENSIONS		
Height	40" (1,016)	40" (1,016)
Minimum Saw Length (Transport) – in (mm)	56" (1,142)	56" (1,142)
Maximum Saw Length (Working) – in (mm)	114" (2,896)	114" (2,896)
Maximum Pointer Length – in (mm)	40" (1,016)	40" (1,016)
Frame Width – in (mm)	17" (432)	17" (432)
Saw Width – in (mm)	26" (660)	26" (660)
Front (Outside to Outside Wheel Width) – in (mm)	14-3/16" (360)	14-3/16" (360)
Rear (Outside to Outside Wheel Width) – in (mm)	15-1/4" (388)	15-1/4" (388)
Blade to Wall – in (mm)	2-9/16" (65)	2-9/16" (65)
Wheel Base Length – in (mm)	16-1/6" (407)	16-1/6" (407)
Weight Crated – lbs. (kg)	345 (157)	345 (157)
Weight Uncrated – lbs (kg)	310 (141)	310 (141)
ACCESSORIES	UPC	SMART PART #
Water Tank Kit for 13HP & 20HP	701846 28014	238001

*= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER



Water Tank Kit

PRODUCT FEATURES



Vibration Reducing Handle Bars

Shock-absorbing handle bars reduce vibrations up to 40%.



Quick Belt Tensioning

Provides fast and accurate belt tensioning.



Fast Blade Guard Lock

No hassle, blade guard securing lock.



The next generation of multi-purpose concrete saws. The C1318P and C1418P features shock-absorbing handle bars. The new sleek design of the water tank, with increased capacity and improved securing, adds an additional 6.5 gallons of water over the cut. And, a newly-designed belt tensioning system helps keep the saw cutting tried and true. All these features, coupled with the Honda 13HP engine or Kohler 14HP, makes the C1318P and the C1418P the premiere choice for rental and service work.

TECHNICAL SPECIFICATIONS

PRODUCT #	C1318P	C1418P
UPC	701846 42453	701846 02768
Blade Guard Capacity – in (mm)	18" (457)	
Maximum Depth of Cut – in (mm)	6-5/8" (168)	
Arbor Size – in (mm)	1" (25)	
Blade Flange Diameter – in (mm)	4-1/2" (114)	
Blade Shaft RPM	2,573	
Blade Shaft Diameter – in (mm)	1.18" (30)	
Blade Shaft Bearings	Heavy Duty Pillow Block	
Blade Shaft Drive	Single 10 Groove Belt	
Blade Guard Attachment	Hinged, All Steel	
Blade Control	Hand Wheel/Screw Feed	
Axle – Front – in (mm)	25/32" (20)	
Axle – Rear – in (mm)	25/32" (20)	
Wheels – Front D x W x B – in (mm)	4-59/64" x 1-31/32" x 25/32" (125 x 50 x 20)	
Wheels – Rear D x W x B – in (mm)	8" x 1-1/4" x 25/32" (203 x 32 x 20)	
Handle Bars/Adjustment Length	6-1/4" (160)	
Control	5.28 gal. (20 l)	
Speed	Push	
Chassis	Heavy Duty Steel Box with Longitudinal and Horizontal Reinforcements	
Power Source	Gasoline, Single Cylinder 4 Cycle	
Engine Type	Honda GX390	Kohler CH440
Specifications	GX390K1QXC9	CH440-1349
Maximum Horsepower*	13 HP (9.5kW)	14 HP (10.5kW)
Net Horsepower*	11 HP (8.2 kW)	14 HP (10.5kW)
Displacement – cu in (l)	23.7 cu in (0.39 l)	24.7 cu in (0.429 l)
Bore – in (mm)	3.5" (88)	3.5" (88)
Stroke – in (mm)	2.5" (64)	2.7" (69)
Cylinders/Cycle	Single Cylinder 4 Cycle	Single Cylinder 4 Cycle
Fuel Capacity – gal (l)	1.79 gal. (6.5 l)	1.9 (6.8)
Oil Capacity – qt (l)	1.16 qt. (1.1 l)	1.4 (1.3)
Air Filter	Four Stage Cyclone	Four Stage Kohler
Starter	Manual	Manual
Engine Cooling	Forced Air	Forced Air
SAW DIMENSIONS		
Height	39" (990)	39" (990)
Minimum Saw Length (Transport) – in (mm)	33-1/2" (850)	33-1/2" (850)
Maximum Saw Length (Working) – in (mm)	61-1/2" (1,5610)	61-1/2" (1,5610)
Maximum Pointer Length – in (mm)	20-7/8" (528)	20-7/8" (528)
Frame Width – in (mm)	16-1/2" (421)	16-1/2" (421)
Saw Width – in (mm)	22" (609)	22" (609)
Front (Outside to Outside Wheel Width) – in (mm)	10-7/16" (265)	10-7/16" (265)
Rear (Outside to Outside Wheel Width) – in (mm)	16-57/64" (429)	16-57/64" (429)
Blade to Wall – in (mm)	4-1/2" (114)	4-1/2" (114)
Wheel Base Length – in (mm)	13" (332)	13" (332)
Weight Crated – lbs. (kg)	240 (109)	240 (109)
Weight Uncrated – lbs (kg)	220 (100)	220 (100)

*= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER



Visit our YouTube page for more product information at:
www.youtube.com/NortonAbrasives

PRODUCT FEATURES



Fast Release Guard

The quick release pull pin keeps the blade guard locked down for safety during operation. No more jam nuts or tools needed - just pull and lift.



Tough Frame and Raised Axle

Thick, heavy-duty gauge metal frame endures the hardest of users and job sites. Resists twisting for a tried and true straight cut.



Uncomplicated Control Panel

Everything at your fingertips to manage the saw with ease: depth locking mechanism, emergency shut off and water valve within easy reach.



Rental equipment has to withstand any and all conditions by user and application. For that reason, the Norton Clipper C13PE and C14PEK suits any rental fleet that both the novice and expert will appreciate to hold-up through tough situations. The 18" blade guard, ride-on water system and quick-release blade guard lock all keep safety in mind while the rugged frame, powerful engine and easy-to-use console makes cutting a breeze.

***WATER TANK SOLD SEPARATELY.**

TECHNICAL SPECIFICATIONS

PRODUCT #	C13PE	C14PEK
UPC	701846 47524	701846 02766
Blade Guard Capacity - in (mm)	18" (457)	
Maximum Depth of Cut - in (mm)	6-5/8" (168)	
Arbor Size - in (mm)	1" (25)	
Blade Flange Diameter - in (mm)	4-1/2" (114)	
Blade Shaft RPM	2,700	
Blade Shaft Diameter - in (mm)	1.00" (25.4)	
Blade Shaft Bearings	Heavy Duty Pillow Block	
Blade Shaft Drive	3 Belts	
Blade Guard Attachment	Hinged, All Steel	
Blade Control	Hand Wheel/Screw Feed	
Axle - Front - in (mm)	3/4" (19)	
Axle - Rear - in (mm)	3/4" (19)	
Wheels - Front - in (mm) D x W x B	4" x 1.5" x 3/4" (102 x 38 x 19)	
Wheels - Rear - in (mm) D x W x B	8" x 2.50" x 3/4" (203 x 64 x 19)	
Handle Bars/Adjustment Length - in (mm)	-NA-	
Water Tank Capacity - gal (l)	-NA-	
Control	Push	
Chassis	Heavy Duty Box Design	
Power Source	Gasoline, Single Cylinder 4 Cycle	
Motor/Engine Type	Honda GX390	Kohler CH440
Specifications	GX390K1QXC9	CH440-1349
Maximum Horsepower*	13 HP (9.5 kW)	14 HP (10.5kW)
Net Horse Power*	11 HP (8.2 kW)	14 HP (10.5kW)
Displacement - cu In (l)	23.7 cu in (0.39 l)	24.7 cu in (0.429)
Bore - in (mm)	3-1/2" (88)	3.5" (88)
Stroke - in (mm)	2-1/2" (64)	2.7 (69)
Cylinders/Cycle	Single Cylinder 4 Cycle	Single Cylinder 4 Cycle
Fuel Capacity - gal (l)	1.79 gal. (6.5 l)	1.9 (6.8)
Oil Capacity - qt (l)	1.16 qt. (1.1 l)	1.4 (1.3)
Air Filter	Four Stage Cyclone	Four Stage Kohler
Starter	Manual	Manual
Engine Cooling	Forced Air	Forced Air
SAW DIMENSIONS		
Height - in (mm)	38-13/16" (986)	38-13/16" (986)
Minimum Saw Length (Transport) - in (mm)	42-3/4" (1086)	42-3/4" (1086)
Maximum Saw Length (Working) - in (mm)	63" (1600)	63" (1600)
Maximum Pointer Length - in (mm)	20" (508)	20" (508)
Frame Width - in (mm)	16-1/2" (419)	16-1/2" (419)
Saw Width - in (mm)	21-27/64" (544)	21-27/64" (544)
Front (Outside to Outside Wheel Width) - in (mm)	14-17/32" (369)	14-17/32" (369)
Rear (Outside to Outside Wheel Width) - in (mm)	19-9/32" (490)	19-9/32" (490)
Blade to Wall - in (mm)	1-23/32" (44)	1-23/32" (44)
Wheel Base Length - in (mm)	15-3/4" (400)	15-3/4" (400)
Weight Crated - lbs. (kg)	240 (109)	240 (109)
Weight - Uncrated - lbs (kg)	220 (100)	220 (100)
ACCESSORIES		SMART PART #
Water Tank Assembly for C13PE		701846 31499
INCLUDES: Bracket with lifting bail, water tank with fittings (valve, elbows, hose barbs, hose clamps, and hose), and mounting hardware.		247120

*= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER



Water Tank Kit

PRODUCT FEATURES



Adjustable Height Handle Bars

Stay-level handle bar system adjusts to four different positions for the utmost in operator comfort.



Quick Belt Tensioning

Easy to change V belts for fast and accurate belt tensioning.



Water Supply

Includes a water tank with garden hose fitting.



With extreme reliability, portability, and strong performance, the new full featured Norton Clipper C914P and C914PK walk-behind saw is redefining the compact concrete saw class. The powerful Honda and Kohler 9HP engine, 14" maximum blade capacity, and the strongest chassis in class make for the fastest and straightest cuts every time. Designed for easy transportation, simple operation, and low maintenance, the C914P and C914PK are the right choice for contractors and rental. The C914P and C914PK are equally at home cutting concrete, sidewalks, asphalt, or decorative concrete making it the perfect saw for any job.

TECHNICAL SPECIFICATIONS

PRODUCT #	C914P	C914PK
UPC	701846 08504	701846 32011
Blade Guard Capacity - in. (mm)	14" (350)	
Maximum Depth of Cut - in. (mm)	4-1/2" (114)	
Arbor Size - in. (mm)	1" (25.4)	
Blade Flange Diameter - in. (mm)	4" (107)	
Blade Shaft RPM	2,840	
Blade Shaft Diameter - in. (mm)	7/8" (22)	
Blade Shaft Bearings	Heavy Duty Pillow Block	
Blade Shaft Drive	3 Belts	
Blade Guard Attachment	Hinged, All Steel	
Blade Control	Hand Wheel/Screw Feed	
Axle - Front - in (mm)	19/32" (15)	
Axle - Rear - in (mm)	25/32" (20)	
Wheels - Front - in (mm) D x W x B	3-15/16" x 1-3/8" x 0.59" (100 x 35 x 15)	
Wheels - Rear - in (mm) D x W x B	7-7/8" x 1-49/64" x 0.79" (200 x 45 x 20)	
Handle Bars/Adjustment Length	9-29/64" (245)	
Control	Push	
Chassis	Heavy Duty Box Design	
Water Tank Capacity - gal (l)	6.6 (25)	
Power Source	Gasoline, Single Cylinder 4 Cycle	
Motor/Engine Type	Honda	Kohler
Specifications	Honda GX270QC9	Kohler PA-CH395-3149
Maximum Horsepower* (kW)	8.4 (6.3)	9.5 (7.1)
Net Horse Power* (kW)	6.5 (4.8)	9.5 (7.1)
Displacement - cu In (l)	16.5 (0.27)	16.9 (277)
Bore - in (mm)	3.0 (77)	3.1 (78)
Stroke - in (mm)	2-5/16" (58)	2.3 (58)
Cylinders/Cycle	Single Cylinder 4 Cycle	Single Cylinder 4 Cycle
Fuel Capacity - gal (l)	1.4 (5.3)	1.9 (6.8)
Oil Capacity - qt (l)	0.29 (1.1)	1.4 (1.3)
Airfilter	Four Stage Cyclone	Four Stage Kohler
Starter	Manual	Manual
Engine Cooling	Forced Air	Forced Air
SAW DIMENSIONS		
Height - in (mm)	37-59/64" (963)	37-59/64" (963)
Minimum Saw Length (Transport) - in (mm)	35-37/64" (929)	35-37/64" (929)
Maximum Saw Length (Working) - in (mm)	57-55/64" (1,469)	57-55/64" (1,469)
Maximum Pointer Length - in (mm)	21-9/32" (541)	21-9/32" (541)
Frame Width - in (mm)	12-47/64" (323)	12-47/64" (323)
Saw Width - in (mm)	19" (483)	19" (483)
Front (Outside to Outside Wheel Width) - in (mm)	12-47/64" (323)	12-47/64" (323)
Rear (Outside to Outside Wheel Width) - in (mm)	13-45/64" (348)	13-45/64" (348)
Blade to Wall - in (mm)	1-3/8" (35)	1-3/8" (35)
Wheel Base Length - in (mm)	17-21/64" (440)	17-21/64" (440)
Weight Crated - lbs. (kg)	198.4 lbs (90.6 kg)	198.4 lbs (90.6 kg)
Weight - Uncrated - lbs (kg)	169.4 lbs (77 kg)	169.4 lbs (77 kg)

*= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER

PRODUCT FEATURES



Gasoline Engine

Mounted with the dependable Honda 5.5HP engine for best performance.



Front Blade Mount

10" blade guard capacity. Additional weight helps keep the blade in the cut.



Fold-Down Design

Easy storage and transport.



“

Having a powerful Honda 5HP engine, the GC55 saw cuts faster than any other saw we have. The roller system allows you to roll on a concrete slab and cut a straight line without any difficulty. The weight of the saw is fantastic, making it an extremely portable machine.

– Tony Psencik, Suncoast Post-Tension, Ltd.

”

With a compact, light-weight design backed by the reliable Honda 5HP gasoline engine, the GC55 early entry saw is intended for a variety of applications. From green, cured or decorative concrete cutting to expansion joints, the features of this small push saw are hard to beat in a single saw. The low, wide profile of the frame, along with the front mount blade, contribute to producing a more disciplined cut. Now available in two models; our standard GC55 or our new GC55 VAC with Vacuum Attachment System. The GC55 and GC55 VAC include a wet kit for additional dust control.

TECHNICAL SPECIFICATIONS

PRODUCT #	GC55
UPC	70184630005
Blade Guard Capacity – in. (mm)	10" (254)
Maximum Depth of Cut – in. (mm)	3-1/2" (88)
Arbor Size – in. (mm)	5/8" (15.9)
Blade Flange Diameter – in. (mm)	3-5/64" (78)
Blade Shaft RPM	3,000
Blade Shaft Diameter – in. (mm)	7/8" (20)
Blade Shaft Bearings	Sealed Radial Bearings
Blade Shaft Drive	1 Cogged
Blade Guard Attachment	All Steel
Blade Control	Screw Feed
Axle – Front – in. (mm)	55/64" (22)
Axle – Rear – in. (mm)	55/64" (22)
Wheels – Front – in. (mm) D x W x B	3-3/8" x 2-3/4" x 25/32" (85 x 70 x 20)
Wheels – Rear – in. (mm) D x W x B	3-3/8" x 2-3/4" x 25/32" (85 x 70 x 20)
Handle Bars/Adjustment Length – in. (mm)	6" (152.4)
Control	Push
Chassis	Heavy Duty Stamped Steel with Reinforcements
Power Source	Single Cylinder 4 Cycle
Motor/Engine Type	Honda GX160
Specifications	GX160K1QXC9
Maximum Horsepower	5.5 HP (4.1 kW) – *
Net Horse Power	4.8 HP (3.6 kW) – *
Voltage	-NA-
Cycle/Current/Phase	-NA-
Full Load Amps	-NA-
Starting Amps	-NA-
Displacement – cu. In (l)	9.9 cu in (0.16 l)
Bore – in. (mm)	2.7" (68)
Stroke – in. (mm)	1.8" (45)
Cylinders/Cycle	Single Cylinder 4 Cycle
Fuel Capacity – gal. (l)	.95 (3.6 l)
Oil Capacity – qt. (l)	.63 (.6 l)
Air Filter	Four Stage Cyclone
Starter	Manual
Engine Cooling	Forced Air

SAW DIMENSIONS

Height – in (mm)	24-7/32" (615)
Minimum Saw Length (Transport) – in. (mm)	32" (813)
Maximum Saw Length (Working) – in. (mm)	48" (1,218)
Maximum Pointer Length – in. (mm)	13-1/4" (337)
Frame Width – in. (mm)	13-11/16" (348)
Saw Width – in. (mm)	18-1/8" (460)
Front (Outside to Outside Wheel Width) – in. (mm)	8-21/32" (220)
Rear (Outside to Outside Wheel Width) – in. (mm)	13" (330)
Blade to Wall – in. (mm)	7-1/2" (190)
Wheel Base Length – in. (mm)	19" (483)
Weight Crated – lbs (kg)	135 (61)
Weight Uncrated – lbs (kg)	115 (52)

ACCESSORIES

		SMART PART #
GC55 Vacuum Attachment Accessory Kit	70184602861	233933
Includes: Fully assembled cutting arm with belt guard, belt, and blade shaft. Blade guard with vacuum port and skirt, stay level arm, and all hardware. Does not include GC55 saw, vacuum or wet kit.		

*= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER



Vacuum Attachment Accessory Kit



Visit our YouTube page for more product information at:
www.youtube.com/NortonAbrasives

PRODUCT FEATURES



Center Mounted Blade Guard

Center mounted blade guard for straighter cuts and built in vacuum port for the best in dust control.



Gasoline Engine

Mounted with the dependable Honda 5.5HP engine for best performance.



Fold-Down Design

Easy storage and transport.



With all of the standard features of our GC55, the GC55 VAC includes a vacuum attachment system and wet kit for additional dust control. With a compact, light-weight design backed by the reliable Honda 5HP gasoline engine, the GC55 VAC early entry saw is intended for a variety of applications. From green, cured or decorative concrete cutting to expansion joints, the features of this small push saw are hard to beat in a single saw. The low, wide profile of the frame, along with the front mount center blade, contribute to producing a straighter cut.

TECHNICAL SPECIFICATIONS

PRODUCT #	GC55VAC
UPC	701846 02860
Blade Guard Capacity – in (mm)	10" (254)
Maximum Depth of Cut – in (mm)	1-7/8" (48)
Arbor Size – in (mm)	5/8" (15.9)
Blade Flange Diameter – in (mm)	3-5/64" (78)
Blade Shaft RPM	3,000
Blade Shaft Diameter – in (mm)	7/8" (20)
Blade Shaft Bearings	Sealed Radial Bearings
Blade Shaft Drive	1 Cogged
Blade Guard Attachment	All Steel
Blade Control	Screw Feed
Axle – Front – in (mm)	55/64" (22)
Axle – Rear – in (mm)	55/64" (22)
Wheels – Front – in (mm) D x W x B	3-3/8" x 2-3/4" x 25/32" (85 x 70 x 20)
Wheels – Rear – in (mm) D x W x B	3-3/8" x 2-3/4" x 25/32" (85 x 70 x 20)
Handle Bars/Adjustment Length – in (mm)	6" (152.4)
Control	Push
Chassis	Heavy Duty Stamped Steel with Reinforcements
Power Source	Single Cylinder 4 Cycle
Motor/Engine Type	Honda GX160
Specifications	GX160K1QXC9
Maximum Horsepower*	5.5 HP (4.1 kW) – *
Net Horse Power*	4.8 HP (3.6 kW) – *
Voltage	-NA-
Cycle*/Current/Phase	-NA-
Full Load Amps*	-NA-
Starting Amps*	-NA-
Displacement – cu in (l)	9.9 cu in (0.16 l)
Bore – in (mm)	2.7" (68)
Stroke – in (mm)	1.8" (45)
Cylinders/Cycle	Single Cylinder 4 Cycle
Fuel Capacity – gal (l)	.95 (3.6 l)
Oil Capacity – qt (l)	.63 (.6 l)
Air Filter	Four Stage Cyclone
Starter	Manual
Engine Cooling	Forced Air


SAW DIMENSIONS

Height – in (mm)	24-7/32" (615)
Minimum Saw Length (Transport) – in (mm)	39" (910)
Maximum Saw Length (Working) – in (mm)	56" (1,422)
Maximum Pointer Length – in (mm)	13-1/4" (337)
Frame Width – in (mm)	13-11/16" (348)
Saw Width – in (mm)	18-1/8" (460)
Front (Outside to Outside Wheel Width) – in (mm)	8-21/32" (220)
Rear (Outside to Outside Wheel Width) – in (mm)	13" (330)
Blade to Wall – in (mm)	7-1/2" (190)
Wheel Base Length – in (mm)	19" (483)
Weight Crated – lbs (kg)	151 (69)
Weight Uncrated – lbs (kg)	130 (59)

*= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER


GMAX DIAMOND BLADES

Designed with a thicker core that resists flexing and provides a straighter cut with less spalling, GMAX makes quick work of early entry/green concrete cutting. The anchor slot gullets reduce vibration for less chipping. And, the exclusive universal arbor adapts to all models.



Anchor Slot Gullet Technology

Increases productivity by reducing vibration, for a smoother cut, while keeping the blade cool and extending life.




Thicker Core

Resists flexing and provides a straighter and faster cut for less spalling.



Exclusive Universal Arbor

Allows the GMAX blade to be used on most early entry/green concrete saws.



Asphalt and Abrasive Materials

Asphalt, green concrete, asphalt over concrete, abrasive blocks, mortar and other abrasive materials.

DRY – EARLY ENTRY

Having the right blade for green concrete cutting is essential to getting the smoothest cut without spalling. The GMAX diamond blade series with its anchor slot gullet technology reduces vibration that results in chipping and irregular cut patterns. A thick core, special bond and diamond combination allows the blade to cut faster on most all saws, with perfection. Available in three different matrixes to reduce your time on the job in any aggregate type.

GMAX – HARD AGGREGATE (PURPLE)



Offers the best friability of diamond to ensure the operator maintains a smooth cut in the hardest materials, like flint and chert.

UPC	SIZE	MAX RPM	SEGMENT HEIGHT	MAX POWER
701846 41868	6 x .110 x 1-5/8 SC	10,185	.413"	4.3hp
701846 41863	8 x .110 x 1-5/8 SC	7,640	.413"	6hp
701846 41860	10 x .110 x 1-5/8 SC	6,115	.413"	13hp



GMAX – MEDIUM/HARD AGGREGATE (RED)



For non-to-medium abrasive sand, granite and quartz type materials. The high-quality bond and diamond configuration, along with the core features of the red specification's anchor slot gullet design to reduce spalling, ensures a smooth, flawless cut.

UPC	SIZE	MAX RPM	SEGMENT HEIGHT	MAX POWER
701846 41867	6 x .110 x 1-5/8 SC	10,185	.413"	4.3hp
701846 41864	8 x .110 x 1-5/8 SC	7,640	.413"	6hp
701846 41862	10 x .110 x 1-5/8 SC	6,115	.413"	13hp



GMAX – MEDIUM/SOFT AGGREGATE (YELLOW)



The yellow segment specification makes early entry cutting easy in limestone, granite and other softer aggregate mixtures.

UPC	SIZE	MAX RPM	SEGMENT HEIGHT	MAX POWER
701846 41866	6 x .110 x 1-5/8 SC	10,185	.413"	4.3hp
701846 41864	8 x .110 x 1-5/8 SC	7,640	.413"	6hp
701846 41861	10 x .110 x 1-5/8 SC	6,115	.413"	13hp



DRY – GREEN CONCRETE

GMAX – MULTI-PURPOSE



Designed specifically for our GC55 down-cut green concrete push saw, the GMAX Multi-Purpose blade is excellent in green concrete. The unique segment specification and anchor slot gullet allows this blade to be used in green concrete applications with outstanding results.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT	MAX POWER
701846 83758	NXDGRN0895	8 x .095 x 1-5/8	7,640	.393"	6hp
701846 75125	EE9110	9 x .110 x 1-5/8	6,600	.275"	6hp
701846 84508	EE10110	10 x .110 x 1-5/8	6,115	.275"	6hp



For precision green cutting, use the GMAX line of early entry blades, up to 10", on the **Norton Clipper GC55** push saw.

See page 46 for details.



Reinforced Concrete and Harder Building Materials

Reinforced concrete, hard bricks, limestone, terrazzo, and other hard materials.



WET – MEDIUM AGGREGATES

CHARGER



The steel core is designed to keep the cut straight while the .410" segment height prolongs cutting wear. Suitable for cutting medium aggregates with 35 HP up to 72 HP flat saws.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT	MAX POWER
70184681366	CGWCMD1412	14 x .125 x 1	4,365	.413"	35hp
70184681368	CGWCMD1812	18 x .125 x 1	3,395	.413"	35hp
70184683965	CGWCMD2012	20 x .125 x 1	3,055	.413"	35hp
70184681468	CGWCMD2415	24 x .155 x 1	2,550	.413"	35hp
70184681472	CGWCMD2615	26 x .155 x 1	2,350	.413"	35hp
70184683969	CGWCMD3618	36 x .187 x 1	1,700	.413"	35hp



CLASSIC



Laser welded blade at an economical price for general purpose cutting of cured concrete, medium hard aggregate and no steel reinforcement. The bond and diamond combination allow fast cutting action on limited horse powered flat saws.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT	MAX POWER
70184681360	CHWCGP1612	16 x .125 x 1	3,820	.315"	35hp
70184681361	CHWCGP1812	18 x .125 x 1	3,395	.315"	35hp
70184681362	CHWCGP2012	20 x .125 x 1	3,055	.315"	35hp
70184681465	CHWCGP2415	24 x .155 x 1	2,550	.315"	35hp
70184683833	CHWCGP2615	26 x .155 x 1	2,350	.315"	35hp
70184683386	CHWCGP3017	30 x .175 x 1	2,040	.315"	35hp





Reinforced Concrete and Harder Building Materials

Reinforced concrete, hard bricks, limestone, terrazzo, and other hard materials.

WET – ALL AGGREGATES



PARADIGM



Paradigm technology combines a unique specification blend that increases blade speed and product life to optimize performance in multiple flat saw horsepower ranges and aggregate types.

UPC	PART #	SIZE	AGGREGATE	SEGMENT HEIGHT	MAX POWER
701846 46319 RDS	C1170	18 x .125 x 1	Soft	.460"	35 - 48hp
701846 46384 RDS	C2160R	36 x .187 x 1	Soft	.539"	66hp
701846 46382 RDS	C2170R	30 x .165 x 1	Soft	.421"	66hp
701846 46394	C2370	20 x .155 x 1	Medium	.460"	66hp
701846 46395 RDS	C2370R	24 x .155 x 1	Medium	.421"	66hp
701846 46397 RDS	C2370R	26 x .155 x 1	Medium	.460"	35 - 48hp
701846 46398 RDS	C2370R	26 x .165 x 1	Medium	.500"	66hp
701846 46337	C1370	18 x .125 x 1	Medium	.460"	35 - 48hp
701846 46392	C2370	18 x .155 x 1	Medium	.460"	66hp
701846 46400 RDS	C2370R	30 x .165 x 1	Medium	.540"	66hp
701846 47390 RDS	C2770R	30 x .175 x 1	Medium	.460"	66hp
701846 46402 RDS	C2360R	36 x .187 x 1	Medium	.413"	66hp
701846 46475 RDS	C3360R	42 x .190 x 1	Medium	.540"	66hp
701846 46410	C2570	18 x .155 x 1	Hard	.460"	66hp
701846 46430	C2680HRAS	20 x .155 x 1	Hard	.510"	66hp
701846 46912 RDS	C3580	30 x .165 x 1	Hard	.540"	66hp
701846 46420 RDS	C2560R	36 x .187 x 1	Hard	.410"	66hp



WET – HARD AGGREGATES



CHARGER




For high performance wet cutting hard aggregates with medium reinforcement. The increased diamond depth in the segment specification allows extended life and fast cut for medium to large jobs. Deep sawing is easily achieved on saws up to 35 HP.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT	MAX POWER
701846 81367	CGWCHD1812	18 x .150 x 1	3,395	.590"	35hp
701846 83918	CGWCHD2015	20 x .150 x 1	3,055	.590"	35hp
701846 81467	CGWCHD2417	24 x .175 x 1	2,550	.590"	35hp
701846 83919	CGWCHD2421	24 x .215 x 1	2,550	.590"	35hp
701846 81471	CGWCHD2617	26 x .175 x 1	2,350	.590"	35hp
701846 83920	CGWCHD3017	30 x .175 x 1	2,040	.590"	35hp
701846 83921	CGWCHD3617	36 x .175 x 1	1,700	.590"	35hp



Asphalt and Abrasive Materials

Asphalt, green concrete, asphalt over concrete, abrasive blocks, mortar and other abrasive materials.



WET – ASPHALT



CHARGER




For large road and construction jobs with saws up to 35 HP. Higher diamond content increases productivity and offers faster cutting and longer life in asphalt and green concrete applications.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT	MAX POWER
701846 81478	CGWASP1412	14 x .125 x 1	4,365	.327"	35hp
701846 83912	CGWASP1612	16 x .125 x 1	3,820	.307"	35hp
701846 81479	CGWASP1812	18 x .125 x 1	3,395	.307"	35hp
701846 83927	CGWASP2417	24 x .175 x 1	2,550	.307"	35hp
701846 83928	CGWASP2615	26 x .155 x 1	2,350	.307"	35hp
701846 83929	CGWASP3017	30 x .175 x 1	2,040	.307"	35hp
701846 84024	CGWASP3618	36 x .187 x 1	1,700	.307"	35hp



Asphalt and Abrasive Materials

Asphalt, green concrete, asphalt over concrete, abrasive blocks, mortar and other abrasive materials.



WET – ASPHALT

CLASSIC

An economical choice for fast cutting and good life when performing jobs in a variety of abrasive materials such as green concrete and asphalt on saws up to 35 HP.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT	MAX POWER
70184681375	CHWASP1412	14 x .125 x 1	4,365	.326"	35hp
70184683895	CHWASP1612	16 x .125 x 1	3,820	.326"	35hp
70184681376	CHWASP1812	18 x .125 x 1	3,395	.326"	35hp
70184683897	CHWASP2012	20 x .125 x 1	3,055	.326"	35hp
70184681476	CHWASP2415	24 x .155 x 1	2,550	.326"	35hp
70184683900	CHWASP2418	24 x .187 x 1	2,550	.326"	35hp
70184683899	CHWASP2615	26 x .155 x 1	2,350	.326"	35hp
70184683903	CHWASP3018	30 x .187 x 1	2,040	.326"	35hp



WET – ASPHALT OVER CONCRETE

CHARGER

Manufactured for asphalt over concrete and other abrasive materials cutting. Designed to run efficiently on flat saws up to 35 HP while producing an even clean cut.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT	MAX POWER
70184681486	CGWAOC1812	18 x .125 x 1	3,395	.307"	35hp
70184681487	CGWAOC2415	24 x .150 x 1	2,550	.307"	35hp
70184683395	CGWAOC2617	26 x .175 x 1	2,350	.307"	35hp
70184683396	CGWAOC3018	30 x .187 x 1	2,040	.307"	35hp
70184683397	CGWAOC3618	36 x .187 x 1	1,700	.307"	35hp



CLASSIC

Lower cost but high performance blade ideal for general purpose cutting in asphalt over concrete applications on low horse power saws. Tailored with undercut protection to retard segment wear for maximum debris removal.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT	MAX POWER
70184681482	CHWAOC1412	14 x .125 x 1	4,365	.326"	35hp
70184681483	CHWAOC1812	18 x .125 x 1	8,725	.326"	35hp



DRY – ASPHALT AND CONCRETE

CLASSIC

Ideal blade for small-to-medium size jobs on low horsepower machines. Drop segment undercut protection reduces core wear when wet cutting in abrasive materials. Economically priced with good productivity in abrasive materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT	MAX POWER
70184603329	CHDAOC1812	18 x .125 x 1	3,395	.472"	20hp
70184603330	CHDAOC2015	20 x .150 x 1	3,055	.472"	20hp





RANGE OVERVIEW



MODEL#
BBL5247
UPC#
70184630007



MODEL#
BBC307
UPC#
70184630011



MODEL#
BBM307
UPC#
70184600684



MODEL#
CST120 ALU
UPC#
70184608390

**MAX. BLADE
CAPACITY**



**MAX.
HORSEPOWER**

5 HP (3.7 kW)

3 HP (2.2 kW)

3 HP (2.2kW)

2.4 HP (1.8 kW)

PRODUCT FEATURES



All Steel Frame

Super strong fillet welds deliver maximum strength and durability.



Sloped Front Water Pan

Allows complete control of the foot pedal and allows more control of depth of cut while reducing operator fatigue



Position of Cutting Head Blade Offset

Operator has a better view of material being cut and more stabilization of material on conveyor.



Having introduced the first masonry saw over 80 years ago, the Norton Clipper BBL heavy-duty block saws have become the industry standard for masons worldwide. Equipped in either electric or gas, these saws are available with single or three-phase electric motor as well as a more powerful 13HP gasoline engine. Having a rugged all-steel frame design with forklift brackets, these saws resist twisting and damage during transport around a job site. A blade capacity up to 24" and features of extended water pans and open back frame allows cutting of larger materials. The balanced cutting head makes for effortless cutting depth positioning.

TECHNICAL SPECIFICATIONS

PRODUCT #	BBL547	BBL527	BBL727	BBL5247	BBL7247
UPC – Single	701846 83211	701846 83150	N/A	701846 30007	N/A
UPC – 3 Phase	701846 83334	701846 83385	701846 83485	701846 30008	701846 30009
Blade Guard Capacity – in. (mm)	14" (355)	20" (508)	20" (508)	24" (609)	24" (609)
Maximum Depth of Cut – in. (mm)	5" (127)	8" (203)	8" (203)	10" (254)	10" (254)
Arbor Size – in. (mm)	1" (25.4)	1" (25.4)	1" (25.4)	1" (25.4)	1" (25.4)
Blade Flange Diameter – in. (mm)	4" (101)	4" (101)	4" (101)	4" (101)	4" (101)
Blade Shaft RPM	2,900	2,400	2,400	1,800	1,800
Blade Shaft Bearings	1" Heavy Duty Flange				
Blade Shaft Drive	2 Belt				
Blade Guard Attachment	All Steel, Stay Level				
Conveyor Cart	All steel cart, tilt-lock cart wheels, anti-skid surface, measuring rule; 45°/90° cutting guide				
Frame	Heavy-duty, jig-welded steel frame. Open construction for larger materials. Adjustable foot pedal and head height control.				
Water Pump	Electric – all electric saws have an electrical water pump				
Power Source	Electric				
Motor/Engine Type	Baldor				
Specifications	T.E.F.C. Thermal Protection				
Net Horsepower*	5 HP (3.7 kW)	5 HP (3.7 kW)	7-1/2 HP (5.6 kW)	5 HP (3.7 kW)	7-1/2 HP (5.6 kW)
Voltage	208-230 volts	208-230 volts	NA	208-230 volts	NA
3 PH – Voltage	230/460 volts	230/460 volts	230/460 volts	230/460 volts	230/460 volts
Cycle*/Current/Phase	60Hz/AC/1	60Hz/AC/1	NA	60Hz/AC/1	NA
3 PH – Cycle/Current/Phase	60Hz/AC/3	60Hz/AC/3	60Hz/AC/3	60Hz/AC/3	60Hz/AC/3
Full Load Amps*	20.6 Amp	20.6 Amp	16.8/8.4 Amps	20.6 Amp	16.8/8.4 Amp
Starter	Capacitor	Capacitor	Capacitor	Capacitor	Capacitor
Motor/Engine Cooling	Air	Air	Air	Air	Air

SAW DIMENSIONS

Saw Length – in. (mm)	60" (1,524)	60" (1,524)	60" (1,524)	60" (1,524)	60" (1,524)
Saw Width – in. (mm)	26" (660)	26" (660)	26" (660)	26" (660)	26" (660)
Saw Height – in. (mm)	54" (1,372)	54" (1,372)	54" (1,372)	54" (1,372)	54" (1,372)
Maximum Arbor Height Over Table – in. (mm)	30" (762)	30" (762)	30" (762)	30" (762)	30" (762)
Cart Length – in. (mm)	16-1/2" (418.5)	16-1/2" (418.5)	16-1/2" (418.5)	16-1/2" (418.5)	16-1/2" (418.5)
Cart Width – in. (mm)	23" (584)	23" (584)	23" (584)	23" (584)	23" (584)
Pan Length – in. (mm)	43-1/8" (1,095)	43-1/8" (1,095)	43-1/8" (1,095)	43-1/8" (1,095)	43-1/8" (1,095)
Pan Width – in. (mm)	22-7/16" (569)	22-7/16" (569)	22-7/16" (569)	22-7/16" (569)	22-7/16" (569)
Weight Crated – lbs (kg)	475 (216)	475 (216)	475 (216)	475 (216)	475 (216)
Weight Uncrated – lbs (kg)	440 (199.5)	440 (199.5)	440 (199.5)	440 (199.5)	440 (199.5)

575 VOLT AND 600 VOLT, 3-PHASE OPTIONS AVAILABLE. ASK CUSTOMER SERVICE FOR MORE DETAILS

ACCESSORIES	UPC	SMART PART #
BBL Electric Water Pump – PE-1	701846 68392	214169
BBL Conveyor Cart Replacement	003100 07390	083777
BBL Tilting Table	003100 04556	310004556
BBL Transport Accessory	003100 04609	310004609

***= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER**



BBL Electric Water Pump - PE-1



BBL Conveyor Cart Replacement



BBL Tilting Table



BBL Transport Accessory

PRODUCT FEATURES



Powerful Engine

Honda 13 HP engine with cyclone air filtration and power-enhancing jackshaft.



Accurate Adjustments

Ultra-strong foot pedal and hand wheel for exact depth adjustments make the BBL suitable for any cutting needs.



All-Steel Conveyor Cart

Long-lasting all-steel conveyor cart with tilt-lock wheels ensures smooth and precise cutting every time.



The Norton Clipper BBL series gasoline masonry saw features the powerful Honda GX390 engine with cyclone air filtration to meet any cutting needs. The BBL gas masonry saws feature a power-enhancing jack shaft that transmits more torque to the blade for faster cutting, and provides mechanical advantages to make for the easiest starting in colder weather. The BBL gas saw features the same rugged best-in-the-industry frame as the electric models. BBL series saws are designed with masons in mind and are available with 14", 20", and 24" blade capacities to meet your every need.

TECHNICAL SPECIFICATIONS

PRODUCT #	BBL1347	BBL1327	BBL13247
UPC – Single	701846 83214	701846 83212	701846 30010
Blade Guard Capacity – in. (mm)	14" (355)	20" (508)	24" (609)
Maximum Depth of Cut – in. (mm)	5" (127)	8" (203)	10" (254)
Arbor Size – in. (mm)	1" (25.4)	1" (25.4)	1" (25.4)
Blade Flange Diameter – in. (mm)	4" (101)	4" (101)	4" (101)
Blade Shaft RPM	2,900	2,400	1,800
Blade Shaft Bearings	1" Heavy Duty Flange		
Blade Shaft Drive	2 Belt		
Blade Guard Attachment	All Steel, Stay Level		
Conveyor Cart	All steel cart, tilt-lock cart wheels, anti-skid surface, measuring rule; 45°/90° cutting guide		
Frame	Heavy-duty, jig-welded steel frame. Open construction for larger materials. Adjustable foot pedal and head height control.		
Water Pump	Mechanically Belt Driven		
Power Source	Gasoline, Single Cylinder 4 Cycle		
Motor/Engine Type	Honda, GX390		
Specifications	GX390K1QXC9		
Net Horsepower*	11 HP (8.2 kW)	11 HP (8.2 kW)	11 HP (8.2 kW)
Starter	Recoil	Recoil	Recoil
Motor/Engine Cooling	Air	Air	Air
SAW DIMENSIONS			
Saw Length – in. (mm)	60" (1,524)	60" (1,524)	60" (1,524)
Saw Width – in. (mm)	26" (660)	26" (660)	26" (660)
Saw Height – in. (mm)	57" (1,448)	57" (1,448)	57" (1,448)
Maximum Arbor Height Over Table – in. (mm)	30" (762)	30" (762)	30" (762)
Cart Length – in. (mm)	16-1/2" (418.5)	16-1/2" (418.5)	16-1/2" (418.5)
Cart Width – in. (mm)	23" (584)	23" (584)	23" (584)
Pan Length – in. (mm)	43-1/8" (1,095)	43-1/8" (1,095)	43-1/8" (1,095)
Pan Width – in. (mm)	22-7/16" (569)	22-7/16" (569)	22-7/16" (569)
Weight Crated – lbs (kg)	475 (216)	475 (216)	475 (216)
Weight Uncrated – lbs (kg)	440 (199.5)	440 (199.5)	440 (199.5)

575 VOLT AND 600 VOLT, 3-PHASE OPTIONS AVAILABLE. ASK CUSTOMER SERVICE FOR MORE DETAILS

ACCESSORIES	UPC	SMART PART #
BBL Mechanical Water Pump Assembly (pulley not included)	003100 04436	073279
BBL 9' Mechanical Water Pump Kit (Water Pump, Pulley, Extended Shaft 9.18', and Hose)	701846 31858	701846 31858
BBL Water Pump Pulley	003100 04883	076552
BBL Heavy-Duty Water Pump	701846 28601	076031
BBL Conveyor Cart Replacement	003100 07390	083777
BBL Tilting Table	003100 04556	310004556
BBL Transport Accessory	003100 04609	310004609

***= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER**



BBL Mechanical Water Pump Assembly




BBL 9' Mechanical Water Pump Kit



BBL Water Pump Pulley



BBL Heavy-Duty Water Pump



BBL Conveyor Cart Replacement



BBL Tilting Table



BBL Transport Accessory

PRODUCT FEATURES



Water Pan Design

The extended length and open back make it easier for rip cutting of larger masonry materials.



Tilt-Locking Cart Wheels

Unique design that keeps conveyor in place with less shifting and smoother push/pull.



Stay Level Blade Guard

Full depth of cut.



Combines the performance of a full size masonry saw with the convenience of portability. Also available in gas or electric versions, the BBC saws have a rugged jig-welded frame, durable enough for even the heaviest work load. Available with 14" and 20" blade guard capacities making the BBC suitable for just about any job. Standard rear-wheel dolly design and removable legs make transport and set-up easy.

TECHNICAL SPECIFICATIONS

PRODUCT #	BBC157	BBC207	BBC347	BBC307
UPC	701846 82488	701846 82501	701846 08527	701846 30011
Blade Guard Capacity – in. (mm)	14" (355)	14" (355)	14" (355)	20" (508)
Maximum Depth of Cut – in. (mm)	5" (127)	5" (127)	5" (127)	8" (203)
Arbor Size – in. (mm)	1" (25.4)	1" (25.4)	1" (25.4)	1" (25.4)
Blade Flange Diameter – in. (mm)	4" (107)	4" (107)	4" (107)	4" (107)
Blade Shaft RPM	2,900	2,900	2,900	2,400
Blade Shaft Bearings	1" Heavy Duty Flange			
Blade Shaft Drive	1 Belt			
Blade Guard Attachment	All Steel, Stay Level			
Conveyor Cart	All steel cart, tilt-lock cart wheels, anti-skid surface, measuring rule; 45°/90° cutting guide			
Frame	Heavy-duty, jig-welded steel frame. Open construction for larger materials.			
Water Pump	Electric			
Power Source	Electric			
Motor/Engine Type	Baldor			
Specifications	T.E.F.C., Thermal Protection			
Net Horsepower*	1-1/2 HP (1.1 kW)	2 HP (1.5 kW)	3 HP (2.2 kW)	3 HP (2.2 kW)
Voltage	115/230 volts	115/230 volts	208-230 volts	208-230 volts
Cycle*/Current/Phase	60 Hz/AC/1	60 Hz/AC/1	NA	60 Hz/AC/1
Full Load Amps	13.4/6.7 Amps	16.8/8.4 Amps	13 Amps	13 Amps
Starter	Capacitor	Capacitor	Capacitor	Capacitor
Engine Cooling	Air	Air	Air	Air
SAW DIMENSIONS				
Saw Length – in. (mm)	60" (1,524)	60" (1,524)	60" (1,524)	60" (1,524)
Saw Width – in. (mm)	24" (609)	24" (609)	24" (609)	24" (609)
Saw Height – in. (mm)	34" (864)	34" (864)	34" (864)	34" (864)
Maximum Arbor Height Over Table – in. (mm)	24-1/2" (623)	24-1/2" (623)	24-1/2" (623)	24-1/2" (623)
Cart Length – in. (mm)	16" (404)	16" (404)	16" (404)	16" (404)
Cart Width – in. (mm)	19-3/8" (492)	19-3/8" (492)	19-3/8" (492)	19-3/8" (492)
Pan Length – in. (mm)	39-3/8" (1,000)	39-3/8" (1,000)	39-3/8" (1,000)	39-3/8" (1,000)
Pan Width – in. (mm)	18-1/8" (460)	18-1/8" (460)	18-1/8" (460)	18-1/8" (460)
Weight Crated – lbs (kg)	280 (127)	280 (127)	280 (127)	280 (127)
Weight Uncrated – lbs (kg)	250 (113)	250 (113)	250 (113)	250 (113)
ACCESSORIES	UPC	SMART PART #		
BBC Electric Water Pump – PE-1	701846 68392	214169		
BBC Conveyor Cart Replacement	003100 07367	083754		

*= DATA PROVIDED BY ENGINE MANUFACTURER

GENUINE NORTON CLIPPER DIAMOND BLADE INCLUDED WITH SAW.



BBC Electric Water Pump - PE-1



BBC Conveyor Cart Replacement

PRODUCT FEATURES



Powerful Engine

Honda 5.5 HP engine with cyclone air filtration and power-enhancing jackshaft.



Tilt-Locking Cart Wheels

Built-in transport wheels and fork lift brackets make for easy moving of the BBC Gas Masonry saws.



Stay Level Blade Guard

Large, extreme-duty cart which can handle the largest and heaviest of materials with ease.



The Norton Clipper BBC series gasoline masonry saws are designed to make easy work of any masonry job. Featuring a jack-shaft system, which enhances the power to the blade, for the fastest cutting and most powerful portable gasoline saw available. All-steel reinforced extended-length frames allow rip cutting of blocks. With forklift brackets, front and rear carry handles, wheel dolly, heavy-duty sealed bearings, stay-level blade guard system, and the choice of 14" or 20" blade guard sizes, the BBC gasoline masonry saw has all the features needed to handle any job. The BBC gasoline masonry saws are designed to handle all of your cutting needs from block, brick, and stone, to pavers; the BBC is the professional's choice.

TECHNICAL SPECIFICATIONS

PRODUCT #	BBC547	BBC507
UPC	701846 82175	701846 30012
Blade Guard Capacity – in. (mm)	14" (355)	20" (508)
Maximum Depth of Cut – in. (mm)	5" (127)	8" (203)
Arbor Size – in. (mm)	1" (25.4)	1" (25.4)
Blade Flange Diameter – in. (mm)	4" (101)	4" (101)
Blade Shaft RPM	2,900	2,400
Blade Shaft Bearings	1" Heavy Duty Flange	1" Heavy Duty Flange
Blade Shaft Drive	1 Belt	1 Belt
Blade Guard Attachment	All Steel, Stay Level	All Steel, Stay Level
Conveyor Cart	All steel cart, tilt-lock cart wheels, anti-skid surface, measuring rule; 45°/90° cutting guide	
Frame	Heavy-duty, jig-welded steel frame. Open construction for larger materials. Adjustable foot pedal and head height control.	
Water Pump	Mechanically Belt Driven	Mechanically Belt Driven
Power Source	Gasoline	Gasoline
Motor/Engine Type	Honda GX200	Honda GX200
Specifications	GX200K1QXC9	GX200K1QXC9
Net Horsepower*	5.5 HP (4.1 kW)	5.5 HP (4.1 kW)
Voltage	NA	NA
Cycle*/Current/Phase	NA	NA
Full Load Amps	NA	NA
Starter	Recoil	Recoil
Engine Cooling	Forced Air	Forced Air
Displacement – cu. In (l)	11.96 cu. In (0.196 l)	11.96 cu. In (0.196 l)
Bore – in. (mm)	2.7" (68)	2.7" (68)
Stroke – in. (mm)	2.12" (54)	2.12" (54)
Cylinders/Stroke	Single Cylinder 4 Cycle	Single Cylinder 4 Cycle
Fuel Capacity – gal. (l)	.95 gal. (3.6 l)	.95 gal. (3.6 l)
Oil Capacity – qt. (l)	.63 at. (.6 l)	.63 at. (.6 l)
Air Filter	Four Stage Cyclone	Four Stage Cyclone
SAW DIMENSIONS		
Saw Length – in. (mm)	50" (1,270)	53" (1,346)
Saw Width – in. (mm)	24" (609)	24" (609)
Saw Height – in. (mm)	38" (965)	38" (965)
Maximum Arbor Height Over Table – in. (mm)	24-1/2" (623)	24-1/2" (623)
Cart Length – in. (mm)	16" (404)	16" (404)
Cart Width – in. (mm)	19-3/8" (492)	19-3/8" (492)
Pan Length – in. (mm)	39-3/8" (1,000)	39-3/8" (1,000)
Pan Width – in. (mm)	18-1/8" (460)	18-1/8" (460)
Weight Crated – lbs (kg)	305 (138)	305 (138)
Weight Uncrated – lbs (kg)	275 (125)	275 (125)
ACCESSORIES	UPC	SMART PART #
BBC Mechanical Water Pump Assembly	003100 04237	072305
BBC 9' Mechanical Water Pump Kit (Water Pump, Pulley, Extended Shaft 9.18', and Hose)	701846 31858	701846 31858
BBC Water Pump Pulley	003100 04669	075270
BBC Conveyor Cart Replacement	003100 07367	83754

*= DATA PROVIDED BY ENGINE MANUFACTURER




BBC Mechanical Water Pump Assembly



BBC 9' Mechanical Water Pump Kit



BBC Water Pump Pulley



BBC Conveyor Cart Replacement

PRODUCT FEATURES



All Steel Construction

All welded strong honeycomb reinforcement design.



Clear View Cutting System

Offset of motor and blade allows operator to see the complete cutting surface.



Wet or Dry Cutting

Quick attach garden hose water system. Using the included wet cutting system meets OSHA Silica dust control requirements.



The innovative design of the BBM307 small masonry saws has been copied many times due to its compact, all-steel unibody construction, giving the best weight-to-strength distribution. A 14" blade capacity and ergonomically-designed, three-position locking, cutting head provides a safe, clear view of the work area. The BBM307 features a powerful 3HP brush motor, overload protection, garden hose connection, and a channeled-flow water pan to direct dust and slurry away from the operator.

TECHNICAL SPECIFICATIONS

PRODUCT #	BBM307	
UPC	701846 00684	
Blade Guard Capacity – in. (mm)	14" (355)	
Maximum Depth of Cut – in. (mm)	5" (127)	
Arbor Size – in. (mm)	1" (25.4)	
Blade Flange Diameter – in. (mm)	4" (101)	
Blade Shaft RPM	3,600	
Blade Shaft Bearings	Sealed Radial Bearings	
Blade Shaft Drive	Gear Drive	
Blade Guard Attachment	All Steel, Pivoting Posi-Loc Cutting Head	
Conveyor Cart	Aluminum With Steel Wheels and Seale Bearings	
Water Pump	Optional	
Frame	Steel Reinforced Frame	
Power Source	Electrical	
Motor/Engine Type	AC Universal Motor	
Specifications	Carbon Brush, Thermal Protection	
Net Horsepower*	3 HP (2.2 kW)	
Voltage	115 volts	
Cycle*/Current/Phase	60Hz/AC/1	
Full Load Amps	10 Amps	
Starter	NA	
Engine Cooling	Forced Air	
Air Filter	Yes	
SAW DIMENSIONS		
Saw Length – in. (mm)	31-1/2" (800)	
Saw Width – in. (mm)	18" (470)	
Saw Height – in. (mm)	30" (762)	
Maximum Arbor Height Over Table – in. (mm)	15-1/16" (383)	
Cart Length – in. (mm)	10-7/16" (265)	
Cart Width – in. (mm)	16-17/32" (420)	
Pan Length – in. (mm)	30-1/8" (765)	
Pan Width – in. (mm)	16" (405)	
Weight Crated – lbs (kg)	90 (40.8)	
Weight Uncrated – lbs (kg)	75 (34)	
ACCESSORIES	UPC	SMART PART #
Wet Kit	701846 00704	235003
Stand	701846 00691	235001
Conveyor Cart with Vacuum Attachment	701846 02862	233934

*= DATA PROVIDED BY ENGINE MANUFACTURER



Wet Kit



Stand



Conveyor Cart with Vacuum Attachment



Visit our YouTube page for more product information at:
www.youtube.com/NortonAbrasives

PRODUCT FEATURES




Powerful Induction Motor

Powerful long life dual voltage 115/230v commercial grade 2 HP induction motor.



Quiet Operation

Belt-driven blade shaft for smooth and quiet operation.



Less Mess

Channeled-flow water pan and conveyer cart direct dust and slurry away from the operator.



An evolutionary extension of the BBM307, the extremely portable BBM158 features a powerful, long-life commercial 2 HP induction motor which is designed for continuous cutting of bricks, block, pavers, stones, wall stones, and a variety of other masonry materials. The BBM158 motor has the ability to run on both 115v or 230v with a flick of a switch, allowing it to be used on most any job site. This machine is fully loaded with an all-steel honeycomb frame, heavy-duty conveyor cart with precision rollers for the straightest cuts, pivoting head for exact depth adjustments, belt-drive blade shaft for smoother and quieter operation, and includes a Norton Clipper 14" diamond blade for the fastest cutting; the BBM158 has all the features that professionals demand. If you want the most portable induction motor saw available, the BBM158 is the only choice.

TECHNICAL SPECIFICATIONS

PRODUCT #	BBM158	
UPC	701846 26327	
Blade Guard Capacity – in. (mm)	14" (355)	
Maximum Depth of Cut – in. (mm)	5" (127)	
Arbor Size – in. (mm)	1" (25.4)	
Blade Flange Diameter – in. (mm)	4" (101)	
Blade Shaft RPM	2,800	
Blade Shaft Bearings	Sealed Radial Bearings	
Blade Shaft Drive	Belt Drive	
Blade Guard Attachment	All Steel, Pivoting Cutting Head	
Conveyor Cart	Aluminum With Steel Wheels and Seale Bearings	
Water Pump	Optional	
Frame	Steel Reinforced Frame	
Power Source	Electrical	
Motor/Engine Type	Induction	
Specifications	T.E.F.C., Thermal Protection	
Net Horsepower*	2 HP	
Voltage	115/230 volts	
Cycle*/Current/Phase	60Hz/AC/1	
Full Load Amps	16.8/8.4 Amps	
Starter	NA	
Engine Cooling	Forced Air	
Air Filter	NA	
SAW DIMENSIONS		
Saw Length – in. (mm)	31-1/2" (800)	
Saw Width – in. (mm)	18" (470)	
Saw Height – in. (mm)	27-3/4" (695)	
Maximum Arbor Height Over Table – in. (mm)	16-17/32" (420)	
Cart Length – in. (mm)	10-7/16" (265)	
Cart Width – in. (mm)	16-17/32" (420)	
Pan Length – in. (mm)	30-1/8" (765)	
Pan Width – in. (mm)	16" (405)	
Weight Crated – lbs (kg)	150 (68)	
Weight Uncrated – lbs (kg)	123.2 (56)	
ACCESSORIES	UPC	SMART PART #
Wet Kit	701846 00704	235003
Stand	701846 00691	235001
Conveyor Cart with Vacuum Attachment	701846 02862	233934

*= DATA PROVIDED BY ENGINE MANUFACTURER

GENUINE NORTON CLIPPER DIAMOND BLADE INCLUDED WITH SAW.



Wet Kit


Stand

Conveyor Cart with Vacuum Attachment



Visit our YouTube page for more product information at:
www.youtube.com/NortonAbrasives

PRODUCT FEATURES



Guiding Bars

Strong chrome-plated guiding bars for high precision cutting.



Tilting Head

Allows cuts up to 45°.



Side Extension Table

Lets you easily adapt to different width materials.



As materials became longer, heavier, thicker and harder, an alternative solution was needed. With its long cutting lengths and powerful motor, coupled with a strong and robust frame to support heavy materials, this is the solution for the future of tile cutting.

The CST Series is designed to handle heavier and larger materials than a traditional masonry or tile saw for precision cutting of masonry, stone, flooring, and tile products. It allows miter cutting of material up to 45° and designed to cut materials up to 47-1/4" (1.2 m) in length. The CST120 ALUMINUM is a lightweight solution when mobility is the priority. It is a powerful machine offering long cutting lengths, folding legs, and transport wheels making it easy to transport.

TECHNICAL SPECIFICATIONS

PRODUCT #	CST120	CST120 ALU
UPC	701846 08389	701846 08390
Blade Guard Capacity – in. (mm)	14" (355)	14" (355)
Maximum Depth of Cut 90°– in. (mm)	4-5/16" (110)	4-5/16" (110)
Maximum Depth of Cut 45°– in. (mm)	3-15/64" (82.5mm)	3-15/64" (82.5mm)
Maximum Length of Cut – in. (mm)	47-1/4" (1,200)	47-1/4" (1,200)
Maximum Material Height – in. (mm)	5-7/64" (130)	5-7/64" (130)
Arbor Size – in. (mm)	1" (25.4)	1" (25.4)
Blade Flange Diameter – in. (mm)	4" (101)	4" (101)
Blade Shaft RPM	2,800	2,800
Blade Shaft Bearings	Sealed	Sealed
Blade Shaft Drive	Direct	Direct
Blade Guard Attachment	All Steel, with Intergrated Water System	All Steel, with Intergrated Water System
Conveyor Cart	Fixed Table	Fixed Table
Water Pump	Electric	Electric
Frame	Steel	Aluminum
Power Source	Electric	Electric
Motor/Engine Type	CEP	CEP
Specifications	T.E.F.C. Thermal Protection	T.E.F.C. Thermal Protection
Net Horsepower*	2.4 HP (1.80 kW)	2.4 HP (1.80 kW)
Voltage	115v	115v
Cycle*/Current/Phase	60Hz/AC/1	60Hz/AC/1
Full Load Amps	16 A	16 A
Starter	Capacitor	Capacitor
SAW DIMENSIONS		
Saw Length – in. (mm)	63" (1,600)	64-13/64" (1,630)
Saw Width – in. (mm)	26" (660)	26" (660)
Saw Height – in. (mm)	53-1/8" (1,350)	53-1/8" (1,350)
Maximum Arbor Height Over Table – in. (mm)	12-7/64" (307.5)	12-7/64" (307.5)
Table Length – in. (mm)	51-45/64" (1,315)	51-45/64" (1,315)
Table Width – in. (mm)	21-1/2" (545)	21-1/2" (545)
Pan Length – in. (mm)	61" (1,550)	61" (1,550)
Pan Width – in. (mm)	25-39/64" (650)	25-39/64" (650)
Weight Crated – lbs (kg)	392 (178 kg)	238 (108 kg)
Weight Uncrated – lbs (kg)	352 (160 kg)	198 (90 kg)
ACCESSORIES	UPC	SMART PART #
Slide Stop	003104 78996	310478 996
Side Extension Flat (0.55 x 0.45 M)	003104 79000	310479 000
Side Extension with Rollers (1 x 0.50 M)	003104 78999	310478 999
Laser Cutting Guide with Hardware	701846 08425	701846 08425
Angle Guide	003104 79001	310479 001
Water Pump 115v/60Hz/1	701846 09058	701846 09058

*= DATA PROVIDED BY ENGINE MANUFACTURER



Slide Stop



Side Extension Flat (0.55 x 0.45 M)



Side Extension with Rollers (1 x 0.50 M)


get the silent treatment **AND ENJOY EVERY MINUTE**

Defying everything you've heard before, the Norton Clipper Silencio is more than just a sandwiched silent blade. We take sound dampening to another level by reducing noise up to 15 dB(A). Masons enjoy the patented technology performance benefits while nearby workers and onlookers enjoy quieter times.

If cost is a factor, try the new Silencio Charger that cuts noise with a unique more economical sandwich core design.



Scan to
learn more



.590" Segment Height

New specification provides premium life and performance.



New Gullet Design

Reduces cutting noise by as much as 15 dB(A).



Patent-Pending Steel Center

Design absorbs noise and vibration.



General Purpose and Masonry Building Materials

Blocks, medium-hard building bricks, paving slabs, concrete roof tiles and other medium-hard materials.

WET – SEGMENTED RIM



SILENCIO



With a laser-welded segment height up to .590" and newly developed specification, this blade maximizes cutting performance and product life when wet cutting hard natural stone materials. And, it's quieter – reducing cutting noise by up to 15 dB(A), thanks to the use of high-technology materials and a patent-pending steel-center design. Safer for high traffic environments and less disruptive to work locations.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 84534	SILMBR14125	14 x .125 x 1	4,365	.590"
701846 84535	SILMBR20125	20 x .125 x 1	3,055	.590"



SILENCIO CHARGER



A more economical silent core design, serrated segment shape, and longer life formula increase the material cutting range and blade life while reducing noise. A perfect solution when cutting in sound sensitive work areas.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 03318	SILCG14122	14 x .122 x 1	4,365	.472"



CHARGER



High performance wet cutting with an extra wide .263" segment specification that allows thorough cleaning and extended life in a variety of materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 81338	CGWMGP1401	14 x .100 x 1	4,365	.275"
701846 81339	CGWMGP2001	20 x .125 x 1	3,055	.263"



CLASSIC



The softer bond provides longer life at an economical price for small to medium size jobs on compact masonry saws.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 81331	CHWMGP1401	14 x .100 x 1	4,365	.275"
701846 81332	CHWMGP2001	20 x .125 x 1	3,055	.263"





General Purpose and Masonry Building Materials

Blocks, medium-hard building bricks, paving slabs, concrete roof tiles and other medium-hard materials.

DRY – SEGMENTED RIM



CHARGER



High performance dry cutting of a variety of materials. The segment specification allows extended life and fast cut for medium to large jobs.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184681429	CGDMGP2001	20 x .125 x 1	3,055	.263"



CLASSIC



The bond provides longer life at an economical price for small to medium size jobs on smaller compact masonry saws cutting a combination of brick and soft block.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184684251	CODMGP10H2001	20 x .165 x 1	3,055	.393"



VALUPLUS



For value and performance on small to medium size jobs. The sintered blade cuts unreinforced soft to medium concrete fast on saws up to 13 HP.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184684181	VPHSGP1420	14 x .110 x 1"/20mm	5,460	.393"
70184684428	VPHSGP1420 20PK	14 x .110 x 1"/20mm	5,460	.393"



DRY – TURBO RIM



CHARGER



Combines the characteristics of standard Charger blade with a turbo rim configuration for cutting hard, dense materials with minimal effort. A better bond and diamond concentration for maximum cutting speed, life and quality of cut.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184684525	CGHSTS1420	14 x .125 x 1"/20mm	5,460	.472"





Reinforced Concrete and Harder Building Materials

Reinforced concrete, hard bricks, limestone, terrazzo, and other hard materials.

DRY – SEGMENTED RIM



DUO EVO



The unique shape of the DUO EVO and DUO segments optimizes the angle of attack while enhancing the evacuation of the particles. The result is an exceptional cutting speed allied with optimum performance life up to 50% over other blades in critically hard materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 84218	DUOEVO14118	14 x .118 x 1"/20mm	5,460	.590"
701846 93356	DUOEVO16130	16 x .130 x 1"/20mm	4,500	.472"



DUO



The original DUO. The innovative, exclusive design introduced in 2002 has become a dominant name in the market. The unique dual segment per land technology provides excellent cutting speed with low vibration and high comfort of cut. The exclusive arrow shape gullets not only indicate blade direction but they also assist in fast removal of cutting debris. Maximum performance when cutting medium to hard materials – general purpose.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 83612	DUO14110	14 x .110 x 1"/20mm	5,460	.393"
701846 83613	DUO14125	14 x .125 x 1"/20mm	5,460	.393"
701846 83798	DUO16125	16 x .125 x 1"/20mm	4,500	.393"



CHARGER




High performance when on all kinds of hard materials. Smooth, fast and accurate cuts when dry cutting on larger masonry saws.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 81426	CGDMBR1401	14 x .110 x 1	4,365	.263"
701846 81427	CGDMBR2001	20 x .125 x 1	3,055	.263"
701846 84556	CODMBR2401	24 x .150 x 1	2,550	.275"



Asphalt and Abrasive Materials

Asphalt, green concrete, asphalt over concrete, abrasive blocks, mortar and other abrasive materials.



DRY – SEGMENTED RIM



CHARGER



High performance wear-resistant bond for dry cutting all kinds of soft and abrasive materials. Excellent blade life and cut speed when cutting on large upright masonry saws for commercial production.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184681330	CGDMBL1401	14 x .100 x 1	4,365	.326"
70184681424	CGDMBL2001	20 x .125 x 1	3,055	.326"



CLASSIC



Ideal blade for small to medium size jobs with masonry saws. Economically priced with good productivity in abrasive materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184603329	CHDAOC1812	18 x .125 x 1	3,395	.472"
70184603330	CHDAOC2015	20 x .150 x 1	3,055	.472"



VALUPLUS



Dry cutting sintered segment blade for abrasive materials. Drop-segment wear-retardant extends life of core. Economically priced with good performance in asphalt, green concrete and other abrasive materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184603333	VPHSABR14125	14 x .125 x 1"/20mm	5,460	.452"



Norton Clipper Classic and ValuPlus


These Classic blades are an exceptional choice for general purpose wet or dry cutting on low horsepower saws. Soft enough to handle concrete but with drop segments on the core to maximize segment life when cutting abrasive materials like asphalt and block.

When a more economical solution is what you're after, try the new ValuPlus sintered segment blade for abrasive materials.



Natural Stone and Tiles

Ceramic and stone tiles, granite, marble, very hard bricks and other very hard and dense materials.



WET – SEGMENTED RIM – HARD REFRACTORIES, TILES



CHARGER



High performance wet cutting of a variety of materials. Industrial grade segment specification allows extended life and fast cut on refractory materials with 70% plus alumina.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184681348	NXWRHD1401	14 x .095 x 1	4,365	.326"
70184681456	NXWRHD1801	18 x .125 x 1	3,395	.326"
70184681457	NXWRHD2001	20 x .125 x 1	3,055	.326"



CHARGER



High performance solution for small to medium size jobs. Efficient cutting of thick granite, marble and refractory materials with 70% or less alumina.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184681453	CGWRGP1401	14 x .100 x 1	4,365	.250"
70184681454	CGWRGP1801	18 x .125 x 1	3,395	.250"
70184681455	CGWRGP2001	20 x .125 x 1	3,055	.250"



WET – CONTINUOUS RIM – HARD REFRACTORIES, TILES



SLICER



Razor like cut, but with high tensile strength steel core for greater accuracy and less wobbling. The bond and diamond specification enhance cutting speed and improve blade life, particularly in hard materials for premium performance.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
70184684187	NXSLC1401	14 x .080 x 1	4,365	.393"



SLICER TURBO MESH



Unique mesh segment designed for fast cutting and minimal chipping on extra hard ceramics, porcelain and other hard/dense materials. The reinforced inner core prevents undesirable flexing while cutting in demanding applications.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
70184608972	NXSLCTM1401	14 x .090 x 1"/20mm	4,365	.394"



DRY – TURBO RIM – GRANITE, MARBLE, TILES



AERO-JET



New innovative design allows for very fast, smooth cutting. The improved .392" high segment rim adds extremely long life whether cutting wet or dry in hard materials. Exclusive arch-shaped protection inserts allow for precision straight cuts. The ventilated waved steel core for better cooling and intensive use. Exceptional cutting on a very wide range of materials with a high quality finished cut.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
70184683785	AEROHS1420	14 x .125 x 1"/20mm	5,460	.392"



Multi-Purpose, All Materials

Concrete, reinforced concrete, granite, building materials, thin steel sections, angle iron up to 1/2" material thickness, rebar up to no. 5.



DRY – SEGMENTED RIM – SOFT TO HARD AGGREGATES



4X4



Multi-purpose laser welded blade for dry cutting a range of construction materials without sacrificing performance or price. Depth of cut is easily controlled with the patented depth-of-cut indicators cut into the steel core. Anti-crack gullets for enhanced safety cutting steel and metal (up to 5mm thick).

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 84547	4X414125	14 x .125 x 1"/20mm	5,460	.393"
701846 45306	4X416125	16 x .125 x 1"/20mm	4,500	.393"



MULTI-CUT

NEW



The perfect combination of performance and price on high-speed, masonry, and floor saws. The laser welded segments are designed for cutting speed and long life, while a precise 1"/20mm laser cut dual arbor hole provides consistently secure mounting on the saw. Premium features combined with low pricing make for a reliable, fast cutting, long life blade for a variety of common construction materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 09680	MULTICUT14125	14 x .125 x 1"/20mm	5,460	.472"
701846 31788	MULTICUT16125	16 x .125 x 1"/20mm	4,500	.472"



RANGE OVERVIEW



MODEL#

CTC1020XL

CTC705

UPC#

70184630013

70184681496

MAX. BLADE
CAPACITY10"
(254mm)7"
(178mm)MAX.
HORSEPOWER

2 HP (1.5 kW)

1 HP (0.7 kW)

PRODUCT FEATURES



2HP Motor

More powerful than using conventional 1.5HP and can make a rip cut of 24" tile.



Light-Weight

60 lbs vs. standard 100-125 lbs for easier transportation.



Aluminum Rails with Stainless Insert

Provides long life and easy portability due to low coefficient of friction, creating smoother slide.



Built with the professional in mind, the CTC1020XL is the newest to the tile industry. The powerful 2HP motor makes ripping materials, up to 24", trouble-free. The combination of having a light-weight, sturdy frame and a newly designed polypropylene pan, to help reduce area contamination, gives an operator all the essentials to get the job done quickly and efficiently.

TECHNICAL SPECIFICATIONS

PRODUCT #	CTC1020XL	
UPC	701846 30013	
Blade Guard Capacity – in. (mm)	10" (254)	
Maximum Depth of Cut – in. (mm)	3-3/4" (88)	
Arbor Size – in. (mm)	5/8"	
Blade Flange Diameter – in. (mm)	3 (78)	
Blade Shaft RPM	3,000	
Maximum Material Size – in. (mm)	24" x 24"	
Rip Cut Size – in. (mm)	24" (610)	
Diagonal Size – in. (mm)	18" (457)	
Cutting Head	Cast Aluminum	
Built-In 45° Miter Cut	NO, Includes Miter Block	
Cutting Table	Aluminum With Rubber Coating	
Water Pump	YES	
Power Source	Electric	
Motor/Engine Type	Brush Motor with Thermal Protection	
Maximum Horsepower*	2 HP	
Voltage	115 volt	
Cycle*/Current/Phase	60 Hz/AC/1	
Full Load Amps	13 Amp	
SAW DIMENSIONS		
Saw Length – in. (mm)	51-7/8" (1,318)	
Saw Width – in. (mm)	25-3/16" (640)	
Saw Height – in. (mm)	20-7/8" (530)	
Saw Height With Stand – in. (mm)	41-13/16" (1,240)	
Arbor to Top of Cart – in. (mm)	4-3/4" (120)	
Cart (Table) Length – in. (mm)	16" (406)	
Cart (Table) Width – in. (mm)	16-9/64" (410)	
Cart Travel – in. (mm)	22-5/8" (575)	
Pan Length – in. (mm)	51-7/8" (1,318)	
Pan Width – in. (mm)	25-3/16" (640)	
Weight Crated – lbs (kg)	75 (34)	
Weight Uncrated – lbs. (kg)	65 (29.5)	
ACCESSORIES	UPC	SMART PART #
Electric Water Pump - PE-1	701846 68392	214169
Premium Stand w/Work Table	701846 43045	242098
Adjustable Angle Guide	701846 80907	233043

*= DATA PROVIDED BY ENGINE MANUFACTURER
GENUINE NORTON CLIPPER DIAMOND BLADE INCLUDED WITH SAW.



Electric Water Pump



Premium Stand with Work Table




Adjustable Angle Guide

PRODUCT FEATURES



Motor Upgrade

Strong belt-driven 1 HP motor provides powerful and precise cutting.



Light-Weight Conveyor

Smooth slide creates straight cuts and has a locking mechanism for easier transportation.



Water Pump

High intake and output to keep fresh water in pan with a durable filter to keep debris out.



A great value for a 7" tile saw that can handle the small to medium size jobs. This saw has many features of more expensive tile saws, like a belt-driven 1 HP motor for maximum motor-to-blade power. A sturdy aluminum cutting table with anti-skid top for keeping material in place while cutting and a light-weight water pan for easy cleaning and/or single operator use getting on and off the site.

TECHNICAL SPECIFICATIONS

PRODUCT #	CTC705	
UPC	701846 81496	
Blade Guard Capacity – in. (mm)	7" (177)	
Maximum Depth of Cut – in. (mm)	2-1/4" (57)	
Arbor Size – in. (mm)	5/8"	
Blade Flange Diameter – in. (mm)	2-1/2" (66)	
Blade Shaft RPM	6,000	
Maximum Material Size – in. (mm)	17" (431)	
Rip Cut Size – in. (mm)	17" (431)	
Diagonal Size – in. (mm)	12" (305)	
Cutting Head	Cast Aluminum	
Built-In 45° Miter Cut	No	
Cutting Table	Aluminum	
Water Pump	Yes	
Power Source	Electric	
Motor/Engine Type	Carbon Brush	
Maximum Horsepower*	1 HP (075kW)	
Voltage	115 volt	
Cycle*/Current/Phase	60 Hz/AC/1	
Full Load Amps	8.5 Amps	
SAW DIMENSIONS		
Saw Length – in. (mm)	30" (762)	
Saw Width – in. (mm)	19-3/4" (502)	
Saw Height – in. (mm)	17-1/2" (445)	
Saw Height With Stand – in. (mm)	47-3/4" (1,213)	
Arbor to Top of Cart – in. (mm)	Adjustable	
Cart (Table) Length – in. (mm)	14-1/4" (362)	
Cart (Table) Width – in. (mm)	15" (381)	
Cart Travel – in. (mm)	18-3/4" (477)	
Pan Length – in. (mm)	30" (762)	
Weight Crated – lbs. (kg)	50 (22.7)	
Weight Uncrated – lbs. (kg)	43 (19.5)	
ACCESSORIES	UPC	SMART PART #
Electric Water Pump - PE-1	701846 68392	214169
Premium Stand w/Work Table	701846 43045	242098
Adjustable Angle Guide	701846 80907	233043

*= DATA PROVIDED BY ENGINE MANUFACTURER
GENUINE NORTON CLIPPER DIAMOND BLADE INCLUDED WITH SAW.



Electric Water Pump




Premium Stand with Work Table



Adjustable Angle Guide


razor sharp FOR THE EDGE YOU NEED

To produce razor-like cuts in porcelain or ceramic, marble and granite, the Slicer diamond blade is unbeatable. The high tensile, strengthened steel core blade extends life and speed to provide a clean, crisp, accurate cut. Don't settle, when Slicer can help you achieve exceptional results.




Premium Segment Specification

Special bond for the smoothest cut and finish, ideal for porcelain.



Precision Cuts, Every Time

Razor-thin design reduces loss of material




Thinnest Cuts, Longest Life

Thin, high tensile strength steel core for better accuracy and less wobbling.

Natural Stone and Tiles

Ceramic and stone tiles, granite, marble, very hard bricks and other very hard and dense materials.



WET – CONTINUOUS RIM

SLICER TURBO MESH

Unique mesh segment designed for fast cutting and minimal chipping on extra hard ceramics, porcelain and other hard/dense materials. The reinforced inner core prevents undesirable flexing while cutting in demanding applications.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
701846 08970	NXSLCTM0700	7 x .080 x DM-7/8-5/8	8,730	.394"
701846 08971	NXSLCTM1000	10 x .080 x 1-7/8-5/8	6,115	.394"



SLICER

Razor-like cut, but with high tensile strength steel core for greater accuracy and less wobbling. The bond and diamond specification enhance cutting speed and improve blade life for premium performance, particularly in porcelain tile and other hard materials.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
701846 84183	NXSLC0700	7 x .060 x 5/8	8,730	.393"
701846 84184	NXSLC0800	8 x .060 x 5/8	7,640	.393"
701846 84185	NXSLC1000	10 x .060 x 5/8	6,115	.393"



CLASSIC


Excellent quality with good performance in general purpose materials. The right bond and diamond content allows clean cutting with long use. Well suited for softer tile or stone materials on low horsepower tile saws.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
701846 84017	CON7WT	7 x .065 x 5/8	8,730	.393"
076607 02785	CON8WT	8 x .070 x 5/8	7,640	.393"
076607 02784	CON10WT	10 x .070 x 5/8	6,115	.393"



Natural Stone and Tiles

Ceramic and stone tiles, granite, marble, very hard bricks and other very hard and dense materials.



DRY – CONTINUOUS RIM

CLASSIC



An economical solution for small to medium size jobs cutting softer ceramic tile and stone materials with efficient cutting ability.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
076607 02788	CON7DT	7 x .090 x DM-7/8-5/8	8,730	.275"

ADDITIONAL BLADE DIAMETERS AVAILABLE IN THE PORTABLE HAND-HELD SECTION OF THIS CATALOG.



VALUPLUS



A value price point for small to medium size jobs cutting standard ceramic tile with efficient cutting on low horsepower tile saws.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
701846 84089	VPDT0700	7 x .090 x DM-7/8-5/8	8,730	.197"

ADDITIONAL BLADE DIAMETERS AVAILABLE IN THE PORTABLE HAND-HELD SECTION OF THIS CATALOG.



DRY – TURBO RIM

AERO-JET



New innovative design allows for very fast, smooth cutting. The improved .392" high segment rim adds extremely long life whether cutting wet or dry in hard materials. Exclusive arch-shaped protection inserts allow for precision straight cuts. The ventilated waved steel core for better cooling and intensive use. Exceptional cutting on a very wide range of materials with a high quality finished cut.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
701846 83781	AERO0700	7 x .090 x DM-7/8-5/8	8,730	.392"
701846 83783	AERO1000	10 x .110 x 1-7/8-5/8	6,115	.392"

ADDITIONAL BLADE DIAMETERS AVAILABLE IN THE PORTABLE HAND-HELD SECTION OF THIS CATALOG.





General Purpose and Masonry Building Materials

Blocks, medium-hard building bricks, paving slabs, concrete roof tiles and other medium-hard materials.

DRY – SEGMENTED RIM



CHARGER



High performance dry cutting of a variety of materials. The segment specification allows extended life and fast cut for medium to large jobs.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
07660704019	CGDSEG1000	10 x .080 x 1-7/8-5/8	6,115	.393"



CLASSIC



The improved bond provides longer life at an economical price for small to medium size jobs on smaller tile and rail saws.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
07660701201	CODSEG1000	10 x .080 x 1-7/8-5/8	6,115	.275"



DRY – TURBO RIM



CHARGER



Combines the characteristics of standard Charger blade with a turbo rim configuration for cutting hard, dense materials with minimal effort. A better bond and diamond concentration for maximum cutting speed, life and quality of cut.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
07660704022	CGTURB0700	7 x .090 x DM-7/8-5/8	8,725	.393"



CLASSIC



Great blade for cutting softer tile, brick and pavers with hand held tools or smaller tile saws. Offers chip-free cutting and good blade life.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
07660702787	COTURB0700	7 x .090 x DM-7/8-5/8	8,725	.315"
07660704016	0700TURB05PK	7 x .090 x DM-7/8-5/8	8,725	.315"
07660702780	COTURB1000	10 x .100 x 1-7/8-5/8"	6,115	.275"



VALUPLUS



For value and performance on small to medium size jobs cutting soft brick and tile. The sintered turbo continuous rim cuts fast with a smoother quality of cut.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
70184684107	VPTURB0700	7 x .090 x DM-7/8-5/8	8,730	.315"





General Purpose and Masonry Building Materials

Blocks, medium-hard building bricks, paving slabs, concrete roof tiles and other medium-hard materials.



FOR USE ON CORDLESS POWER TOOLS ONLY



SILENCIO



Laser-welded segments for maximum attachment security in all materials. Sound-dampening sandwich core reduces sound while cutting. Premium segment for faster cutting in difficult materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184608514	SILENCIO0900	9 x .090 x 7/8	6,650	.393"



SILENCIO CLASSIC



With the same features as the original Silencio, the Silencio Classic has longer life segments on a sound-dampened core for softer, more abrasive materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184608591	SILCLB0900	9 x .090 x 7/8"	6,650	.393"



Multi-Purpose, All Materials

Concrete, reinforced concrete, granite, building materials, thin steel sections, angle iron up to 1/2" material thickness, rebar up to no. 5.



FOR USE ON CORDLESS POWER TOOLS ONLY



DIALAST



Vacuum brazed diamond for uni-directional cutting. Cooling holes in core for added cooling to cut harder materials. Solid core gullet design for smooth continuous cutting.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184608590	DIABAT0900	9 x .070 x 7/8	6,650	.125"



Abrasive Cut-off Wheel for Cordless Tools

Steel & Stainless

General-purpose ferrous metals (steel, iron, welds), stainless steel and other high strength alloys.



ABRASIVE CUT-OFF WHEEL FOR USE ON CORDLESS POWER TOOLS ONLY



CHARGER



This Norton Clipper abrasive cut-off wheel completes the 9" offering for use on cordless tools in metal applications. Thinner abrasive wheel for less drag and power draw on cordless tools. Reinforced metal arbor to enhance push and cutting speed. Cordless abrasive blend to maximize cutting speed and tool battery life.

UPC	SIZE	APPLICATION	MAX RPM	STD PKG
70184609080	9 x .078 x 7/8	Metal / Stainless	6,600	25



MAKE YOUR
BATTERY TOOL
MORE VERSATILE!





General Purpose and Masonry Building Materials

Blocks, medium-hard building bricks, paving slabs, concrete roof tiles and other medium-hard materials.

DRY – SEGMENTED RIM



DUO

The original DUO. The innovative, exclusive design introduced in 2002 has become a dominant name in the market. The unique dual segment per land technology provides excellent cutting speed with low vibration and high comfort of cut. The exclusive arrow shape gullets not only indicate blade direction but they also assist in fast removal of cutting debris. Maximum performance when cutting hard materials and fiber cement board.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184684526	DUO0450	4-1/2 x .086 x 7/8-5/8-20mm	13,300	.393"
70184684527	DUO0500	5 x .086 x 7/8-5/8-20mm	12,000	.393"
70184684129	DUO0700	7 x .098 x DM-7/8-5/8	8,730	.393"



CHARGER

High performance dry cutting of a variety of materials. The segment specification allows extended life and fast cut for medium to large jobs.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184681505	CGDSEG0400	4 x .080 x 7/8-5/8-20mm	15,000	.393"
07660704021	CGDSEG0450	4-1/2 x .080 x 7/8-5/8-20mm	13,300	.393"
70184682851	CGDSEG0500	5 x .080 x 7/8-5/8-20mm	12,000	.393"
70184683820	CGDSEG0600	6 x .080 x 7/8-5/8-20mm	10,185	.393"
07660704020	CGDSEG0700	7 x .090 x DM-7/8-5/8	8,730	.393"



CLASSIC

The improved bond provides longer life at an economical price for small to medium size jobs on smaller tile and rail saws.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
07660702791	CODSEG0400	4 x .080 x 7/8-5/8-20mm	15,000	.393"
07660702789	CODSEG0450	4-1/2 x .080 x 7/8-5/8-20mm	13,300	.393"
70184684006	CODSEG0600	6 x .080 x 7/8-5/8-20mm	10,185	.393"
07660702786	CODSEG0700	7 x .090 x DM-7/8-5/8	8,730	.315"



VALUPLUS

For value and performance on small to medium size jobs cutting soft abrasive materials like brick and tile. The sintered rim delivers a quality cut and good life.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184684098	VPSEG0400	4 x .080 x 7/8-5/8-20mm	15,000	.315"
70184684099	VPSEG0450	4-1/2 x .080 x 7/8-5/8-20mm	13,300	.315"
70184684100	VPSEG0700	7 x .090 x DM-7/8-5/8	8,730	.315"





General Purpose and Masonry Building Materials

Blocks, medium-hard building bricks, paving slabs, concrete roof tiles and other medium-hard materials.

DRY – TURBO RIM



CHARGER



Combines the characteristics of standard Charger blade with a turbo rim configuration for cutting hard, dense materials with minimal effort. A better bond and diamond concentration for maximum cutting speed, life and quality of cut.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
07660705475	CGTURB0400	4 x .080 x 7/8-5/8-20mm	15,000	.393"
07660704023	CGTURB0450	4-1/2 x .080 x 7/8-5/8-20mm	13,300	.393"
70184682853	CGTURB0500	5 x .080 x 7/8-5/8-20mm	12,000	.393"
07660704022	CGTURB0700	7 x .090 x DM-7/8-5/8	8,730	.393"



CLASSIC



Great blade for cutting softer tile, brick and pavers with hand held tools or smaller tile saws. Offers chip-free cutting and good blade life.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
07660702792	COTURB0400	4 x .080 x 7/8-5/8-20mm	15,000	.315"
07660702790	COTURB0450	4-1/2 x .080 x 7/8-5/8-20mm	13,300	.315"
07660702787	COTURB0700	7 x .090 x DM-7/8-5/8	8,730	.315"



VALUPLUS




For value and performance on small to medium size jobs cutting soft brick and tile. The turbo continuous rim cuts fast with a smoother quality of cut.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184684105	VPTURB0400	4 x .080 x 7/8-5/8-20mm	15,000	.315"
70184684106	VPTURB0450	4-1/2 x .080 x 7/8-5/8-20mm	13,300	.315"
70184684107	VPTURB0700	7 x .090 x DM-7/8-5/8	8,730	.315"



Natural Stone and Tiles

Ceramic and stone tiles, granite, marble, very hard bricks and other very hard and dense materials.



DRY – TURBO RIM



AERO-JET



New innovative design allows for very fast, smooth cutting. The improved .392" high segment rim adds extremely long life whether cutting wet or dry in hard materials. Exclusive arch-shaped protection inserts allow for precision straight cuts. The ventilated waved steel core for better cooling and intensive use. Exceptional cutting on a very wide range of materials with a high quality finished cut.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
70184683778	AERO0400	4 x .070 x 7/8-5/8-20mm	15,000	.392"
70184683779	AERO0450	4-1/2 x .070 x 7/8-5/8-20mm	13,300	.392"
70184683780	AERO0500	5 x .070 x 7/8-5/8-20mm	12,000	.392"
70184683781	AERO0700	7 x .090 x DM-7/8-5/8	8,730	.392"



WET - CONTINUOUS RIM



SLICER TURBO MESH



Unique mesh segment designed for fast cutting and minimal chipping on extra hard ceramics, porcelain and other hard/dense materials. The reinforced inner core prevents undesirable flexing while cutting in demanding applications.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
70184609059	NXSLCTM0450	4 1/2" x .050" x 7/8"-5/8"-20mm	13,300	.394"
70184609060	NXSLCTM0500	5" x .050" x 7/8"-5/8"-20mm	12,000	.394"
70184608970	NXSLCTM0700	7" x .080" x DM-7/8"-5/8"	8,730	.394"



DRY – CONTINUOUS RIM



CLASSIC



An economical solution for small to medium size jobs cutting softer ceramic tile and stone materials with efficient cutting ability.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
07660702793	CON4DT	4 x .080 x 7/8-5/8-20mm	15,000	.275"
07660704018	0400TURBO5PK	4 x .080 x 7/8-5/8-20mm	15,000	.315"
07660701194	CON45DT	4-1/2 x .080 x 7/8-5/8-20mm	13,300	.275"
07660704017	0450TURBO5PK	4-1/2 x .080 x 7/8-5/8-20mm	13,300	.315"
07660705344	COMBO Pack	4-1/2 x .080 x 7/8-5/8-20mm	13,300	.315"
70184684011	COTURB0600	6 x .080 x 7/8-5/8-20mm	10,185	.315"
07660702788	CON7DT	7 x .090 x DM-7/8-5/8	8,730	.275"
07660704016	0700TURBO5PK	7 x .090 x DM-7/8-5/8	8,730	.315"



VALUPLUS



A value price point for small to medium size jobs cutting standard ceramic tile with efficient cutting on low horsepower tile saws.

UPC	PART #	SIZE	MAX RPM	RIM HEIGHT
70184684087	VPDT0400	4 x .080 x 7/8-5/8-20mm	15,000	.275"
70184684088	VPDT0450	4-1/2 x .080 x 7/8-5/8-20mm	13,300	.275"
70184684089	VPDT0700	7 x .090 x DM-7/8-5/8	8,730	.275"



General Purpose and Masonry Building Materials

Blocks, medium-hard building bricks, paving slabs, concrete roof tiles and other medium-hard materials.



DRY – TUCK POINTING



CLASSIC



An economical solution for small to medium tuck pointing jobs. High quality performance for heavy grout removal or mortar jointing. The heavy duty wide segment reduces wear in abrasive materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184681776	CHTUCK0400	4 x .250 x 7/8-5/8-20mm	15,000	.275"
70184681777	CHTUCK0450	4-1/2 x .250 x 7/8-5/8-20mm	13,300	.275"
70184681778	CHTUCK0500	5 x .250 x 7/8-5/8-20mm	12,000	.275"
70184681779	CHTUCK0700	7 x .250 x 7/8-5/8-20mm	8,730	.275"



VALUPLUS



A value price point for small-to-medium size jobs. Cleans grout and mortar joints quickly and efficiently with hand-held tools.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184684020	CON4TP	4 x .250 x 7/8-5/8-20mm	15,000	.393"
70184683862	CON45TP	4-1/2 x .250 x 7/8-5/8-20mm	13,300	.393"



Reinforced Concrete and Harder Building Materials

Reinforced concrete, hard bricks, limestone, terrazzo, and other hard materials.



DRY – CRACK CHASING



CHARGER



A heavy V-shaped segment designed with a special bond and diamond content for maximum removal of grout, mortar jointing, crack chasing and crack widening. Fast cutting and long life in abrasive materials using portable tools. Highly competitive to others of its kind in the market.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
70184683856	CGCC0400	4 x .375 x 7/8-5/8-20mm	15,000	.550"
70184683859	CGCC0700	7 x .375 x 7/8-5/8-20mm	8,730	.550"





General Purpose and Masonry Building Materials

Blocks, medium-hard building bricks, paving slabs, concrete roof tiles and other medium-hard materials.

DRY – CUP GRINDER

3X3

Ensures very high material removal rate, extreme comfort while working without vibrations and a self-sharpening feature. These new cups offer the best finishing and longest life even on softer, more abrasive materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
Single Row for Fast Stock Removal				
701846 01763	3X3CG0400	4 x 5/8"-11	15,000	.177"
701846 01766	3X3CG0500	5 x 5/8"-11	12,000	.177"
701846 01769	3X3CG0700	7 x 5/8"-11	8,730	.177"

CHARGER

Increased segment to surface for more material removal than the Norton Classic cup grinder. The diamond and bond configuration provide a more comfortable feel while extending life and better finish on a wide range of materials.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
Single Row for Fast Stock Removal				
701846 01762	CGCG0400	4 x 5/8"-11	15,000	.177"
701846 01765	CGCG0500	5 x 5/8"-11	12,000	.177"
701846 01768	CGCG0700	7 x 5/8"-11	8,730	.177"

CLASSIC

Provides efficient material removal rate thanks to the small contact surfaces of the segments. The cups also have flat sides to avoid damaging walls or ceilings during flush grinding.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
Single Row for Fast Stock Removal				
701846 01761	CCCG0400	4 x 5/8"-11	15,000	.177"
701846 01764	CCCG0500	5 x 5/8"-11	12,000	.177"
701846 01767	CCCG0700	7 x 5/8"-11	8,730	.177"



Infiltrated High-Density (iHD)

Segments made with patented technology for longer life and faster grinding are available in three types. Designated by their unique segment designs, the Norton Clipper Classic, with a single building shaped segment provides a good removal rate. Two building in the Norton Clipper Charger cups for a better finished, faster cut. And, the Norton Clipper 3X3, with three buildings ensures the highest stock removal, best comfort, longest life and overall best finish.



Large Grinding Surface

For better comfort with minimal vibration.



iHD Segments

Made with patented technology for longer life and faster grinding.



Thick Body

For more safety, allowing more pressure when needed, resisting flexing causing breakage.



General Purpose and Masonry Building Materials

Blocks, medium-hard building bricks, paving slabs, concrete roof tiles and other medium-hard materials.

DRY – CUP GRINDER

CLASSIC

Available in a range of sizes and segment designs for optimum performance by life or by speed. Ideal for leveling all types of masonry materials, brick, block, concrete and stone. Strategically placed hole designs help ventilate dust from the surface extending life of the cups.

UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
Single Row for fast stock removal				
70184682585	CHSCPH0400	4 x 7/8-5/8-20mm	15,000	.210"
70184684035	CHSCPH0500	5 x 7/8-5/8-20mm	12,000	.210"
70184682594	CHSCPH0700	7 x 7/8-5/8-20mm	8,730	.210"
70184682555	CHSCPT0400	4 x 5/8-11	15,000	.210"
70184684036	CHSCPT0500	5 x 5/8-11	12,000	.210"
70184682593	CHSCPT0700	7 x 5/8-11	8,730	.210"



UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
Double Row for Long Life, Smooth Finish				
70184682588	CHDCPH0400	4 x 7/8-5/8-20mm	15,000	.210"
70184684037	CHDCPH0500	5 x 7/8-5/8-20mm	12,000	.210"
70184682596	CHDCPH0700	7 x 7/8-5/8-20mm	8,730	.210"
70184682586	CHDCPT0400	4 x 5/8-11	15,000	.210"
70184684038	CHDCPT0500	5 x 5/8-11	12,000	.210"
70184682595	CHDCPT0700	7 x 5/8-11	8,730	.210"



UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
Swirl for Most Aggressive Cut, Smooth Finish				
70184683826	CHSWCPT0400	4 x 5/8"-11	15,000	.180"
70184684040	CHSWCPT0500	5 x 5/8"-11	12,000	.180"
70184683827	CHSWCPT0700	7 x 5/8"-11	8,730	.180"




UPC	PART #	SIZE	MAX RPM	SEGMENT HEIGHT
Turbo for Long Life, Very Smooth Finish				
70184683830	CHTURCPT0400	4 x 5/8"-11	15,000	.210"
70184683831	CHTURCPT0700	7 x 5/8"-11	8,730	.210"



you won't get left in the dust **WITH THE NORTON VACUUM SHROUD**

Hand grinding of concrete and masonry surfaces and mortar is a tough, dirty task. It doesn't have to be with the new Norton Vacuum Shroud. The Vacuum Shroud's design creates a cyclonic effect, extracting dust and debris from the work surface into the support vacuum. This prolongs the life of the grinding cup and grinder and provides a smoother surface while decreasing the chance of dust particle inhalation. A durable, heavy-duty, scratch-resistant plastic design can withstand the constant abuse of hand grinding applications. The hinged front can be used to work closely to the corner of the walls or improve visibility of the surface while reducing airborne dust.



UPC

701846**94059**

701846**41039**

DESCRIPTION

5" vacuum shroud kit – includes one shroud, five different adapter rings to fit most popular right angle grinders, and one 5" x 5/8-11 Norton Clipper cup wheel.

7" vacuum shroud kit – includes one shroud, five different adapter rings to fit most popular right angle grinders, and one 7" x 5/8-11 Norton Clipper cup wheel.



Simple and Easy Design

Durable, scratch-resistant body with steel reinforcement ring to provide strong support when grinding. Provides smoother and longer shroud life.



Additional Adapters

Five extra adaptor rings enabling the shroud to be mounted on various industry grinders. Every kit comes with a single row diamond cup.



Hinged Window

Provides additional visibility of the surface with closer grinding performance along walls and corners.





RANGE OVERVIEW



MODEL#

DR620

UPC#

70184600925



HHD3TOL HAND-HELD

70184621725



HHDETOL

70184600917



HHDET1800

70184684243

MAX. DRILLING
CAPACITY

10"
(254mm)

6"
(127mm)

6"
(127mm)

4"
(127mm)

MAX.
HORSEPOWER

25 Amps

15 Amps

15 Amps

15 Amps

PRODUCT FEATURES



Vacuum Pump

Superior stabilization.



Wheel Attachment

Ease of transporting around job site.



Ceiling Jack

Extending ceiling jack for indoor drilling.



DR520



DR620

The Norton Clipper DR series of core drills offer a versatile drill rig with exceptional utility to meet the tough demands of today's rental and contractor industry. The basic design of the carriage and pinion assembly provides a simple trouble-free system to extend service life in the rental fleet. The DR620 drill rig stand offers the additional utility of a pivoting column for drilling vertically on a sloping surface.

TECHNICAL SPECIFICATIONS

PRODUCT #	DR520	DR620
UPC	701846 00924	701846 00925
Gears	2	2
Motor Type	Milwaukee	Milwaukee
Motor Specification	4096	4096
Voltage	115 volts	115 volts
Cycle*/Current/Phase	60 Hz/AC/1	60 Hz/AC/1
Amperage	15 Amp	20 Amp
RPM	450/900	450/900
Spindle Thread Size	1-1/4"-7 UNC	1-1/4"-7 UNC
Base – Combo – in. (mm) LxW	18-7/8" x 13-3/4" (450x350)	18-7/8" x 13-3/4" (450x350)
Column Length – in. (mm)	42" (1,067)	40" (1,016)
Slide Carriage	One Piece Aluminum Carriage, Rack and Pinion, Carriage Lock, and Quick Detach Motor Mount Dove Tail	
Wheel Base (outside to outside) in. (mm)	15-1/2" (394)	15-1/2" (394)
Wheels (D x W x B) in. (mm)	6"x1-3/8"x3/4" (152x35x19)	6"x1-3/8"x3/4" (152x35x19)
Vacuum Pump	YES	YES
Control Panel	YES	YES
Weight Crated – lbs (kg)	140 (63.5)	140 (63.5)
Weight Uncrated – lbs (kg)	125 (56.7)	125 (56.7)
RECOMMENDED BIT SIZES		
Low in. (mm)	6" to 10" (152 to 254)	6" to 10" (152 to 254)
High in. (mm)	2" to 6" (50 to 152)	2" to 6" (50 to 152)
DRILL RIG STANDS		
DS5/DS6 Drill Rig Stand – Standard Base	701846 00922	D55
DS5/DS6 Drill Rig Stand – Pivoting Base	701846 00923	D56
DM5/DM6 DRILL MOTORS		
15 amp Milwaukee	701846 57976	403061
20 amp Milwaukee	701846 57985	403064
ACCESSORIES		
Spacer Block	701846 00927	408002
2.64 Gallon Pressure Water Tank – Metal Manual Pump, 8ft (2.5m) with Quick Detach Fittings	003104 64031	310464031
9.24 Gallon Pressure Water Tank – Plastic Electric pump, automatic shut off, 34ft (10.4m) hose	701846 02829	233936
Water Collector Ring	701846 58498	402034
Core Bit Quick Release Attachment	701846 00938	408003
Vacuum Pump for DR520/620	701846 45802	408299

*= DATA PROVIDED BY ENGINE MANUFACTURER



CORE BITS

Minimum and Maximum Recommended Operating Speeds


BIT DIAMETER	MIN. (RPM)	IDEAL SPEED (RPM)	MAX. (RPM)
1"	2,400	3,200	4,000
2"	1,200	1,600	2,000
3"	800	1,050	1,300
4"	600	800	1,000
5"	475	640	800
6"	400	530	665
7"	340	450	600
8"	300	400	500
10"	240	320	400
12"	200	265	330
14"	170	225	285
16"	150	200	250
18"	130	175	220
20"	120	160	200
24"	100	130	165
26"	90	125	150
30"	80	105	130
32"	75	100	125
34"	70	95	120
36"	65	85	110
40"	60	80	100
42"	55	75	95

PRODUCT FEATURES



Single-Speed, 15 Amp

Smart Electronics allow bits to spin with ease.



Sturdy All-Metal Carriage

Equipped with a side level and hand-held rig adaptor ensures smooth operation.



Wide Base Platform

A bit guide allows straighter drilling.



Recommended Core Bit

Norton Clipper Charger
See page 110

This rig package provides the rental market with a strong, stable-performing hand-held core drill and sturdy rig stand. The single-speed drill features "Smart Electronics" motor protection and safety clutch for safe operation, which means no overheating of electrical parts. Geared at 940 RPMs, there is plenty of power to easily spin a 4" bit by hand and a 6" with the stand. When you need a core drill that can cover the basics but also maximize your return on investment, the HDR600C is a great solution.

TECHNICAL SPECIFICATIONS

PRODUCT #	HDR600C	
UPC	701846 44020	
Gears	1	
Motor Type	Electric	
Voltage	115 volts	
Cycle*/Current/Phase	60Hz/AC/1	
Amperage*	15 Amps	
RPM (No Load)	940	
Smart Electronics	YES	
Weight Crated – lbs. (kg)	18 (8.1)	
Weight Uncrated – lbs. (kg)	12 (5.4)	
RECOMMENDED BIT SIZES		
Low – in. (mm)	2" to 4" (50 to 102)	
High – in. (mm)	n/a	
ACCESSORIES	UPC	SMART PART #
Portable Stand CDR163	003104 68577	CDR163
Core Bit Quick Release Attachment	701846 00938	408003

*= DATA PROVIDED BY MOTOR MANUFACTURER

PRODUCT FEATURES



Water Attachment and Accessories

1-1/4-7 Male with 5/8-11 adapter and quick attach water accessories for wet drilling.



Storage Space Saver

Provides room for side handle, manual, and extra tools in a compact and convenient case.



Heavy-Duty Carrying Case

Light-weight, high-impact plastic protects drill during transportation.



The HHD3TOL hand-held core drill is perfect for professional or heavy rental user, providing all the power needed for most any drilling job. Having speeds from 770 to 2,580 rpm allows the use of 1" up to 6" diamond core bits. The Cardi "Smart Electronics" adds protection by not overheating electrical parts. With the comfortable rear handle, and three-speed variability, operator comfort is improved, and productivity enhanced.

TECHNICAL SPECIFICATIONS


PRODUCT #	HHD3TOL	
UPC	701846 21725	
Gears	3	
Motor Type	Electric	
Voltage	115 volts	
Cycle*/Current/Phase	60Hz/AC/1	
Amperage*	15 (18) Amps	
RPM	770/1,860/2,580	
Smart Electronics	YES	
Weight Crated	27 (12.2)	
Weight Uncrated	17 (7.3)	
RECOMMENDED BIT SIZES		
Low – in. (mm) 2" to 4" (50 to 102)	4" to 6" (100 to 150)	
Medium - in. (mm)	2" to 3" (50 to 75)	
High – in. (mm) 1/2" to 2" (12 to 50)	1" to 2" (25 to 50)	
ACCESSORIES	UPC	SMART PART #
Portable Stand CDR163	003104 68577	CDR163
Core Bit Quick Release Attachment	701846 00938	408003

*= DATA PROVIDED BY MOTOR MANUFACTURER

Recommended Core Bit

Norton Clipper Paradigm
See page 110

PRODUCT FEATURES



1-1/4" – 7 Spindle with 5/8-11 Threaded Adaptor

Allows additional bit types to be used.



Heavy-Duty Carrying Case

Light-weight, high-impact plastic that protects drill during transportation.



Optional Stand

Provides additional drilling flexibility with its sturdy column and carriage for smooth drilling.



Weighing only 13 pounds, the HHDETOL is a Norton Clipper hand-held core drill with a 15 amp motor. The "Smart Electronic" system protects it from system overload. This unit comes with a durable plastic carrying case, safety clutch, 5/8-11 threaded adaptor and 1-1/4-7 threaded spindle. Ideal for electricians, plumbers and the professional contractor.

TECHNICAL SPECIFICATIONS

PRODUCT #	HHDETOL	
UPC	701846 00917	
Gears	2	
Motor Type	Electric	
Voltage	115 volts	
Cycle*/Current/Phase	60Hz/AC/1	
Amperage*	15 Amps	
RPM (No Load)	1,180/2,150	
Smart Electronics	YES	
Weight Crated – lbs. (kg)	19 (8.6)	
Weight Uncrated – lbs. (kg)	13 (5.9)	
RECOMMENDED BIT SIZES		
Low – in. (mm)	2" to 4" (50 to 102)	
High – in. (mm)	1/2" to 2" (12 to 50)	
ACCESSORIES	UPC	SMART PART #
Portable Stand CDR163	003104 68577	CDR163
Core Bit Quick Release Attachment	701846 00938	408003

*= DATA PROVIDED BY MOTOR MANUFACTURER

Recommended Core Bit

Norton Clipper Charger
See page 111

PRODUCT FEATURES



Smart Electronics Protection

No over-heating of electrical components.



Water Attachment and Accessories

1-1/4-7 Male with 5/8-11 adapter and quick attach water accessories for wet drilling.



Rugged Carrying Case

Protects unit and accessories from damage.



A light-weight and user-friendly core drill. With its "Smart Electronics" motor protection from Cardi means no overheating of electrical parts. The powerful 15 amp motor drives core bits up to 4" with ease. The HHDET1800 hand-held core drill has a single-speed gear box and mechanical safety clutch. Packaged in a rugged carrying case to protect the drill during transport.

TECHNICAL SPECIFICATIONS

PRODUCT #	HHDET1800	
UPC	701846	84243
Gears	1	
Motor Type	Electric	
Voltage	115 volts	
Cycle*/Current/Phase	60Hz/AC/1	
Amperage*	15 Amps	
RPM (No Load)	940	
Smart Electronics	YES	
Weight Crated – lbs. (kg)	18 (8.1)	
Weight Uncrated – lbs. (kg)	12 (5.4)	
RECOMMENDED BIT SIZES		
Low – in. (mm)	2" to 4" (50 to 102)	
High – in. (mm)	n/a	
ACCESSORIES	UPC	SMART PART #
Portable Stand CDR163	003104	68577 CDR163
Core Bit Quick Release Attachment	701846	00938 408003

*= DATA PROVIDED BY MOTOR MANUFACTURER

Recommended Core Bit

Norton Clipper Classic
See page 111

ACCESSORIES FOR CORE DRILLING

UPC	SMART PART #	DESCRIPTION
701846 69858	Y1017	Nylon Washer



UPC	SMART PART #	DESCRIPTION	SIZE
701846 65995	402760	Extension	6" x 1-1/4" 7 Thread



UPC	SMART PART #	DESCRIPTION	SIZE
701846 48793	402758	Extension	6" x 5/8" 11 Thread



UPC	SMART PART #	DESCRIPTION	SIZE
701846 48791	402756	Extension	12" x 1-1/4" 7 Thread



UPC	SMART PART #	DESCRIPTION	SIZE
701846 48792	402757	Extension	12" x 5/8" 11 Thread



UPC	SMART PART #	DESCRIPTION	SIZE
701846 49430	400148	Coupling	1-1/4" – 7(F) – 5/8" – 11(M)



UPC	SMART PART #	DESCRIPTION	SIZE
701846 49797	400147	Coupling	5/8" – 11(F) – 1 1/4" – 7(M)



NOTE:

- Wet bits from 1" to 1-1/2" diameter have 5/8"-11 threaded adapters
- Wet bits 1-3/4" diameter and larger have 1-1/4"-7 threaded adapters
- Classic, charger, paradigm wet bits have 16" tube length and produce 13" coring depth
- Dry cutting bits come with 5/8"-11 threaded adapters and 11 inch tube length



ACCESSORIES FOR CORE DRILLING (CONTINUED)

UPC	SMART PART #	DESCRIPTION
003104 68577	CDR163	Portable Stand CDR163



UPC	SMART PART #	DESCRIPTION
701846 45802	408299	Vacuum Pump for CD100



UPC	SMART PART #	DESCRIPTION
701846 00938	408003	Core Bit Quick Release Attachment



UPC	SMART PART #	DESCRIPTION
701846 00927	408002	Spacer Block



UPC	SMART PART #	DESCRIPTION
701846 58498	402034	Water Collector Ring



UPC	SMART PART #	DESCRIPTION
701846 00983	408012	Vacuum Base Gasket - DS5/DS6



UPC	SMART PART #	DESCRIPTION
003104 94440	310494440	Dust Collector 3/8" to 3" (10-85mm)
003104 94441	310494441	Dust Collector 3-1/2" to 6"



UPC	SMART PART #	DESCRIPTION
003104 70303	310470303	Water Collector 5" (130mm) Max Bit
003104 70304	310470304	Water Collector 10" (300) Max Bit



hard to the core A NEW PARADIGM FOR DRILLING

You get a little “bit” more perfection with this innovative design of Norton Clipper Paradigm. A tapered top permits the core bit to penetrate quick and efficiently into the toughest aggregates and steel-reinforced concrete while strategic fluting accelerates cut and debris extraction. Remember, not all holes are created equally.




Strong Cores

Each tube is laser-welded to withstand demanding applications.



Tapered Segment

Turbo type design allows faster penetration.



Large Segment Height

Extends product life.





Reinforced Concrete and Harder Building Materials

Reinforced concrete, hard bricks, limestone, terrazzo, and other hard materials.

WET



PARADIGM



A turbo segment permits the core to penetrate quick and efficiently into the toughest cured concrete. With significantly increased performance over existing products in the market today, these provide the best tier solution without the premium price tag.

UPC	PART #	SIZE IN INCHES	SIZE IN MM	MAX RPM	SEGMENT HEIGHT
70184601410	PDBIT0200	2"	51mm	2,000	.490"
70184601411	PDBIT0250	2-1/2"	64mm	1,300	.490"
70184601412	PDBIT0300	3"	76mm	1,300	.490"
70184601413	PDBIT0350	3-1/2"	89mm	1,300	.490"
70184601414	PDBIT0400	4"	102mm	1,000	.490"
70184601415	PDBIT0450	4-1/2"	114mm	800	.490"
70184601416	PDBIT0500	5"	127mm	800	.490"
70184601417	PDBIT0600	6"	152mm	665	.490"
70184601418	PDBIT0700	7"	178mm	600	.490"
70184601419	PDBIT0800	8"	203mm	500	.490"
70184601706	PDBIT1000	10"	254mm	400	.490"
70184601707	PDBIT1200	12"	305mm	330	.490"
70184601708	PDBIT1400	14"	356mm	285	.490"



Wet Bits from 1" to 1-1/2" diameter have 5/8"-11 threaded adapters.

CHARGER




Laser welded segments for faster penetration in medium aggregate with reinforcement and maximum utilization of segment life.

UPC	PART #	SIZE IN INCHES	SIZE IN MM	MAX RPM	SEGMENT HEIGHT
70184682778	CGBIT0100	1"	25mm	4,000	.375"
70184682779	CGBIT0125	1-1/4"	32mm	3,000	.375"
70184682780	CGBIT0150	1-1/2"	38mm	3,000	.375"
70184682781	CGBIT0175	1-3/4"	44mm	2,000	.375"
70184682782	CGBIT0200	2"	51mm	2,000	.475"
70184682783	CGBIT0225	2-1/4"	57mm	1,300	.475"
70184682784	CGBIT0250	2-1/2"	64mm	1,300	.475"
70184682785	CGBIT0300	3"	76mm	1,300	.475"
70184682786	CGBIT0350	3-1/2"	89mm	1,000	.475"
70184682787	CGBIT0400	4"	102mm	1,000	.475"
70184682788	CGBIT0425	4-1/4"	108mm	800	.475"
70184682789	CGBIT0450	4-1/2"	114mm	800	.475"
70184682790	CGBIT0500	5"	127mm	800	.475"
70184682791	CGBIT0600	6"	152mm	665	.475"
70184682792	CGBIT0700	7"	178mm	600	.475"
70184682793	CGBIT0800	8"	203mm	500	.475"
70184682794	CGBIT1000	10"	254mm	400	.475"
70184682795	CGBIT1200	12"	305mm	330	.475"
70184682796	CGBIT1400	14"	356mm	285	.475"



Wet Bits 1-3/4" diameter and larger have 1-1/4"-7 threaded adapters.



Classic, Charger, and Paradigm Wet Bits have a 16" Tube Length and produce a 13" Core Length





Reinforced Concrete and Harder Building Materials

Reinforced concrete, hard bricks, limestone, terrazzo, and other hard materials.

WET




CLASSIC



Economical choice for use in harder concrete with heavy reinforcement and masonry materials with good performance.

UPC	PART #	SIZE IN INCHES	SIZE IN MM	MAX RPM	SEGMENT HEIGHT
70184684447	CHBIT0100	1"	25mm	4,000	.375"
70184684448	CHBIT0150	1-1/2"	38mm	3,000	.350"
70184682762	CHBIT0200	2"	51mm	2,000	.350"
70184682763	CHBIT0225	2-1/4"	57mm	2,000	.350"
70184682764	CHBIT0250	2-1/2"	64mm	1,300	.350"
70184682765	CHBIT0300	3"	76mm	1,300	.350"
70184682766	CHBIT0350	3-1/2"	89mm	1,300	.350"
70184682767	CHBIT0400	4"	102mm	1,000	.350"
70184682768	CHBIT0425	4-1/4"	108mm	1,000	.350"
70184682769	CHBIT0450	4-1/2"	114mm	800	.350"
70184682770	CHBIT0500	5"	127mm	800	.350"
70184682771	CHBIT0600	6"	152mm	665	.350"
70184682772	CHBIT0700	7"	178mm	600	.350"
70184682773	CHBIT0800	8"	203mm	500	.350"
70184682774	CHBIT1000	10"	254mm	400	.350"
70184682775	CHBIT1200	12"	305mm	330	.350"
70184682776	CHBIT1400	14"	356mm	285	.350"



Wet Bits from 1" to 1-1/2" diameter have 5/8"-11 threaded adapters.

Wet Bits 1-3/4" diameter and larger have 1-1/4"-7 threaded adapters.

WET - PRESTRESSED CONCRETE



CHARGER




Fast drilling segments spaced to prevent segment loss when penetrating tensioned steel cable.

UPC	PART #	SIZE IN INCHES	SIZE IN MM	MAX RPM	SEGMENT HEIGHT
70184683983	CGPBIT0100	1"	25mm	4,000	.375"
70184683984	CGPBIT0125	1-1/4"	32mm	3,000	.375"
70184683985	CGPBIT0150	1-1/2"	38mm	3,000	.375"
70184683987	CGPBIT0200	2"	51mm	2,000	.350"
70184683988	CGPBIT0225	2-1/4"	57mm	1,300	.350"
70184683989	CGPBIT0250	2-1/2"	64mm	1,300	.350"
70184683990	CGPBIT0300	3"	76mm	1,300	.350"
70184683991	CGPBIT0350	3-1/2"	89mm	1,000	.350"
70184683992	CGPBIT0400	4"	102mm	1,000	.350"
70184683993	CGPBIT0425	4-1/4"	108mm	800	.350"
70184683994	CGPBIT0450	4-1/2"	114mm	800	.350"
70184683995	CGPBIT0500	5"	127mm	800	.350"
70184683996	CGPBIT0600	6"	152mm	665	.350"
70184683997	CGPBIT0700	7"	178mm	600	.350"
70184683998	CGPBIT0800	8"	203mm	500	.350"
70184683999	CGPBIT1000	10"	254mm	400	.350"
70184684000	CGPBIT1200	12"	305mm	330	.350"
70184684001	CGPBIT1400	14"	356mm	285	.350"



Wet Bits from 1" to 1-1/2" diameter have 5/8"-11 threaded adapters.

Wet Bits 1-3/4" diameter and larger have 1-1/4"-7 threaded adapters.



Classic, Charger, and Paradigm Wet Bits have a 16" Tube Length and produce a 13" Core Length





General Purpose and Masonry Building Materials

Blocks, medium-hard building bricks, paving slabs, concrete roof tiles and other medium-hard materials.

DRY



CHARGER



Dry drilling core bits for use on portable drilling equipment. Best suited for applications in soft, non-reinforced cured concrete and concrete block.

UPC	PART #	SIZE IN INCHES	SIZE IN MM	MAX RPM	SEGMENT HEIGHT
701846 83300	CGDBIT0100	1"	25mm	6,000	.275"
701846 83301	CGDBIT0125	1-1/4"	32mm	6,000	.275"
701846 83302	CGDBIT0150	1-1/2"	38mm	6,000	.275"
701846 83303	CGDBIT0175	1-3/4"	44mm	5,000	.276"
701846 83304	CGDBIT0200	2"	51mm	5,000	.275"
701846 83305	CGDBIT0250	2-1/2"	64mm	5,000	.275"
701846 83306	CGDBIT0300	3"	76mm	5,000	.275"
701846 83307	CGDBIT0350	3-1/2"	89mm	5,000	.275"
701846 83308	CGDBIT0400	4"	102mm	5,000	.275"
701846 83309	CGDBIT0450	4-1/2"	114mm	5,000	.275"
701846 83310	CGDBIT0500	5"	127mm	3,500	.275"
701846 83311	CGDBIT0600	6"	152mm	2,500	.275"



Dry Core Bits have 5/8"-11 threaded adapters.




This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

MERCHANDISING SOLUTIONS

OUR SELF-SELLING GOAL

Over two thirds of final consumer purchase decisions are made at the point-of-sale. The interaction between the product, the distributor and the consumer is key to the success of selling product.

New Norton Clipper branded display kits have been designed with a selection of components to help tailor the display for different products and merchandising requirements. In addition, a range of point-of-sale materials are available to further support sales growth for masonry, rental and construction supply distributors.



NORTON CLIPPER GONDOLA (BACKWALL) MERCHANDISER DISPLAY KIT

The complete kit comes with all components needed to create a full display for all Norton Clipper products. Wall merchandiser as shown is 40" wide x 90" high. This kit can be configured to fit 40" wide x 48" high aisle gondola set.




Backwall Merchandiser Display
Kit #: 0410048416

Kit Contains:



Norton Clipper header
(Qty 1)



Pegboards (Qty 4)



Double peg hooks for
diamond clamshell packages
(Qty 15)



Base (Qty 1)



Shelf (Qty 1)



Display legs (Qty 4)



Single peg hooks for
abrasive products (Qty 20)

Additional merchandising elements available and can be ordered separately:



Core Bit Hangers / UPC # 00510120422 – Effectively display your range of core bits with these simple hangers that can fit a wide range of Norton Clipper core bits

STARTING RECOMMENDATIONS FOR BEST WALL SETS

Contractor Supply Starter Abrasives Set

PART #	DESCRIPTION	QTY
Grinding Wheels		
70184601510	Norton Clipper Classic 7" x 1/4" x 5/8"-11 Metal / Stainless	10
70184609143	Norton Clipper Classic 4-1/2" x 1/4" x 5/8"-11 - Multi-Material	10
70184601503	Norton Clipper Classic 4-1/2" x 1/4" x 5/8"-11 - Metal / Stainless	10
Cut-off Wheels		
70184601465	Norton Clipper Classic Type 27 4-1/2" x .045" x 7/8"	25
70184601466	Norton Clipper Classic Type 27 5" x .045" x 7/8"	25
70184601467	Norton Clipper Classic Type 27 6" x .045" x 7/8"	25
70184601456	Norton Clipper Classic Type 01 4 5" x .045" x 7/8" Metal / Stainless	25
70184601457	Norton Clipper Classic Type 01 6" x .040" x 7/8" Metal / Stainless	25
Circular Saw Wheels		
70184609146	Norton Clipper Classic 6.5" x 3/32" x 5/8"	25
70184609147	Norton Clipper Classic 7" x 3/32" x 5/8"	25
Chop Saw Wheel		
70184601477	Norton Clipper Classic 14" x 3/32" x 1" Metal Side Reinforced	10
High-Speed Wheels – Universal Arbor		
70184601493	Norton Clipper Classic 14" x 1/8" x 1" 20mm Metal	10
70184601491	Norton Clipper Classic 14" x 1/8" x 1" 20mm Concrete	10
Flap Discs - Fiberglass Backing - Type 27		
70184609163	Norton Clipper Classic 4-1/2" x 5/8"-11 - 40 Grit	5
70184609164	Norton Clipper Classic 4-1/2" x 5/8"-11 - 60 Grit	5
70184609165	Norton Clipper Classic 4-1/2" x 5/8"-11 - 80 Grit	5
70184609166	Norton Clipper Classic 7" x 5/8"-11 - 40 Grit	5
70184609167	Norton Clipper Classic 7" x 5/8"-11 - 60 Grit	5
70184609168	Norton Clipper Classic 7" x 5/8"-11 - 80 Grit	5
Rapid Strip Discs		
70184601595	4-1/2" x 7/8" Ex. Course 10/10	10
70184601594	4-1/2" x 5/8"-11 Ex. Course 10/10	10
Wheels & Wire Brushes		
70184609160	Norton Clipper Classic Coarse Wire Wheel Brush - 1 pack 2" x .012" x Drill 1/4 Brass	6
70184609152	Norton Clipper Classic Crimp Wire Cup Brush 3" x .012" x Drill 1/4 Brass Coated	6
70184609151	Norton Clipper Classic Crimp Wire Cup Brush 3" x .014" x 5/8"-11 Carbon	4
70184609149	Norton Clipper Classic Knot Wire Cup Brush 3" x .02" x 5/8"-11 Carbon	4
70184609150	Norton Clipper Classic Knot Wire Cup Brush 3" x .02" x 5/8"-11 Stainless	4
70184609159	Norton Clipper Classic Coarse Wire Crimp Brush - 1 pack 2" x .012" x Drill 1/4 Brass	6
70184609156	Norton Clipper Classic Coarse Wire Wheel 3" x .012" x Drill 1/4 Brass	6
70184609155	Norton Clipper Classic Coarse Wire Wheel 4" x .012" x Drill 1/4 Carbon	6
70184609161	Norton Classic Wire Wheel Brush - 1 pack 6" x .012" x Fits 1/2"	6
70184609153	Norton Clipper Classic Knotted Wire Wheel Brush 4" x .02" x 5/8"-11 Stainless	5
70184609154	Norton Clipper Classic Knotted Wire Wheel Brush 4" x .02" x 5/8"-11 Carbon	5
70184609157	Norton Clipper Classic Coarse Wire End Brush 1" x .012" x Drill 1/4 Brass	6
70184609158	Norton Clipper Classic Wire Brush - 6 pack 1" x .012" x Drill 1/4 Brass	6



STARTING RECOMMENDATIONS FOR BEST WALL SETS

Contractor Supply Starter Diamond and Abrasive Set

PART #	DESCRIPTION	QTY
Diamond Blades		
07660702790	Norton Clipper Classic 4-1/2" x .080" x 7/8"-5/8"-20mm Turbo	2
07660701194	Norton Clipper Classic 4-1/2" x .080" x 7/8"-5/8"-20mm Continuous	2
07660702789	Norton Clipper Classic 4-1/2" x .080" x 7/8"-5/8"-20mm Segmented	2
70184684547	Norton Clipper 4x4 14" x .118" x 1"-20mm Segmented	2
70184645926	Norton Clipper 4x4 MaxCut iHD 14" x .125" x 1"-20mm Segmented	2
70184684181	Norton Clipper ValuPlus 14" x .110" x 1"-20mm Segmented	2
07660702786	Norton Clipper Classic 7" x .080" x DM-7/8"-5/8" Segmented	2
07660702787	Norton Clipper Classic 7" x .090" x DM-7/8"-5/8" Turbo	2
70184681777	Norton Clipper Classic 4-1/2" x .250" x 7/8"-5/8"-20mm Tuck Pointing	2
Diamond Cup Grinders		
70184682595	Norton Clipper Classic 7" x 5/8"-11 Double Row	2
70184682593	Norton Clipper Classic 7" x 5/8"-11 Single Row	2
70184682555	Norton Clipper Classic 4" x 5/8"-11 Single Row	2
70184682586	Norton Clipper Classic 4" x 5/8"-11 Double Row	2
Abrasives		
70184601493	Norton Clipper Classic 14" x 1/8" x 1"-20mm UA High-Speed Metal	10
70184601491	Norton Clipper Classic 14" x 1/8" x 1"-20mm UA High-Speed Concrete	10
70184601609	Norton Clipper Classic 6/4-3/4" x 2" x 5/8"-11 Concrete Cup Wheel	5
Core Bits		
70184682782	Norton Clipper Charger 2" Bit	1
70184682785	Norton Clipper Charger 3" Bit	1
70184682787	Norton Clipper Charger 4" Bit	1
70184682791	Norton Clipper Charger 6" Bit	1




NORTON CLIPPER FREE-STANDING MERCHANDISER DISPLAY KIT

Free-standing displays for most popular High-Speed Saw/Diamond/Abrasives displays where customers can view in open area of a showroom. High-quality construction. Consistent branding and graphics. This free standing unit as shown is 40" wide at base x 90" high.



Free-standing Merchandiser Display
Kit #: 510116151

Kit Contains:



Norton Clipper header (Qty 1)



Clipper header (Qty 2)



Shelves (Qty 3)



Pegboards (Qty 3)



Double peg hooks for diamond clamshell packages (Qty 15)



Single peg hooks for abrasive products (Qty 20)

Additional merchandising elements available and can be ordered separately:



Core Bit Hanger / UPC # 00510120422 – Effectively display your range of core bits with these simple hangers that can fit a wide range of Norton Clipper core bits

STARTING RECOMMENDATIONS FOR BEST FREE-STANDING SETS

Saw Side

PART #	DESCRIPTION	QTY
High Speed Gas Saw		
701846 47565	Norton Clipper 14" iLube High-Speed Gas Saw	1
Diamond Blades		
701846 84547	Norton Clipper 4x4 14" x .118" x 1" 20mm – Segmented	5
Abrasives – Universal Arbor		
701846 01493	Norton Clipper Classic 14" x 1/8" x 1"-20mm High Speed Metal	10
701846 01491	Norton Clipper Classic 14" x 1/8" x 1"-20mm High Speed Concrete	10



STARTING RECOMMENDATIONS FOR BEST FREE-STANDING SETS


Diamond Side

PART #	DESCRIPTION	QTY
Diamond Blades		
07660702790	Norton Clipper Classic 4-1/2" x .080" x 7/8"-5/8"-20mm Turbo	2
07660701194	Norton Clipper Classic 4-1/2" x .080" x 7/8"-5/8"-20mm Continuous	2
07660702789	Norton Clipper Classic 4-1/2" x .080" x 7/8"-5/8"-20mm Segmented	2
70184684547	Norton Clipper 4x4 14" x .118" x 1"-20mm- Segmented	2
07660702786	Norton Clipper Classic 7" x .080" x DM-7/8"-5/8" Segmented	2
07660702787	Norton Clipper Classic 7" x .090" x DM-7/8"-5/8" Turbo	2
70184681777	Norton Clipper Classic 4-1/2" x .250" x 7/8"-5/8"-20mm Tuck Pointing	2
Diamond Cups		
70184682595	Norton Clipper Classic 7" x 5/8"-11 Double Row	2
70184682593	Norton Clipper Classic 7" x 5/8"-11 Single Row	2
70184682555	Norton Clipper Classic 4" x 5/8"-11 Single Row	2
70184682586	Norton Clipper Classic 4" x 5/8"-11 Double Row	2
Core Bits		
70184682782	Norton Clipper Charger 2" Bit	1
70184682785	Norton Clipper Charger 3" Bit	1
70184682787	Norton Clipper Charger 4" Bit	1
70184682791	Norton Clipper Charger 6" Bit	1

Abrasive Side

PART #	DESCRIPTION	QTY
Grinding Wheels		
70184601502	Norton Clipper Classic 4-1/2" x 1/4" x 5/8"-11 Concrete	10
70184601503	Norton Clipper Classic 4-1/2" x 1/4" x 5/8"-11 Metal / Stainless	10
70184601510	Norton Clipper Classic 7" x 1/4" x 5/8"-11 Metal / Stainless	10
Cut-off Wheels		
70184601455	Norton Clipper Classic Type 01 4-1/2" x .040" x 7/8" Metal / Stainless	25
70184601465	Norton Clipper Classic Type 27 4-1/2" x .045" x 7/8" Metal / Stainless	25
70184601457	Norton Clipper Classic Type 01 6" x .040" x 7/8" Metal / Stainless	25
70184601460	Norton Clipper Charger Type 01 4-1/2" x .045" x 7/8" Metal / Stainless	25
70184601470	Norton Clipper Charger Type 27 4-1/2" x .045" x 7/8" Metal / Stainless	25
70184601462	Norton Clipper Charger Type 01 6" x .045" x 7/8" Metal / Stainless	25
Circular Saw Wheels		
70184601484	Norton Clipper Classic 7" x 3/32" x DM-5/8" Metal	25
Flap Discs		
70184601579	Norton Clipper Classic 4-1/2" X 5/8"-11 Type 27 Flat 40 Grit	10
70184601580	Norton Clipper Classic 4-1/2" X 5/8"-11 Type 27 Flat 60 Grit	10
70184601581	Norton Clipper Classic 4-1/2" X 5/8"-11 Type 27 Flat 80 Grit	10
70184601591	Norton Clipper Charger 4-1/2" X 5/8"-11 Type 27 Heavy Duty 40 Grit	10
70184601592	Norton Clipper Charger 4-1/2" X 5/8"-11 Type 27 Heavy Duty 60 Grit	10
70184601593	Norton Clipper Charger 4-1/2" X 5/8"-11 Type 27 Heavy Duty 80 Grit	10
Chop Saw Wheel		
70184601477	Norton Clipper Classic 14" x 3/32" x 1" Metal Side Reinforced	10
Wire Brushes		
70184601615	Norton Clipper Classic 4" x .020" x 5/8"-11 Std CS Twist Knot Wheel	5
70184601617	Norton Clipper Classic 12" x .035" x 1" CS Joint/Crack Cleaning Brush	2
Miscellaneous Abrasives		
70184601609	Norton Clipper Classic 6/4-3/4" x 2" x 5/8"-11 Concrete Cup	5






Diamond Aisle Talker
UPC # 70184695555

The diamond blade talkers describe which diamond products work best of each application. Our 5 step specification method makes it simple to recommend the right diamond product for each job. Size 36" high x 12" wide.

Mounting hooks included.



Abrasive Aisle Talker
UPC # 70184695556


Quickly and easily understand and sell the range of coated and bonded abrasive products in a way that keeps things aligned and easily accessible by the consumer. Size 36" high x 12" wide.

Mounting hooks included.




Diamond Blade Selection Guide
11" x 17" / Form # 8678
25" x 38" / Form # 8679

A quick reference guide to help easily identify the proper blade to select for your application. Available in a double sided 11x17 sheet, or a full size wall poster.




Norton Clipper Banner
Form # 8650

Bring more brand awareness to your showroom by displaying our 60" x 24" vinyl banner highlighting our diamond blades, abrasives and construction equipment.



Norton Clipper Counter Mat
Form # 8649

Advertise premium Norton Clipper products and reputable history at checkout with this 21" x 16" counter mat. This showcases all of the reasons why Norton Clipper is your most reliable source for all your cutting and grinding construction jobsite solutions.




Norton Clipper Floor Decal
Form # 8648

Take a step in the right direction and give your showroom a more professional look by installing our custom vinyl floor decal. A nice visual to help promote the Norton Clipper brand.

Ask your Norton Clipper representative, or Customer Service Rep, how to order.

Simplified Packaging

taking less talk
TO CUT MORE ROCK!



In addition to our self-selling packaging, we have a new look for our premium iHD diamond blades. Using a brand new technology industrialized for the first time by Norton Clipper, the blade information is printed directly on the entire surface of the diamond blade. This creates an IMPROVED VISUAL IMPACT FOR YOUR SHOWROOM!



“

We have a very large showroom with many vendors, the Norton Clipper point-of-purchase display is the center of attention. It's bright, well organized and features all our fastest moving items. We call it our silent sales person – as customers browse the store they are attracted to the large display and pick the right products to do the job and are out quick and back on the job site. Our silent sales person is so effective that our biggest challenge is keeping the display full as the Norton Clipper products fly off the hooks. Our sales from the point-of-purchase display are incredibly strong; this maximizes our turns and earns. If we didn't have such a great point-of-purchase display our sales of Norton Clipper products wouldn't be as great as they are today.”

– **Unicon Concrete Specialties,**
Edmonton, Alberta Canada

”

DON'T LEARN **SAFETY GUIDES** BY ACCIDENT!

SAFETY IS EVERYONE'S JOB

Make the safety of yourself and your team a priority on every job site and learn the proper use and function of all your Norton Clipper products and equipment.



Breakages/Personal Injury

In the event of on-machine breakage of Norton Clipper abrasive products, call your local Norton Clipper Distributor immediately. Whether involving personal injury or not, the user should leave the equipment and other evidence undisturbed until a Norton Clipper Sales Representative has been notified and conducts an investigation. Prompt action on the part of product user, Distributor and Norton Clipper sales personnel is important to ensure swift determination of the breakage cause and to guard against recurrence.

Safe Operating Practices

Safe operating practices must be part of every grinding wheel user's operation. The greatest efficiency and lowest overall abrasive/diamond cost can be realized only if proven care and use techniques become standard practice.





- Be sure to read any safety material/ guidelines provided with the abrasive product.
- Always check the wheel for cracks or damage before use.
- Before mounting the wheel, use a tachometer to measure the spindle speed.
- Ensure the mounting flanges, backplate or adapter supplied by the machine manufacturer are used and kept in good condition. ANSI Safety Requirement B7.1 provides wheel mounting requirements. Check mounting flanges for equal and correct diameter and use blotters when supplied.
- Always mount, true and dress the wheel in conformance with the guidelines published in the ANSI Safety Requirements B7.1.
- Ensure the correct wheel guard is in place before starting the wheel. Allow the wheel to come up to full operating speed before starting to grind for a minimum of one minute, and stand out of the plane of rotation.
- NEVER use a high-speed air sander as a portable grinder.
- NEVER use a high-speed air sander as a portable grinder.
- NEVER exceed the maximum operating speed marked on the wheel being used. The following formula may be used to calculate wheel speed:
SFPM = Spindle Speed in RPM x Wheel Dia. in inches x .262
- Avoid dropping or bumping the wheel.
- When not using the wheel, store the wheel in its original packing materials. This protects the wheel from chips and cracking, as well as provides easy identification of the wheel.

For more information on product safety, ask your Norton Distributor for these publications:

- "Primer on Grinding Wheel Safety" (form 474)
- Portable Grinding Safety (form 1406)
- ANSI B7.1 "Safety Requirements for the Use, Care and Protection of Abrasive Wheels"
- Material Safety Data Sheets
- Other applicable regulations

UAMA Approved Safety Icons

The UAMA has approved a new set of standardized icons to be used throughout the Abrasive industry to convey safety information to the users. Below are the approved icon types and their definitions.

ICON TYPES	EXAMPLE
Safety Icon: A pictorial whose purpose is to relay safety related information to the user.	
Hazard Alert Icon: This type of safety icon conveys information primarily related to the nature of a hazard. It contains a graphical depiction of the hazard drawn within a yellow equilateral triangle.	
Prohibition Icon: This type of safety icon conveys actions that should not be taken. It consists of a red circular band with a 45° diagonal red band from upper left to lower right. The icon contains a black depiction of what should not be done within the red band on a white background.	
Mandatory Action Icon: This type of safety icon conveys actions that should be taken to avoid hazards. It consists of a white image within a solid blue or black circular surround shape.	
Proper Machine Use Icon: This type of icon is designed to show the use of the wheel on a proper machine. The icon can be a bit more realistic to show components such as a safety guard and an auxiliary handle. The recommended angle of use may also be depicted.	

ICON	MEANING	ICON	MEANING
	Improper use may break wheel and cause serious injury or death.		Always use wheel guard for angle grinder.
	No side grinding. Cutting only.		Always use wheel guard for non-portable machine.
	No side grinding. Cutting only		Protect your eyes.
	No cutting. Side grinding only.		Protect your face.
	No cutting. Side grinding only, grouped icon.		Protect your lungs against dust.
	Do not use a damaged wheel.		Protect your hearing.
	Do not use on High-Speed Gas Saws.		Protect your eyes and face.
	Do not use on Angle Grinders.		Protect your eyes and hearing. Combined icon.
	Do not use on die grinders		Protect your eyes, ears and lungs.
	Warning alert symbol.		Protect your hands.
 safety.uama.org	Read OSHA and ANSI B7.1. Visit the industry safety page: www.safety.uama.org		Use matched diameter, relieved flanges.

Silica and What You Need to Know

Background and Health impacts

Silica (SiO₂) is one of the most common minerals in the earth's crust. Glass, beach sand, silicone and granite are all "silica" materials. Products containing silica have been used for thousands of years in building and is a key ingredient in many products we use every day. There are two forms of silica; crystalline and non-crystalline. Crystalline silica is a mineral that occurs in several forms. Quartz, the most common form, is a component of sand, stone, rock concrete, brick, block and mortar. Non-crystalline silica is found in glass, silicon carbide and silicone.

When rocks containing crystalline silica are cut, crushed, ground, drill or used in similar industrial processes, dust particles are produced. These particles are very fine, at least 100 times smaller than ordinary beach sand – known as respirable crystalline silica or RCS. Inhaling very small or respirable crystalline silica particles is most hazardous and may cause multiple diseases such as silicosis, followed in severe cases by lung cancer.

Who is at risk from exposure to crystalline silica?

It is estimated that 2.3 million workers are exposed to crystalline silica on the job. The majority of the workers, about 2 million, are in the construction industry. The hazard exists when specific activities create respirable dust that is released into the air.

The New OSHA Standard

OSHA's recently implemented silica standards for Construction "29 CFR 1926.1153" and General Industry "29 CFR 1910.1053" suggests procedures applicable for work in these environments. This new standard affects all activities that generate silica dust on a jobsite. Trades involving brick, stone, concrete and other materials that are difficult to replace must comply with the standard. This is a change around "process", not specific products.

Impacts on Industry

Industries affected by this regulation include Construction, Glass manufacturing, Pottery products, Structural clay products, Concrete products, Foundries, Cut stone and Stone products, Railroads, Refractory products and Asphalt products manufacturing to name a few. Always read the Safety Data Sheet for the workpiece and abrasive before use.


The Occupational Safety and Health Administration (OSHA) has a number of available resources to help companies understand the general information and requirements to explain the new regulations including:

OSHA's Crystalline Silica Rule: Construction
<https://www.osha.gov/Publications/OSHA3681.pdf>

OSHA Fact Sheet
<https://www.osha.gov/publications/OSHA3682.pdf>

Small Entity Compliance Guide for Respirable Crystalline Silica Standard for Construction
<https://www.osha.gov/publications/OSHA3902.pdf>

Small Entity Compliance Guide for Respirable Crystalline Silica Standard for General Industry and Maritime
<https://www.osha.gov/publications/OSHA3911.pdf>



How Diamond Blades Work

Since they do wear down in use, diamond blades are actually “grinding wheels” with diamond particles as the abrasive agent. Individual diamond particles remove material by “scratching out” particles of hard, dense substances, or by “knocking out” larger particles of loosely bonded, abrasive material during the cutting operation.

Although diamonds are the hardest substance in the world, these diamond particles do wear out or break down after cutting for a period of time. New, untouched diamonds are, however, exposed by the wearing down of the metal “bond.”

Large particles of soft, abrasive materials wear down this metal bond faster than the small particles removed from hard, dense materials. Because of this, a diamond blade for cutting a soft, abrasive material must have a hard metal bond to resist this erosion long enough for the exposed diamonds to be properly utilized. Conversely, a soft bond is needed to ensure that it will erode and expose new diamonds, allowing the blade to continue cutting efficiently.

Years of experience and development have given us a vast number of bonds of different hardness levels for different levels of “Controlled Bond Erosion” for all masonry and concrete materials.

How to Mount Diamond or Abrasive Blades

1. Using the blade shaft wrench supplied with the saw, loosen and remove the blade shaft bolt and remove collar. Be sure blade shaft collars and arbor are free of dirt and all foreign materials before mounting blade on the shaft. **TIGHTENING AN ABRASIVE BLADE AGAINST AN UNEVEN SURFACE COULD FRACTURE THE BLADE** or cause blade to run out of alignment, causing excessive blade wear, and/or unsafe sawing conditions.
2. Place the blade on the arbor. Attach loose collar and tighten the blade shaft bolt securely. When tightening bolt against outside blade shaft collar, be sure to tighten enough to hold the blade firmly without slipping, but do not over tighten. **EXCESSIVE TIGHTENING CAN CAUSE AN ABRASIVE BLADE TO FRACTURE.**

How to Use Your Masonry Saw for Dry Cutting

1. Use a proper blade which is clearly marked for dry cutting.
2. Remove water curtain.
3. Disconnect the electric water pump.
4. Use “Step Cutting” as explained previously when using wet or dry cutting diamond blades or abrasive blades.
5. Dry cut only in large open areas with adequate ventilation.

How to Use Your Masonry Saw for Wet Cutting


Water may be supplied either by filling the water pan to within 1/2” of top, or for a continuous flow of clean water use a barrel. When using water from barrel, remove water pump from pan and submerge it in water barrel. Remove the drain plug so the used water and sludge will drain from pan.

1. Prepare water supply.
2. Install water curtain on cutting head pivot bar.
3. Be sure the water pump is plugged into the connection on the masonry saw motor. (It will start when the main switch is turned on.)
4. Handle on petcock should be turned in line with the water flow. Start motor and be certain that both sides of the blade are getting an adequate flow of water.
5. At all times make sure that the water level covers the screen on the bottom of the pump. Do not let sludge and dirt get deep enough in the pan to block the pump inlet.
6. Use “Step Cutting” with abrasive blades as previously described.
7. Use “Jam Cutting” or “Step Cutting” with diamond blades as previously described.

How to Use “Jam Cutting” (Fixed Cutting) and “Step Cutting” With Diamond Blades

In “Jam Cutting,” the cutting head is locked in a fixed position and the material is pushed into the blade as shown in Figure 1. “Jam Cutting” with the cutting head locked in position usually provides greater efficiency than merely holding the head down.

“Jam Cutting” works well with wet diamond blades cutting some soft materials. It is less efficient overall than the “Step Cutting” method for most material, especially when using dry diamond or abrasive blades.



1. To lock the head into position, tighten lever nut at back of saw or lower the cutting head to desired cutting depth, depending on the model saw you are using.
“Step Cutting” with diamond blades is done by applying more pressure to blade and making a deeper cut. Unlike “Step Cutting” with abrasive blades, “Step Cutting” with diamond blades requires only a few passes through the material.
2. In cutting, clamp the material securely or hold it firmly against the conveyor cart backstop. **IF THE MATERIAL IS ALLOWED TO SLIP, RESULTING SEIZURE OF THE BLADE MAY BEND THE DIAMOND BLADE CENTER OR CAUSE A RIM SECTION TO BE TWISTED OFF.**
3. Do not force the material or bump into the blade. **WHEN NEARING COMPLETION OF THE CUT, RETARD AND SLIGHTLY HOLD BACK THE CONVEYOR CART.** If this is not done, the material may be pulled into the blade so fast that excessive pressure on the rim may cause warping or twisting of the rim section.
4. When a new diamond blade is broken in, make the first few cuts slowly until the blade cuts freely and easily.
5. When the blade is cutting freely and easily, **USE IT!** As long as it cuts satisfactorily, do not dress the diamond blade or remove it from the blade shaft.
6. After continuous cutting of extremely hard and dense materials, the blade may slow down and it may be necessary to “dress” the cutting edge. To do this, make a few rapid, shallow cuts using the “Step Cutting” method. If this is not sufficient, then make one or two cuts in a soft abrasive light weight block.

Concrete and Asphalt Sawing Methods

In concrete and asphalt cutting operations, the usual equipment used are 8 to 65HP flat saws.

Asphalt cutting and the cutting of asphalt overlaid concrete should not be considered the same type operation from a blade recommendation standpoint. In the case of asphalt overlay, the application involves cutting both asphalt and cured concrete which gives a different abrasive level than the cutting of asphalt alone.

Generally, the cutting of asphalt overlaid concrete is done at full depth with blades less than 18" in diameter as long as the asphalt is more than 1/3 the total depth of cut. Standard recommended specifications for asphalt overlaid concrete should be employed until the depth of the asphalt reaches 50% of the total cut. At this point, harder blades should be used which would increase the blade life.

The larger diameter blades, 18" and above, are used in a step cutting method at cutting depths of 2" and 3" in short travel distances of 15' to 20'. This allows the blade to remain in a free cutting condition and does not slow down the cutting operation. Asphalt cutting is primarily performed at full depth. However, if the aggregate used in asphalt is larger than .750 in diameter and/or is quartz or chert aggregate, the cutting operation may have to be modified to a step cutting operation.

Green Concrete Sawing Methods

Green concrete is cut to control cracking in large concrete pours. Usually saws from 5 HP to 65 HP are used for this purpose, depending on the size of the job. The initial sawing of the concrete is done within a 24 hour period at a depth of 1/3 to 1/4 of the total concrete thickness. Generally 6" to 14" blades are used with .110" through .150" widths.

After the initial cut has been made, the joint may require additional widening for the backing rod and/or sealant. This requires a blade diameter of 12" or 14" in widths up to .500".

Concrete Deep Sawing Methods

Generally, deep sawing of cured concrete is done using high horsepower concrete saws and blades above 20" in diameter. 65 HP concrete saws are used in conjunction with 24", 30", and 36" diameter blades to obtain the desired depth of 8" to 14" (this is usually the standard thickness of concrete highways in North America). The blades are usually used at approximately 12,000 surface feet per minute (outside rim speed of the blade).

The use of these blades is usually dictated by the hardness of the aggregates contained in the concrete. A cutting rate of 4' to 6' per minute is the speed of cut most operators prefer. This cut rate is usually directly related to the depth of cut. In areas with hard aggregate, it is common to make multiple passes of 2" to 3" deep until desired full depth of cut is reached. Softer aggregates can be cut using deeper passes without sacrificing cutting speed.

Core Drilling Methods

The performance of any diamond core bit depends heavily on the use of proper drilling techniques. Although drilling conditions and materials may vary, following specific guidelines ensures faster drilling speed and longer bit life.

1. Secure the core drill to the work surface so that there is no movement in the drill that would allow the bit to bind in the hole.
2. Use a sufficient supply of water to ensure that hole is constantly being flushed of abrasive cuttings.
3. Slowly lower the bit into the cut so that there is no skidding or lateral movement of the drill bit. The entire circumference of the core bit should penetrate the drilling surface before additional pressure is applied to the handle.
4. Exert steady downward pressure on the bit while drilling. Do not force the bit into the material.
5. Do not stop the flow of water or the rotation of the bit as long as the bit is in the hole.
6. If the drilling rate decreases noticeably, check the core bit. The slower penetration rate generally means that the bit is dull and needs to be reconditioned.

Concrete Saw Safety Precautions

IMPORTANT: FOR COMPLETE SAFETY INFORMATION, REFER TO ANSI SAFETY CODE B7.1 AVAILABLE THROUGH THE AMERICAN NATIONAL STANDARDS INSTITUTE.

IMPORTANT: CONSULT THE MANUFACTURER OF THE HIGH-SPEED HAND-HELD SAW FOR APPROPRIATE SAFETY INFORMATION, AS WELL AS ANSI B7.5.

THE FOLLOWING SAFETY PRECAUTIONS MUST BE OBSERVED.

1. Before mounting any blade on the saw, the blade should be inspected= for any damage that might have occurred during shipment, handling or previous use.
2. The blade shaft collars must be of proper diameter for the size blade being used. The drive pin must be located in the tight collar or the loose pin, and arbor should be cleaned and examined for damage before mounting the blade.
3. The blade must be properly fitted over arbor and drive pin. Drive pin must project through hole in blade and into collar. Do not force the blade onto arbor.
4. Disconnect spark plugs and use the blade shaft lock pin when tightening the blade shaft nut. Tighten the blade shaft nut securely against the outside blade shaft collar. The blade shaft has left hand threads on the right side of the saw and right hand threads on the left side of the saw.
5. The blade guard must always be in place when the saw is running. Always use a proper size blade guard for the size blade being used.
6. The operator should wear safety glasses and appropriate safety equipment at all times.
7. Never leave saw unattended while engine is running.
8. Always secure saw from rolling when not in use.
9. Do not stop the engine on a self-propelled saw while on a grade.
10. When stopping any saw on a grade, the wheels must be chocked.
11. When starting the saw, the operator should stand away from and to the side of the blade.
12. If for any reason the blade stalls in the cut, raise the blade out of the cut and check the outside blade shaft collar and nut for tightness before restarting the engine. Inspect the blade for damage. Use care when resuming a cut. Make certain that the blade is in alignment with the previous cut.
13. During cutting, do not exert excessive side pressure on the handles as a method of steering. Do not force the blade into material by lowering the blade too quickly or by increasing the speed of the saw.
14. Adequate coolant must be used when sawing with wet cutting abrasive or diamond blades. Gravity feed does not supply a sufficient water flow. The water pumps on concrete saws are "booster" pumps only and are not adequate as primary pressure source. An adequate coolant supply is required for wet cutting blades to maintain blade life and cutting efficiency.
15. The blade shaft must be operated within the specified maximum operating speed.
16. Operate engine at proper RPM. Never alter RPM or governor setting.
17. In case of an EMERGENCY "SHUT OFF ENGINE."

Core Drill Safety Precautions

1. In most cases, core drilling requires the use of water. Properly ground the core drill, as the use of any electrical tools in wet areas can be hazardous.
2. The three-pronged plug on the power cord of the motor or the extension cord must be plugged into a grounded electrical outlet of the appropriate voltage.
3. The core drill must be securely fastened to the intended work surface (wall, deck, etc.), using anchor bolts, vacuum pad or jack screw.
4. Use extreme caution when drilling through floors. Check for electrical conduit.
5. Provide protection for all personnel and materials below the areas being drilled.

Masonry Saw Safety Precautions

The following is a list of safety practices which must be observed when sawing with masonry saws:

1. Keep the area around the saw free from debris which could cause falls.
2. Prohibit the use of the saw by unauthorized or untrained personnel.
3. Keep the conveyor cart free of grit and debris which could allow the material to slip or twist during cutting operations.
4. Hold the material firmly against the backstop of the conveyor cart or guide-a-cut, keeping fingers out of the path of the blade.
5. Position the saw on a firm, flat area and be sure that the saw will not move in use.
6. Replace blade collars if they become worn to less than 4" diameter for 18" and 20" blades, or less than 3 1/2" diameter on 14" blades.

Diamond Blade Safety – Do's & Don'ts

All manufacturers of diamond blades are very concerned that their products are used in a safe manner. **The following is a list of Do's and Don'ts for concrete and masonry sawing.** This is provided with the intention of eliminating hazardous conditions or practices. Please take time to read and understand its principles.

Wet Cutting Do's & Don'ts

1. **Do** follow manufacturer's recommended blade specifications for material to be cut.
Don't use a diamond saw blade without checking manufacturer's recommendations for the material to be cut. Improper selection can cause excessive blade wear and possible damage to the diamond saw blade and/or machine, and create an unsafe operating condition.
2. **Do** inspect the diamond blade for damage that may have occurred during shipment or damage due to previous use.
Don't use a new diamond saw blade or remount a used blade which has a core that is not flat or is cracked, which shows segment damage or loss, or which has a damaged arbor hole.
3. **Do** check mounting flanges for equal diameter, excess wear and flatness. Mounting flanges must have adequate relief around arbor hole.
Don't use mounting flanges on which the bearing surfaces are not clean and flat.
4. **Do** be sure that the diamond saw blade is mounted on a correct diameter blade shaft between proper blade flanges and is securely hand-tightened with a wrench.
Don't force blade onto machine blade shaft or mount blade on undersized blade shaft. Either condition can result in unsafe operating conditions and excessive blade wear.
5. **Do** check the saw for proper operating conditions:
 - A. All fluids are at proper levels.
 - B. Blade shaft bearings should be free of end and radial play.
 - C. V-belts should be properly tensioned and pulleys checked for excessive wear.
 - D. Lead off adjustment is set correctly, to allow the blade to travel straight.
 - E. Do operate with blade guard in place and properly secured.**Don't** mount blade on machine that does not meet the minimum requirements set forth in the manufacturer's machine operating manual.
6. **Do** be sure there is a continuous water flow to each side of the blade. Gravity feed does not supply a sufficient water flow. The water pumps on concrete saws are "booster" pumps only and are not adequate as a primary pressure source. An adequate coolant supply is required for wet cutting blades to maintain blade life and cutting efficiency.
7. **DO FOLLOW THE MANUFACTURER'S RECOMMENDED PULLEY SIZES AND OPERATING SPEEDS. FOR SPECIFIC BLADE DIAMETERS, REFER TO MANUFACTURER'S OPERATING MANUAL.**
8. **Do** operate the saw with proper safety attire, i.e., safety glasses, safety helmet, safety shoes and hearing protection.
9. **Do** examine blade periodically for cracks in the steel center or segments, or excessive wear under the segments.

Dry Cutting Do's & Don'ts

1. **Do** follow manufacturer's recommendation regarding specification for material to be cut and suitability for dry cutting applications.
Don't cut dry except with a blade specifically designated for dry cutting by the manufacturer.
2. **Do** inspect the diamond saw blade for damage that may have occurred during shipment or damage due to previous use.
Don't force blade onto machine blade shaft, alter the size of the mounting hole, or tighten mounting nut excessively. The use of bushings to reduce the arbor hole size is not recommended for diamond blades used on high-speed saws.
3. **Do** inspect the diamond blade periodically during use for core flatness, fatigue cracks, segment damage, undercutting and damage to the arbor hole.
Don't exceed the maximum operating speed established for the diamond blade.
4. **Do** check the mounting flanges to be sure that they are of equal or correct diameter, that they do not show excessive wear, and that they are flat.
Don't operate a saw without proper safety guards in place. NEVER OPERATE ANY SAW, WET OR DRY, WITHOUT A BLADE GUARD!
5. **Do** be sure that the diamond blade is mounted on a correct diameter blade shaft between proper blade flanges and is securely hand tightened with the wrench provided or an adjustable wrench no longer than 8".
Don't stand in direct line with dry diamond or abrasive blades during start-up or operation.
6. **Do** check for proper saw machine conditions. Spindle bearings should be free of end and radial play. Consult the operating manual from the saw manufacturer for proper machine maintenance conditions.
Don't cut or grind with the sides of a diamond blade.
7. **Do** follow the manufacturer's recommendation for operating speeds for specific blade diameters.
Don't force the blade into the material; allow the blade to cut at its own speed. Forcing the blade may cause overheating or blade damage.
8. **Do** maintain a firm grip on hand-held saws during cutting operation.
Don't make long continuous cuts with a dry diamond blade. Allow the blade to cool by turning in air every few minutes. The harder the material being cut, the more often the blade should be allowed to cool.
9. **Do** wear proper safety equipment at all times. Always wear safety glasses, safety footwear, snug fitting clothing, hearing and head protection, and respiratory equipment where required.
Don't use the blade to cut material other than that recommended by the manufacturer for that specific blade type.
10. **Don't** use the blade on a type of saw other than that specified by the manufacturer.
11. **Don't** allow the blade to deflect in the cut.
12. **Don't** attempt to cut curves or radii.



HIGH-SPEED HAND SAW BLADES

Maximum Blade
Cutting Depths and
Recommended
Operating Speeds

BLADE DIAMETER	CUTTING DEPTH	MAX. SPEED (RPM)
12"	4"	6,300
14"	5"	5,460
16"	6"	4,500



CONCRETE SAW BLADES

Maximum Blade
Cutting Depths and
Recommended
Operating Speeds

BLADE DIAMETER	CUTTING DEPTH	IDEAL SPEED (RPM)	MAX. SPEED (RPM)
7"	1-1/2"	5,184	8,730
8"	2"	4,536	7,640
12"	3-5/8"	3,024	5,095
14"	4-5/8"	2,592	4,365
16"	5-5/8"	2,268	3,820
18"	6-5/8"	2,016	3,395
20"	7-5/8"	1,814	3,055
24"	9-5/8"	1,512	2,550
26"	10-5/8"	1,396	2,350
30"	11-3/4"	1,120	2,040
36"	14-3/4"	1,008	1,700
42"	17-1/2"	864	1,455
48"	19-3/4"	756	1,275



ABRASIVE BLADES AND WHEELS

Maximum Recommended
Operating Speeds

BLADE DIAMETER	TYPE 1 CUT-OFF WHEELS	HIGH-SPEED BLADES	TYPE 27 AND 28 WHEELS	TYPE 11 CUP WHEELS
4"	19,000		15,000	9,050
4-1/2"	13,300		13,300	
5"	12,000		12,000	7,255
6"	10,000		10,000	6,050
7"	8,600		8,600	
8"	7,500			
9"	6,800	6,800	6,800	
10"	6,110			
12"	5,095	6,300		
14"	4,365	5,400		
16"	3,820	4,500		
18"	3,395			

NOTE: Diamond blade cutting depths listed are approximate. Actual cutting depth will vary with the exact blade diameter or saw type, or the exact diameter of the blade flanges. Cutting depth will also be reduced if saw components extend below the blade flanges.



MASONRY BLADES

Maximum Blade
Cutting Depths and
Recommended
Operating Speeds

BLADE DIAMETER	CUTTING DEPTH	IDEAL SPEED (RPM)	MAX. SPEED (RPM)
14"	5"	2,592	4,365
18"	7"	2,016	3,395
20"	8"	1,814	3,055
24"	10"	1,512	2,550



TILE SAW BLADES

Maximum Blade
Cutting Depths and
Recommended
Operating Speeds

BLADE DIAMETER	CUTTING DEPTH	IDEAL SPEED (RPM)	MAXI. SPEED (RPM)
4"	3/4"	9,072	15,000
4-1/2"	1"	8,063	13,300
5"	1-1/4"	7,257	12,000
6"	1-3/4"	6,048	10,185
7"	2-1/4"	5,184	8,730
8"	2-3/4"	4,536	7,640
9"	3-1/4"	4,032	6,790
10"	3-3/4"	3,629	6,115



CORE BITS

Minimum and Maximum
Recommended Operating
Speeds

BIT DIAMETER	MIN. (RPM)	IDEAL SPEED (RPM)	MAX. (RPM)
1"	2,400	3,200	4,000
2"	1,200	1,600	2,000
3"	800	1,050	1,300
4"	600	800	1,000
5"	475	640	800
6"	400	530	665
7"	340	450	600
8"	300	400	500
10"	240	320	400
12"	200	265	330
14"	170	225	285
16"	150	200	250
18"	130	175	220
20"	120	160	200
24"	100	130	165
26"	90	125	150
30"	80	105	130
32"	75	100	125
34"	70	95	120
36"	65	85	110
40"	60	80	100
42"	55	75	95



Extension Cord Size Recommendations

3 Phase Motor

TOOL HP	AMPS	VOLTAGE	>50'	50' – 100'	100' – 150'	150' – 200'
5	12	230v	#14	#12	#10	#8
5	6	460v	#14	#14	#12	#10
10	24	230v	#10	#8	#6	#4
10	12	460v	#14	#12	#10	#8
20	52	230v	#6	#6	#4	#2
20	26	460v	#10	#8	#6	#4
25	58	230v	#6	#6	#4	#2
25	29	460v	#10	#8	#6	#4
30	37	460v	#8	#6	#4	#2
40	48	460v	#8	#6	#4	#2
50	62	460v	#4	#4	#2	#0



Extension Cord Size Recommendations

1 Phase Motor

TOOL HP	AMPS	VOLTAGE	>50'	50' – 100'	100' – 150'	150' -200'
1/3 – 1/4	7	125v	#18	#18	#16	#14
1/2	10	125v	#18	#16	#14	#12
3/4	13	125v	#16	#14	#12	#10
1	15	125v	#14	#12	#10	#8
1-1/2	20	125v	#12	#10	#8	#6
1-1/2	13	115v	#12	#10	#8	#6
1-1/2	6	230v	#14	#14	#12	#10
2	30	125v	#8	#6	#4	#2
2-1/2	21	115v	#10	#8	#6	#4
2-1/2	11	230v	#14	#12	#10	#8
5	23	230v	#10	#8	#6	#4
7-1/2	33	230v	#8	#8	#6	#4

technical expertise WITH BREAKTHROUGH TECHNOLOGIES



Infiltrated High-Density (iHD) technology achieves high uniform density across each whole segment without applying high pressure like the standard segment process. It processes a robust segments that wear evenly, remain intact, and perform faster at higher cutting speeds.



The Norton Clipper CP500 High-Speed Cut-Off Saw. The patented **iLube®** option automatically controls mixing of oil and fuel for maximum efficiency. An electronic sensor will indicate a low oil level and adjust the engine to idle to prevent engine damage.



Norton Universal Arbor design allows a blade to be adaptable to two different arbor mounts. A knock-out bushing design creates flexibility to use one blade on two machines.



The steel core design of **Norton Clipper Silencio** provides an unprecedented noise-dampening effect on the job site of up to 15dB for 30 times less noise. The revolutionary design drastically reduces the high-pitched whistling effect on masonry and floor saws which is ideal for areas with local regulations sensitive to noise.




In the early 80's, Norton revolutionized the diamond blade market by developing the process of **laser welding** diamond segments to the steel center. This allowed, for the first time, laser-welded diamond products to cut dry on a very wide range of masonry and construction materials while returning exceptional speed of cut and long life when compared with conventional abrasive blades.



The unique laser-welded gullets, split segment design of the **Norton Clipper DUO**, and ellipsoidal shaped gullets of the **Norton Clipper 4X4, 4X4 MaxCut** and **3X3** substantially increase product safety, provide smooth cuts, and help remove debris from the cutting area. Both patented gullets increase cutting speed and life of the blade.



Norton Clipper C1318P Small Push Saw has been redesigned with the operator in mind while maintaining robustness and functionality synonymous with the Clipper name. **Anti-Vibe Handlebars** reduce hand/arm vibration up to 40%.





Norton depth cut indicators easily controls the operator's depth of cut for elimination of over-cutting, resulting in improved job performance. The steel center is permanently marked with patented slots that combine the direction of rotation and depth indicators. As the blade revolves, the depth of cut can be seen through the stroboscopic effect.



Visit Us Online 24/7

Our website continues to evolve in order to provide fuller content with enhanced product information and application solutions. This catalog is a great starting resource for Norton Clipper product selection, but the website is the ideal resource for a more comprehensive product outline which is continually updated with all our most current information, and offers more electronic queries for deeper detail, at a click of a button: www.nortonabrasives.com

Building & Construction page:
www.nortonsga.us/NortonClipper



Trademarks

All trademarks used in this catalog are the property of Saint-Gobain, unless otherwise indicated.

3X3™

4X4™

4X4™ MaxCut™

Aero-Jet™

Blockbuster®

Charger™

Classic™

Clipper®

Dialast™

DUO®

DUO® EVO™

GMAX™

iHD®

Norton®

Paradigm®

Rescue Runner™

Slicer™

Speedy Cart™

StableStart®

ValuPlus™


Redefining Jobsite Muscle™

Reshaping Your World®


[illegible]

NORTON

SAINT-GOBAIN

clipper®**REDEFINING
JOBSITE MUSCLE™****General Purpose and Masonry Building Materials**


Blocks, medium-hard building bricks, paving slabs, concrete roof tiles and other medium hard materials.

**Natural Stone and Tiles**

Ceramic and stone tiles, granite, marble, very hard bricks and other very hard and dense materials.

**Rescue, Demolition**

Ductile, steel, polyvinyl pipe, thin steel plate, acrylic sheet, fiberglass, rubber, standard glass, wood, concrete, brick, asphalt.

**Asphalt and Abrasive Materials**

Asphalt, green concrete, asphalt over concrete, abrasive blocks, mortar and other abrasive materials.

**Reinforced Concrete and Harder Building Materials**

Reinforced concrete, hard bricks, limestone, terrazzo and other hard materials.

**All Materials
Ductile Iron Pipe**

Concrete, reinforced concrete, asphalt over concrete, granite, building materials, thin steel sections, ductile iron pipes, angle iron up to 1/2" material thickness, rebar up to no. 5.

**Steel & Stainless**

General-purpose ferrous metals (steel, iron, welds), stainless steel and other high-strength alloys.


www.facebook.com/NortonAbrasivesNA | www.youtube.com/NortonAbrasives | www.nortonabrasives.com
USA CUSTOMER SERVICE:Toll Free Phone: 1 (800) 554-8003
Toll Free Fax: 1 (800) 443-1092**CANADA CUSTOMER SERVICE:**Toll Free Phone: 1 (800) 263-6565
Toll Free Fax: 1 (800) 561-9490**FORM #7719** REV. 03/23

© Saint-Gobain March 2023.

Norton and Norton Clipper are registered trademarks of Saint-Gobain Abrasives.

