

# Leader MultiChuck MMY Concentric Clamping Systems Technology

## MULTICHUCK MMY CONCENTRIC CLAMPING SYSTEM

The Leader MultiChuck MMY product line consists of manual self-centering static workholding for machining centers, milling machines and grinders. These chucks integrate with Kurt's high density workholding towers and other devices to provide the ultimate in high productivity and high precision workholding.

MultiChuck MMY provides a simple top face operation that enables more chucks, and therefore workpieces, to be 'banked' closely together–which is not the case with the traditional side face lock/unlock systems.



## **MultiChuck Details**

Available with two or three jaws. Standard jaw strokes are 0.157", 0.196", 0.314" and 0.393" across the four variants, and the low height from 0.984" to 1.575" maximizes the machine's Z axis (height can be increased using blocks). Quick change top jaws can be supplied to suit most materials/components. Jaws are sold separately – for more information visit us online at www.kurtworkholding.com

Repeatability for all 2 & 3 Jaw chucks is 0.0002".

MultiChuck MMY can be provided as standard in a range of chuck sizes - 80mm, 100mm, 125mm and 150mm. Base dimensions are: 3.149" x 3.149", 3.937" x 3.937", 4.921" x 4.921" and 5.905" x 5.905". MultiChuck MMY will fit all slotted machine tables.

MultiChuck MMY is capable of external and internal clamping and will satisfy both first and second operations in the same machining cycle - thereby providing continuous output of finished components.

## Ask us about our custom pallet and tombstone systems.

Three Jaw Style MultiChuck MMY. Top Jaws are Sold Separately.



Two Jaw Style MultiChuck MMY. Top Jaws are Sold Separately





Accessories: Jaws, T-wrenches & Boring Rings. See back page for available accessories.



# LEADER MULTICHUCK MMY SPECIFICATIONS

MultiChuck MMY Dimensions								
Key	80	100	125	150				
A	3.149"	3.937"	4.921"	5.905"				
В	0.984"	1.181"	1.378"	1.575"				
С	0.551"	0.551"	0.551"	0.551"				
G	2.362"	3.149"	3.937"	4.724"				
x	1.142"	1.850"	2.323"	2.598"				
Y	0.984"	1.181"	1.378"	1.575"				
z	0.709"	1.063"	1.260"	1.457"				





Jaws are sold separately.

Visit Us Online at www.kurtworkholding.com for more information.

**Top View** 



Specifications - MMY Standard Models, External and Internal Clamping											
Chuck	Chuck Size No. o		No. of	Jaw Stroke		Max Input Torque		Max Clamp Force		Chuck Weight	
Model	inch	mm	Jaws	inch	mm	ft-lb	N-m	lb	kN	lb	kg
MMY-80-3	3.15	80	3	0.095	2.4	15	20	1,010	4.5	2.4	1.1
MMY-80-2	3.15	80	2	0.095	2.4	10	14	670	3.0	2.4	1.1
MMY-100-3	3.93	100	3	0.106	2.7	18	25	1,460	6.5	4.5	2.0
MMY-100-2	3.93	100	2	0.106	2.7	12	17	960	4.3	4.5	2.0
MMY-125-3	4.92	125	3	0.236	6.0	22	25	2,590	11.5	8.2	3.7
MMY-125-2	4.92	125	2	0.236	6.0	15	17	1,710	7.6	8.2	3.7
MMY-150-3	5.91	150	3	0.325	8.25	22	30	3,260	14.5	12.7	5.8
MMY-150-2	5.91	150	2	0.325	8.25	15	20	2,160	9.6	12.7	5.8

• Chucks are convertible to wide opening model by changing out the cam plate.

• 1-1/2 revolutions for entire stroke.



#### MMY Wide Opening Models

MultiChuck MMY combines fast initial jaw travel with controlled second-stage clamping to provide a large jaw opening with high gripping force.

Specifications - MMY Wide Opening Models (OD Clamping Only)													
Chuck	Chuck Size		No. of	<b>Clamping Stroke</b>		<b>Opening Stroke</b>		Max Input Torque		Max Clamp Force		Chuck Weight	
Model	inch	mm	Jaws	inch	mm	ft-lb	N-m	ft-lb	Nn	lb	kn	lb	kg
MMY-80-3/W	3.15	80	3	0.063	1.6	0.252	6.4	15	20	1,010	4.5	2.4	1.1
MMY-80-2/W	3.15	80	2	0.063	1.6	0.252	6.4	10	14	670	3.0	2.4	1.1
MMY-100-3/W	3.93	100	3	0.071	1.8	0.323	8.2	18	25	1,460	6.5	4.5	2.0
MMY-100-2/W	3.93	100	2	0.071	1.8	0.323	8.2	12	17	960	4.3	4.5	2.0
MMY-125-3/W	4.92	125	3	0.158	4.0	0.472	12.0	22	25	2,590	11.5	8.2	3.7
MMY-125-2/W	4.92	125	2	0.158	4.0	0.472	12.0	15	17	1,710	7.6	8.2	3.7
MMY-150-3/W	5.905	150	3	0.217	5.5	0.571	14.5	22	30	3,260	14.5	12.7	5.8
MMY-150-2/W	5.905	150	2	0.217	5.5	0.571	14.5	15	20	2,160	9.6	12.7	5.8



# Leader MultiChuck MMY Concentric Clamping Systems Technology

# Jaw Boring Ring

T Wrench Handle



Bolt Set and Locating Dowels



3 Jaw Sets



2 Jaw Sets



#### Kurt<sup>™</sup> Manufacturing

Industrial Products Division 9445 E. River Road NW Minneapolis, MN 55433 Tel: (763) 574-8309 Fax: (763) 574-8313 Toll Free (US Only): 1 (877) 226-7823 Toll Free Fax (US Only): 1 (877) 226-7828 email address: workholding@kurt.com website address: www.kurtworkholding.com

LIT.MMY.BRO.09.12 Printed in USA © Copyright. All rights reserved











#### **MMY Jaw Kits and Accessories**

Part#	Description	Qty per Chuck						
MMY-080								
LA80-150MMY/P32	"T" Wrench Handle	1						
LA80MMY2/P21	Std. Blank 2 Jaw Kit	1						
LA80MMY3/P21	Std. Blank 3 Jaw Kit	1						
LA80MMY3/P25	3 Jaw Boring Ring	1						
LA80MMY2/P20W	2 Jaw Cam Plate-Wide Opening	1						
LA80MMY3/P20W	3 Jaw Cam Plate-Wide Opening	1						
LA80MMY/P24	Chuck Mounting Kit	1						
MMY-100								
LA80-150MMY/P32	"T" Wrench Handle	1						
LA100MMY2/P21	Std. Blank 2 Jaw Kit	1						
LA100MMY3/P21	Std. Blank 3 Jaw Kit	1						
LA100MMY3/P25	3 Jaw Boring Ring	1						
LA100MMY2/P20W	2 Jaw Cam Plate-Wide Opening	1						
LA100MMY3/P20W	3 Jaw Cam Plate-Wide Opening	1						
LA100-150MMY/P24	Chuck Mounting Kit	1						
	MMY-125							
LA80-150MMY/P32	"T" Wrench Handle	1						
LA125MMY2/P21	Std. Blank 2 Jaw Kit	1						
LA125MMY3/P21	Std. Blank 3 Jaw Kit	1						
LA125MMY3/P25	3 Jaw Boring Ring	1						
LA125MMY2/P20W	2 Jaw Cam Plate-Wide Opening	1						
LA125MMY3/P20W	3 Jaw Cam Plate-Wide Opening	1						
LA100-150MMY/P24	Chuck Mounting Kit	1						
MMY-150								
LA80-150MMY/P32	"T" Wrench Handle	1						
LA150MMY2/P21	Std. Blank 2 Jaw Kit	1						
LA150MMY3/P21	Std. Blank 3 Jaw Kit	1						
LA150MMY3/P25	3 Jaw Boring Ring	1						
LA150MMY2/P20W	2 Jaw Cam Plate-Wide Opening	1						
LA150MMY3/P20W	3 Jaw Cam Plate-Wide Opening	1						
LA100-150MMY/P24	Chuck Mounting Kit	1						

• Jaws are made from AISI 1018 Steel

Jaws are made from AISI 1018 Steel
Chuck Mounting Kits Include:
Chuck mounting bolts • Chuck locating bushings
Jaw mounting screws
Warranty is 12 months from date of purchase.
"T" Handle Wrench sold separately.
For Jaw Set Options Visit Us Online at www.kurtworkholding.com

#### Distributor